

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV.
C

AS85049™/54

FEDERAL SUPPLY CLASS
5935

RATIONALE

REVISION IS REQUIRED TO IMPROVE DRAWINGS, MOVE NOTES TO DESIGN PARAGRAPH TO FOLLOW C1 AS STANDARD FORMAT, REMOVE IMAGES, ADD PLASTIC TIE WRAP RESTRICTION TO NOTICE ON FIRST PAGE, CLARIFY RESTRICTIONS, AND ADD AS95234 TO THE DOCUMENT TITLE AND TABLE 1.

NOTICE

THE COMPLETE REQUIREMENTS FOR PROCURING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF AS85049. SEE APPLICATION NOTE 1.





FIGURE 1 - ACCESSORY CONFIGURATION AND DIMENSIONS

For more information on this standard, visit

<https://www.sae.org/standards/content/AS85049/54C>

THIRD ANGLE PROJECTION



CUSTODIAN: AE-8/AE-8C1

PROCUREMENT SPECIFICATION: AS85049



AEROSPACE STANDARD

(R) CONNECTOR ACCESSORIES, ELECTRICAL, STRAIN RELIEF, NONENVIRONMENTAL, 45°, CATEGORY 4C (FOR AS50151 CRIMP, AS9524, MIL-DTL-26482 SERIES 2, AS81703 SERIES 3, AND MIL-DTL-83723 SERIES III CONNECTORS)

AS85049™/54
SHEET 1 OF 3

REV.
C

Copyright © 2021 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

TABLE 1 – FIGURE 1 DIMENSIONS

DASH NUMBER	FOR CONNECTOR SHELL SIZE (REF)				A MAX.	B MAX.	C DIA. MAX.	D MAX.	E MAX.	F MAX. 1/	G MAX.	WIRING ENTRY MAX.
	AS81703 SERIES 3	MIL-DTL- 26482 SERIES 2	AS50151 CRIMP AS95234	MIL-DTL- 83723 SERIES III								
03	3	--	--	--	.790 (20.07)	1.562 (39.67)	.782 (19.86)	1.110 (28.19)	.540 (13.72)	.500 (12.70)	1.232 (31.29)	.260 (6.60)
08	--	8	8S	8	.790 (20.07)	1.562 (39.67)	.657 (16.69)	1.110 (28.19)	.540 (13.72)	.463 (11.76)	1.232 (31.29)	.260 (6.60)
10	--	10	10S,10SL	10	.790 (20.07)	1.562 (39.67)	.782 (19.86)	1.110 (28.19)	.540 (13.72)	.551 (14.00)	1.232 (31.29)	.365 (9.27)
12	7	12	12,12S	12	.790 (20.07)	1.562 (39.67)	.937 (23.80)	1.110 (28.19)	.540 (13.72)	.644 (16.36)	1.232 (31.29)	.501 (12.73)
14	12	14	14,14S	14	.790 (20.07)	1.562 (39.67)	1.050 (26.67)	1.200 (30.48)	.540 (13.72)	.738 (18.75)	1.232 (31.29)	.575 (14.61)
16	19	16	16,16S	16	.790 (20.07)	1.562 (39.67)	1.239 (31.47)	1.200 (30.48)	.540 (13.72)	.834 (21.18)	1.232 (31.29)	.700 (17.78)
18	27	18	18	18	.790 (20.07)	1.562 (39.67)	1.378 (35.00)	1.300 (33.02)	.540 (13.72)	.914 (23.22)	1.232 (31.29)	.779 (19.79)
20	37	20	20	20	.790 (20.07)	1.812 (46.02)	1.500 (38.10)	1.300 (33.02)	.540 (13.72)	1.00 (25.40)	1.482 (37.64)	.904 (22.96)
22	--	22	22	22	.790 (20.07)	1.812 (46.02)	1.631 (41.43)	1.400 (35.56)	.540 (13.72)	1.10 (27.94)	1.482 (37.64)	1.029 (26.14)
24	--	24	24	24	.790 (20.07)	1.812 (46.02)	1.750 (44.45)	1.400 (35.56)	.540 (13.72)	1.20 (30.48)	1.482 (37.64)	1.144 (29.06)
28	--	--	28	--	.952 (24.18)	1.969 (50.01)	1.970 (50.04)	1.500 (38.10)	.702 (17.83)	1.48 (37.59)	1.469 (37.31)	1.379 (35.03)

1/ DIMENSION F IS THE WIDTH ACROSS THE WIRE SUPPORT.

REQUIREMENTS: ALL REQUIREMENTS SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF AS85049.

1. DESIGN AND CONSTRUCTION:

ACCESSORIES SHALL BE DESIGNED IN ACCORDANCE WITH FIGURE 1 AND TABLE 1. DIMENSIONS ARE IN INCHES AND APPLY AFTER PLATING. UNLESS OTHERWISE SPECIFIED TOLERANCES SHALL BE: XX = $\pm .03$ AND XXX = $\pm .015$ ANGULAR TOLERANCES X = ± 2 . METRIC EQUIVALENTS ARE IN PARENTHESES, ARE GIVEN FOR GENERAL INFORMATION ONLY AND ARE BASED UPON 1 INCH = 25.4 MM.

INTERFACE DIMENSIONS SHALL BE IN ACCORDANCE WITH AS85049, FIGURE 4, OR 4A.

A COMPLETE STRAIN RELIEF UNIT CONSISTS OF COUPLING NUT AND A FOLLOWER WITH STRAIN RELIEF ARM. THE COUPLING NUT SHALL BE CAPTIVATED TO THE FOLLOWER AND SHALL BE FREE TO ROTATE.

2. STRAIN RELIEF UNIT IS USED WITH MS3367-1-X PLASTIC STRAP (SEE APPLICATION NOTE 1) QUALIFIED IN ACCORDANCE WITH AS23190, OR A-A-52080 THROUGH 52084 LACING TAPE, OR EQUIVALENT, NOT SUPPLIED WITH THE CONNECTOR ACCESSORY.
3. THIS CLAMP WILL NOT ACCOMMODATE CONNECTORS USING SIZE 8, 4, AND 0 CONTACTS.

	AEROSPACE STANDARD		AS85049™/54 SHEET 2 OF 3	REV. C
	(R) CONNECTOR ACCESSORIES, ELECTRICAL, STRAIN RELIEF, NONENVIRONMENTAL, 45°, CATEGORY 4C (FOR AS50151 CRIMP, AS9524, MIL-DTL-26482 SERIES 2, AS81703 SERIES 3, AND MIL-DTL-83723 SERIES III CONNECTORS)			



Document Sharing Hub