

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV.
C

AS85049™/77

FEDERAL SUPPLY CLASS
5935

RATIONALE

REVISION IS REQUIRED TO IMPROVE DRAWINGS, MOVE NOTES TO DESIGN PARAGRAPH TO FOLLOW C1 AS STANDARD FORMAT, REMOVE IMAGES, ADD FINISH TABLE, CLARIFY RESTRICTIONS AND ADD METRIC EQUIVALENTS .590 (15.0), .020 (0.51) TO FIGURE 1 AND ADD WASHER – POLYTETRAFLUOROETHYLENE (PTFE) UNDER MATERIALS REQUIREMENT.

NOTICE

THE COMPLETE REQUIREMENTS FOR PROCURING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF AS85049.




FIGURE 1 - ACCESSORY CONFIGURATION AND DIMENSIONS

For more information on this standard, visit
<https://www.sae.org/standards/content/AS85049/77C/>

THIRD ANGLE PROJECTION

CUSTODIAN: AE-8/AE-8C1

PROCUREMENT SPECIFICATION: AS85049



AEROSPACE STANDARD

(R) CONNECTOR ACCESSORIES, ELECTRICAL, BACKSHELL,
ENVIRONMENTAL, 45°, SHIELD TERMINATION,
CATEGORY 2B, NONSELF-LOCKING
(MIL-DTL-38999 SERIES I AND II CONNECTORS)

AS85049™/77
SHEET 1 OF 4

REV.
C

Documents



FIGURE 1 - ACCESSORY CONFIGURATION AND DIMENSIONS (CONTINUED – SAFETY WIRE HOLES)

TABLE 1 - CONNECTOR SHELL SIZE AND CLAMP SIZE

ACCESSORY SHELL SIZE	FITS CONNECTOR SHELL SIZE		CLAMP SIZE (SEE TABLE 2) <u>1/</u>	A MAX. DIA. OF COUPLING RING	B ±.062 (1.57)	C ±.062 (1.57)	D MAX.	L (REF.)
	SERIES I	SERIES II						
08	09	08	01 THROUGH 02	.75 (19.1)	.398 (10.1)	3.088 (78.4)	3.06 (77.72)	3.25 (82.55)
10	11	10	01 THROUGH 03	.85 (21.6)	.458 (11.6)	3.148 (80.0)	3.20 (81.28)	3.39 (86.11)
12	13	12	02 THROUGH 04	1.00 (25.4)	.518 (13.2)	3.208 (81.5)	3.34 (84.84)	3.53 (89.66)
14	15	14	02 THROUGH 05	1.15 (29.2)	.588 (14.9)	3.298 (83.8)	3.49 (88.65)	3.68 (93.47)
16	17	16	02 THROUGH 06	1.25 (31.8)	.678 (17.2)	3.408 (86.6)	3.71 (94.23)	3.90 (99.06)
18	19	18	03 THROUGH 07	1.40 (35.6)	.868 (22.0)	3.598 (91.4)	4.01 (101.85)	4.26 (108.20)
20	21	20	03 THROUGH 08	1.55 (39.4)	.868 (22.0)	3.598 (91.4)	4.13 (104.90)	4.32 (109.73)
22	23	22	03 THROUGH 09	1.65 (41.9)	.958 (24.3)	3.748 (95.2)	4.36 (110.74)	4.55 (115.57)
24	25	24	04 THROUGH 10	1.85 (47.0)	.958 (24.3)	3.748 (95.2)	4.41 (112.01)	4.60 (116.84)

1/ SEE REQUIREMENT 2.

	AEROSPACE STANDARD	AS85049™/77 SHEET 2 OF 4 Documents	REV. C
	(R) CONNECTOR ACCESSORIES, ELECTRICAL, BACKSHELL, ENVIRONMENTAL, 45°, SHIELD TERMINATION, CATEGORY 2B, NONSELF-LOCKING (MIL-DTL-38999 SERIES I AND II CONNECTORS)		



Document Sharing Hub