

NEW PART STANDARD TO REPLACE MS9703.

NOTICE

THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9703A. THIS SAE STANDARD MAY RETAIN THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT.

ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL'S) MAY CONTINUE TO BE MANDATORY FOR DoD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.

AS9703™

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions. SAE Executive Standards Committee provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."





FIGURE 1 - BOLT

For more information on this standard, visit
<https://www.sae.org/standards/content/AS9703>

THIRD ANGLE PROJECTION



CUSTODIAN: E-25

PROCUREMENT SPECIFICATION: AS7471



AEROSPACE STANDARD

SCREW, MACHINE - DOUBLE HEXAGON EXTENDED
WASHER HEAD, DRILLED, NICKEL ALLOY
(UNS N07001), .1380-40 UNJF-3A

AS9703™
SHEET 1 OF 2

Documents

Copyright © 2021 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NUMBER	L	K	APPROX MASS LB/100	PART NUMBER	L	K	APPROX MASS LB/100
MS9703-02	.240-.260	.058-.078	.29	MS9703-14	.990-1.010	.414-.474	.55
MS9703-03	.302-.322	.058-.078	.31	MS9703-15	1.052-1.072	.476-.536	.57
MS9703-04	.365-.385	.058-.078	.33	MS9703-16	1.115-1.135	.539-.599	.59
MS9703-05	.428-.448	.058-.078	.35	MS9703-17	1.178-1.198	.602-.662	.61
MS9703-06	.490-.510	.058-.078	.37	MS9703-18	1.240-1.260	.664-.724	.63
MS9703-07	.552-.572	.058-.078	.39	MS9703-19	1.302-1.322	.726-.786	.65
MS9703-08	.615-.635	.058-.099	.42	MS9703-20	1.365-1.385	.789-.849	.68
MS9703-09	.678-.698	.102-.162	.44	MS9703-21	1.428-1.448	.852-.912	.70
MS9703-10	.740-.760	.164-.224	.46	MS9703-22	1.490-1.510	.914-.974	.72
MS9703-11	.802-.822	.226-.286	.48				
MS9703-12	.865-.885	.289-.349	.50				
MS9703-13	.928-.948	.352-.412	.52				

NOTES:

- /1/ FOR PARTS NUMBERS MS9703-02 THRU MS9703-10, DATUM Z SHALL REPLACE DATUM Y.
2. MATERIAL: AMS5708 (COMPOSITION SIMILAR TO UNS N07001).
- /3/ PROCUREMENT SPECIFICATION: AS7471.
4. HEAD TO SHANK FILLET SHOULD NOT BE COLD ROLLED FOR DASH NUMBERS-14 AND SMALLER.
5. FLUORESCENT PENETRANT INSPECT PER ASTM E1417/E1417M, TYPE 1, SENSITIVITY LEVEL 2.
6. SURFACE TEXTURE: SYMBOLS PER ASME Y14.36M. REQUIREMENTS PER ASME B46.1. UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICROINCHES Ra.
7. BREAK SHARP EDGES .003 TO .015, UNLESS OTHERWISE SPECIFIED.
8. DIMENSIONS ARE IN INCHES.
9. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1983.
10. DO NOT USE UNASSIGNED PART NUMBERS.
11. UNLESS OTHERWISE SPECIFIED, PART INVENTORY MANUFACTURED TO PREVIOUS REVISIONS OF THE APPLICABLE DRAWING OR SPECIFICATION MAY BE PROCURED AND USED UNTIL STOCK IS DEPLETED
12. REVISION INDICATOR: A CHANGE BAR (I) LOCATED IN THE LEFT MARGIN IS FOR THE CONVENIENCE OF THE USER IN LOCATING AREAS WHERE TECHNICAL REVISIONS, NOT EDITORIAL CHANGES, HAVE BEEN MADE TO THE PREVIOUS ISSUE OF THIS DOCUMENT. AN (R) SYMBOL TO THE LEFT OF THE DOCUMENT TITLE INDICATES A COMPLETE REVISION OF THE DOCUMENT, INCLUDING TECHNICAL REVISIONS. CHANGE BARS AND (R) ARE NOT USED IN ORIGINAL PUBLICATIONS, NOR IN DOCUMENTS THAT CONTAIN EDITORIAL CHANGES ONLY.

AS AND AMS ARE SAE INTERNATIONAL PUBLICATIONS.
ASME IS AN AMERICAN SOCIETY OF MECHANICAL ENGINEERS PUBLICATION.
ASTM IS AN ASTM INTERNATIONAL PUBLICATION.

	AEROSPACE STANDARD		AS9703™ SHEET 2 OF 2	
	SCREW, MACHINE - DOUBLE HEXAGON EXTENDED WASHER HEAD, DRILLED, NICKEL ALLOY (UNS N07001), .1380-40 UNJF-3A			

