

SURFACE VEHICLE STANDARD

SAE J1036

REAF.
APR93

Issued 1973-06
Reaffirmed 1993-04-16

Superseding J1036 JAN85

Submitted for recognition as an American National Standard

DIMENSIONAL STANDARD FOR CYLINDRICAL HYDRAULIC COUPLERS FOR AGRICULTURAL TRACTORS

Foreword—This reaffirmed document has been changed only to reflect the new SAE Technical Standards Board format.

1. Scope—This SAE Standard specifies the essential interface dimensions, the installation dimensions, and the operating requirements for hydraulic couplers employed to transmit hydraulic power from agricultural tractors to agricultural implements and farmstead equipment as defined in SAE J1150.

2. References

2.1 Applicable Documents—The following publication forms a part of this specification to the extent specified herein. The latest issue of SAE publications shall apply.

2.1.1 SAE PUBLICATION—Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

SAE J1150—Terminology for Agricultural Equipment

2.2 Definitions—The couplers consist of two parts:

2.2.1 FEMALE PART—The part which provides a cavity to receive the male part. The female part is considered a part of the tractor's hydraulic system, and shall accept and function with a male part which complies with the data in the table.

2.2.2 MALE PART—The probe which fits and locks into the cavity in the female part. The male part is considered a part of the cylinder, motor, and/or implement hydraulic system.

3. Field of Application—This document applies to couplers used on hydraulic lines other than those used for the braking system which must be connected or disconnected frequently to allow the transference of implement and farmstead equipment from one tractor to another.


4. Dimensional Characteristics—The coupler shall comply with Figure 1 and the data in Table 1.

CANCELLED

on
March 63
2001

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.



NOTES:

1. The configuration of the coupler shown is solely for the purpose of illustration and to give dimensional references. It is not intended to give design requirements.
2. Dimension L_2 applies when the balls of diameter d_4 are held at a gauge diameter of d_3 and also against the flank of the ball groove nearest the nose of the valve.

FIGURE 1—HYDRAULIC COUPLER