



SURFACE VEHICLE RECOMMENDED PRACTICE

J1117™

APR2019

Issued 1975-06
Reaffirmed 1986-03
Revised 2019-04

Superseding J1117 MAR1986

(R) Method of Measuring and Reporting the Pressure Differential-Flow Characteristics
of a Hydraulic Fluid Power Valve

RATIONALE

This standard is revised to update references, clarify test procedure, and report out graph and chart examples.

FOREWORD

As the flow passes through these valves, some power loss is experienced due to restrictions and directional changes of the fluid resulting in a differential pressure. Flow is passed through the valve through the ports and in positions as specified. Pressure is recorded at flow increments to produce a well defined curve. The tare loss of the test circuit is subtracted for final data presentation.

1. SCOPE

Applies to hydraulic fluid power valves as applied to Off-Road Self-Propelled Work Machines defined in SAE J1116.

1.1 Purpose

To provide a uniform procedure for measuring and reporting the pressure losses associated with the significant flow paths in a hydraulic fluid power valve.

2. REFERENCES

2.1 Applicable Documents

The following publications form a part of the specification to the extent specified herein. Unless otherwise indicated the latest revision of SAE publications shall apply.

2.1.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or +1 724-776-4970 (outside USA), www.sae.org.

ARP24 Determination of Hydraulic Pressure Drop

SAE J1116 Categories of Off-Road Self-Propelled Work Machines

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2019 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
<http://www.sae.org>

SAE WEB ADDRESS:

Full document details: SAE J1117_201904

SAE values your input. To provide feedback
on this Technical Report, please visit
http://standards.sae.org/J1117_201904

Documents
Document Sharing Hub

2.1.2 ISO Publications

Copies of these documents are available online at <http://webstore.ansi.org/>.

ISO 1219	Fluid power systems and components – Graphical symbols and circuit diagrams
ISO 4406	Hydraulic fluid power - Fluids - Method for coding the level of contamination by solid particles
ISO 80000-1	Quantities and units

3. DEFINITIONS

3.1 TEST FLOW

Any steady state flow rate required to conduct this test.

3.2 INPUT PORT

Any port into which flow is directed for the purpose of this test.

3.3 OUTPUT PORT

Any port from which flow exits for the purpose of this test.

3.4 TARE PRESSURE

The pressure loss between the pressure tapping points as generated by the test equipment exclusive of the test valve.

3.5 CONTROL

Any externally adjustable feature integral with the test valve that varies the flow path and/or flow rate.

3.6 SPECIFIED DATA

That basic information furnished in the request for the test as indicated in Section 7.

4. UNITS

4.1 The International System of Units (SI) is used herein in accordance with ISO 80000-1.

5. GRAPHIC SYMBOLS

5.1 Graphic symbols herein are in accordance with ISO 1219.

6. LETTER SYMBOLS

The following letter symbols are used in this document:

Table 1

		SI Unit	U.S. Unit
ΔP	Pressure differential (Pressure drop)	kPa (kilopascal)	psi
ΔP_m	Measured pressure differential	kPa	psi
ΔP_t	Tare pressure differential	kPa	psi
P1	Input pressure reading	kPa	psi
P2	Output pressure reading	kPa	psi
Q	Test flow	L/min	GPM
Q _m	Specified maximum flow	L/min	GPM

7. SUMMARY OF DESIGNATED INFORMATION

7.1 Specify the following information on all requests for this test:

7.1.1 A description of valve.

7.1.2 The type of fluid (if different than 12.1).

7.1.3 The fluid temperature (if different from the standardized values in 12.2).

7.1.4 The maximum flow for this test (Q_m).

7.1.5 The input port size and type.

7.1.6 The output port size and type.

7.1.7 The control variable positions.

8. GENERAL PROCEDURE

8.1 Conduct the test in accordance with the fixed values specified by the test request.

8.2 Use only standardized values, shown in Section 12, for catalog information and sales literature.

8.3 Test and report of subplate mounted valves may be run with the subplate included. Reports shall explicitly indicate how such valves were tested.