



SURFACE VEHICLE RECOMMENDED PRACTICE

J1598™

AUG2021

Issued 1988-07
Reaffirmed 1994-04
Revised 2021-08

Superseding J1598 JUN2016

Laboratory Testing of Vehicle and Industrial Heat Exchangers for Durability Under Vibration-Induced Loading

RATIONALE

In accordance with the SAE Five-Year Review process, this document includes both technical and editorial revisions, with several sections reworded for clarity.

1. SCOPE

This SAE Recommended Practice is applicable to all liquid-to-gas, liquid-to-liquid, gas-to-gas, and gas-to-liquid heat exchangers used in vehicle and industrial cooling systems. This document outlines the test to determine durability characteristics of the heat exchanger from vibration-induced loading.

1.1 Purpose

This document provides a test guideline for determining the durability of a heat exchanger under specified vibration loading.

2. REFERENCES

2.1 Applicable Documents

The following publications form a part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue of SAE publications shall apply.

2.1.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or +1 724-776-4970 (outside USA), www.sae.org.

SAE J1542 Laboratory Testing of Vehicle and Industrial Heat Exchangers for Thermal Cycle Durability

SAE J1597 Laboratory Testing of Vehicle and Industrial Heat Exchangers for Pressure Cycle Durability

SAE J1726 Charge Air Cooler Internal Cleanliness, Leakage, and Nomenclature

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2021 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
<http://www.sae.org>

SAE WEB ADDRESS:

Full document details: SAE J1598_202108

For more information on this standard, visit
https://www.sae.org/standards/content/J1598_202108

Documents

Document Sharing Hub

3. OBJECTIVE

To verify compliance with established criteria that ensures durability in a specific application. This document describes a system to induce stresses in a heat exchanger resulting from vibration loading. The process is accomplished by vibrating the unit at specified frequencies and amplitudes, or at specified frequencies and acceleration.

4. FACILITY REQUIREMENT

The facility should provide the following as required:

4.1 Equipment

Vibration equipment with controls on frequency, amplitude, and acceleration (for 50 Hz and below, electrohydraulic is suggested; higher frequencies may require electrodynamic). It should be verified that the test equipment will meet the parameters of the agreed upon test plan. Examples of test equipment include multi-axis shaker, sequential axis random shaker, etc.

4.2 Test Fixture

4.2.1 Best practice is using customer-provided vehicle/machine structural members to create a test fixture which represents actual installation.

4.2.2 If actual installation is not available, a fixture should support the heat exchanger with orientation as in service or as specified. The fixture must be rigid so as not to induce any additional dynamic inputs.

4.3 Means of checking heat exchanger integrity.

4.4 Equipment to monitor motion of unit during test.

4.5 Source for pressurizing and heating test unit as required.

4.6 Additional equipment may include but not be limited to the following:

- a. Accelerometers
- b. Automatic data logging equipment
- c. Automatic emergency shutdown
- d. Cycle counters
- e. Digital signal analyzer
- f. Function generator (sine wave, random noise, square wave, ramp function, etc.)
- g. Load transducers
- h. Pressure gauges
- i. Pressure regulators
- j. Data recording equipment
- k. Safety features as specified by regulatory codes and common practices
- l. Strain measurement equipment
- m. Temperature monitoring and control equipment