

Submitted for recognition as an American National Standard

DOOR COURTESY SWITCH

Foreword—This Reaffirmed Document has been changed only to reflect the new SAE Technical Standards Board Format.

1. **Scope**—This SAE Recommended Practice defines the test conditions, procedures, and performance requirements for 6, 12, and 24 V Door Courtesy Switches which are intended for use in motor vehicles.
2. **References**—There are no referenced publications specified herein.
3. **Definitions**—The courtesy lamp switch is a door or door latch actuated device which controls the electrical operation of the courtesy lamp, ignition key alarm, and other related components.
4. **Types**
 - 4.1 **Grounded and Non-Grounded**—Grounded switches provide an electrical path to vehicle ground through their mounting attachment. Non-grounded switches have their electrical conductors insulated from vehicle ground.
 - 4.2 **Single Terminal**—Characterized by one wiring connection to the vehicle.
 - 4.3 **Multi-Terminal**—Any other terminal/connector configuration, other than single terminal.
 - 4.4 **Special**—Switch types, which by their design, construction, and function, require separate definition.
5. **Cycle**—One cycle shall consist of allowing the actuation portion of the switch to move or be moved throughout its travel and to return to its initial position.
6. **Test Requirements**
 - 6.1 **Test Equipment and Instrumentation**
 - 6.1.1 **POWER SUPPLY**—The power supply shall comply with the following specifications:
 - 6.1.1.1 **Output Current**—Capable of supplying the continuous and inrush currents of the design load (reference 6.2.1.1).

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

QUESTIONS REGARDING THIS DOCUMENT: (724) 772-8512 FAX: (724) 776-0243
TO PLACE A DOCUMENT ORDER: (724) 776-4970 FAX: (724) 776-0790
SAE WEB ADDRESS <http://www.sae.org>

6.1.1.2 *Regulation*—Dynamic: The output voltage at the supply shall not deviate more than 1.0 V from zero to maximum load (including inrush current) and should recover 63% of its maximum excursion within 100 ms.

Static: The output voltage at the supply shall not deviate more than 2% with changes in static load from zero to maximum (not including inrush current), and means shall be provided to compensate for static input line variations.

6.1.1.3 *Ripple Voltage*—Maximum 300 mV peak-to-peak.

6.1.2 VOLTmeter—0 to 30 maximum full scale deflection, accuracy $\pm \frac{1}{2}\%$. (Note: a digital meter having at least a $3\frac{1}{2}$ digit readout with an accuracy of $\pm 1\%$ plus 1 digit is recommended for millivolt readings.)

6.1.3 AMMETER—Capable of carrying full system load current, accuracy $\pm 3\%$.

6.2 Test Procedures—Environmental conditions have been selected for this document to help assure satisfactory operation under general customer use conditions. It is essential to duplicate the specific environmental conditions under which the device is expected to function.

6.2.1 ELECTRICAL LOADS

6.2.1.1 The design load applied to the switch is the electrical load defined by the number and type of bulbs (or other electrical load devices) to be operated by each circuit of the switch. For example, the design load for the courtesy lamp circuit may be four 1156 bulbs.

6.2.1.2 The switch shall be operated at 6.4 V DC ± 0.2 V DC for a 6 V system, 12.8 V DC ± 0.2 V DC for a 12 V system, or 25.6 V DC ± 0.2 V DC for a 24 V system. These voltages shall be the open circuit voltage measured at the input terminations of the switch.

6.2.2 TEMPERATURE TEST PROCEDURE

6.2.2.1 The switch shall be exposed for 1 h without electrical load to each of the following temperatures: 25 °C ± 5 °C, 74 °C +0, -3, -32 °C +3, -0. The switch shall be cycled at each temperature for ten cycles at design load.

6.2.2.2 The same switch shall be used for the endurance test described in 6.2.3.

6.2.3 ENDURANCE TEST PROCEDURE

6.2.3.1 The switch shall be electrically connected to operate its design load (both primary and secondary circuit function design electrical loads) at a temperature of 25 °C ± 5 °C.

6.2.3.2 The switch shall be operated for a minimum of 50 000 cycles. The speed and the incident angle of actuation shall be representative of the point of application ("A" pillar, "B" pillar) in the vehicle. The test equipment shall be designed to provide this timing: Travel Time: 0.1 to 1.0 s (time to travel from one extreme position to the other). Dwell time: 2.0 to 5.0 s (time spent stationary at an extreme position). Make and Break Rate Range:

"A" Pillar application: 30 to 300 mm/s.

"B" Pillar application: 0.3 to 3.0 m/s.

6.2.3.3 At the conclusion of the endurance testing, the switch shall be operated for 1 h in each of its positions with the design load connected.