



SURFACE VEHICLE RECOMMENDED PRACTICE

J2284™-1

MAY2023

Issued 2002-03
Revised 2016-11
Stabilized 2023-05

Superseding J2284-1 NOV2016

High-Speed CAN (HSC) for Vehicle Applications at 125 kbps

RATIONALE

Five-Year Review.

STABILIZED NOTICE

This document has been declared “STABILIZED” by SAE Vehicle Architecture for Data Communications Standards Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAE Executive Standards Committee Rules provide that: “This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user.”

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2023 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

Full document details: SAE J2284_1_202305

For more information on this standard, visit
https://www.sae.org/standards/content/J2284/1_202305/

Documents

Document Sharing Hub

FOREWORD

The objective of SAE J2284-1 is to define a level of standardization in the implementation of a 125 kbps vehicle communication network using the Controller Area Network (CAN) protocol. The goal is to achieve a standard Electronic Control Unit (ECU) Physical Layer, Data Link Layer and media design criteria which will allow ECU and tool manufacturers to satisfy the needs of multiple end users with minimum modification to a basic design. Likewise, end users will benefit in lower ECU cost achieved from the high volumes of the basic design.

TABLE OF CONTENTS

1.	SCOPE	3
2.	REFERENCES	3
2.1	Applicable Documents	3
2.2	Related Publications	4
3.	DEFINITIONS	5
4.	ACRONYMS	10
5.	SYSTEM LEVEL ATTRIBUTES OF THE NETWORK	10
5.1	Message Format	10
5.2	Communication Rate	11
5.3	Basic Communication Network Parameters	11
5.4	Topology and Termination	11
5.5	Unshielded Media	13
5.6	Communication/Survivability Under Faulted Conditions	13
5.7	EMC Criteria	14
5.8	Tools	14
5.9	Off-Board Tool Cable Requirements	16

6.	ECU REQUIREMENTS.....	17
6.1	Absolute Maximum Ratings	17
6.2	ECU DC Operating Parameters	17
6.3	ECU Internal Capacitance	21
6.4	Termination	21
6.5	Connector Parameters	21
6.6	Bit Timing Requirements.....	22
6.7	Message Transmission and Reception	24
6.8	ECU Configuration Requirements.....	24
6.9	ElectroMagnetic Compatibility (EMC)	24
7.	CAN COMPONENT REQUIREMENTS	25
7.1	BUS TRANSCEIVER REQUIREMENTS	25
7.2	BUS CONTROLLER REQUIREMENTS	30
7.3	MICROCONTROLLER REQUIREMENTS AND PREFERENCES.....	31
8.	NOTES	32
8.1	Revision Indicator	32
FIGURE 1	SPLIT BUS TERMINATION.....	9
FIGURE 2	MULTIPLE ON-BOARD ECU CONFIGURATION	12
FIGURE 3	SINGLE ON-BOARD ECU CONFIGURATION.....	13
FIGURE 4	OFF-BOARD TOOL PARAMETERS	15
TABLE 1	BASIC COMMUNICATION NETWORK PARAMETERS.....	11
TABLE 2	MULTIPLE ON-BOARD ECU TOPOLOGY REQUIREMENTS	12
TABLE 3	SINGLE ON-BOARD ECU TOPOLOGY REQUIREMENTS	13
TABLE 4	PHYSICAL MEDIA PARAMETERS FOR UNSHIELDED TWISTED PAIR	13
TABLE 5	FAULT BEHAVIOR	14
TABLE 6	OFF-BOARD TOOL CAPACITIVE LOAD (WITHOUT CABLE LOAD).....	15
TABLE 7	OFF-BOARD TOOL PROPAGATION DELAY (LOOP DELAY WITHOUT CABLE DELAY).....	16
TABLE 8	OFF-BOARD TOOL CABLE PROPAGATION DELAY (ONE-WAY DELAY WITHOUT OFF-BOARD TOOL DELAY)	16
TABLE 9	ECU MAXIMUM BUS WIRE VOLTAGE - NO DAMAGE TO ECU (12 V SYSTEM)	17
TABLE 10	ECU OPERATING PARAMETERS – CAN DATA COMMUNICATION.....	18
TABLE 11	ECU DC PARAMETERS - OUTPUT BEHAVIOR RECESSIVE - BUS DISCONNECTED	19
TABLE 12	ECU DC PARAMETERS - OUTPUT BEHAVIOR DOMINANT - BUS DISCONNECTED.....	19
TABLE 13	ECU DC PARAMETERS - INPUT BEHAVIOR - ECU UNPOWERED/BUS BIAS OFF - BUS DISCONNECTED	20
TABLE 14	ECU DC PARAMETERS - INPUT BEHAVIOR - BUS DISCONNECTED	20
TABLE 15	ECU AC PARAMETERS - OUTPUT BEHAVIOR - BUS DISCONNECTED	20
TABLE 16	ECU DC PARAMETERS - RECESSIVE BUS STATE - BUS CONNECTED	20
TABLE 17	ECU DC PARAMETERS - DOMINANT BUS STATE - BUS CONNECTED	21
TABLE 18	ECU INTERNAL CAPACITANCE - ECU DISCONNECTED	21
TABLE 19	ECU TERMINATION CHARACTERISTICS.....	21
TABLE 20	ECU CONNECTOR CHARACTERISTICS	22
TABLE 21	CAN BIT TIMING - MIN/MAX.....	23
TABLE 22	ECU CAN REGISTER SETTINGS FOR STANDARD TIME QUANTA	23
TABLE 23	ECU - BASIC CAN INTERFACE FUNCTIONAL REQUIREMENTS	24
TABLE 24	BUS TRANSCEIVER - BASIC REQUIREMENTS	26
TABLE 25	BUS TRANSCEIVER - MAXIMUM BUS PIN VOLTAGE - NO DAMAGE TO TRANSCEIVER (12 V SYSTEM).....	26
TABLE 26	BUS TRANSCEIVER - GENERAL OPERATING CONDITIONS.....	27
TABLE 27	BUS TRANSCEIVER - DC PARAMETERS - OUTPUT BEHAVIOR - RECESSIVE/OFF STATE	27
TABLE 28	BUS TRANSCEIVER - DC PARAMETERS - OUTPUT BEHAVIOR - DOMINANT STATE.....	28
TABLE 29	BUS TRANSCEIVER - DC PARAMETERS - INPUT BEHAVIOR/THRESHOLD - SLEEP MODE ABSENT	28

TABLE 30	BUS TRANSCEIVER - DC PARAMETERS - INPUT BEHAVIOR/THRESHOLD - SLEEP MODE PRESENT	28
TABLE 31	BUS TRANSCEIVER - AC PARAMETERS	29
TABLE 32	CAN CONTROLLER - BASIC REQUIREMENTS	30

1. SCOPE

This SAE Recommended Practice will define the Physical Layer and portions of the Data Link Layer of the Open Systems Interconnection model (ISO 7498) for a 125 kbps High Speed CAN (HSC) protocol implementation. Both ECU and media design requirements for networks will be specified. Requirements will primarily address the CAN physical layer implementation.

Requirements will focus on a minimum standard level of performance from the High Speed CAN (HSC) implementation. All ECUs and media shall be designed to meet certain component level requirements in order to ensure the HSC implementation system level performance at 125 kbps. The minimum performance level shall be specified by system level performance requirements or characteristics described in detail in Section 5 of this document.

This document is designed such that if the Electronic Control Unit requirements defined in Section 6 are met, then the system level attributes should be obtainable.

This document will address only requirements which may be tested at the ECU and media level. No requirements which apply to the testing of the HSC implementation as integrated into a vehicle are contained in this document. However, compliance with all ECU and media requirements will increase the possibility of communication compatibility between separately procured components and will greatly simplify the task of successfully integrating a HSC communication system in a vehicle.

2. REFERENCES

This specification takes precedence over all conflicts in the documents cited in this section.

2.1 Applicable Documents

The following publications form a part of the specification to the extent specified herein. Unless otherwise indicated, the latest revision of SAE publications shall apply.

2.1.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or +1 724-776-4970 (outside USA), www.sae.org.

SAE J551-15 Vehicle Electromagnetic Immunity - Electrostatic Discharge (ESD)

SAE J1213-1 Glossary of Vehicle Networks for Multiplexing and Data Communications

SAE J2962-2 Communication Transceivers Qualification Requirements – CAN

2.1.2 ISO Publications

Copies of these documents are available online at <http://webstore.ansi.org/>

ISO 10605	Road vehicles - Test methods for electrical disturbances from electrostatic discharge
ISO 11451-2	Road vehicles - Vehicle test methods for electrical disturbances from narrowband radiated electromagnetic energy - Part 2: Off-vehicle radiation sources
ISO 11452-4	Road vehicles - Component test methods for electrical disturbances from narrowband radiated electromagnetic energy - Part 4: Harness excitation methods
ISO 11898-1 :2015(E)	Road vehicles - Interchange of digital information - Controller area network (CAN), Part 1: Data link layer and physical signalling
ISO 11898-2 :2016(E)	Road vehicles - Interchange of digital information - Controller area network (CAN), Part 2: High-speed medium access unit
ISO 26262	Road vehicles - Functional safety

2.1.3 Other Publications

CISPR 25	Limits & Methods of Measurement of Radio Disturbance Characteristics for the Protection of Receivers Used On-Board Vehicles
----------	---

2.2 Related Publications

The following publications are provided for information purposes only and are not a required part of this SAE Technical Report.

2.2.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or +1 724-776-4970 (outside USA), www.sae.org.

SAE J1930	Electrical/Electronic Systems Diagnostic Terms, Definitions, Abbreviations and Acronyms
SAE J2190	Enhanced Diagnostic Test Modes
SAE 970295	CAN Bit Timing Requirements

2.2.2 ISO Publications

Copies of these documents are available online at <http://webstore.ansi.org/>

ISO 7498	Data processing systems, Open systems interconnection standard reference manual
ISO 7637-1	Road vehicles, Electrical disturbance by conduction and coupling
ISO 14229	Road vehicles, Diagnostic systems, Specification of diagnostic services

2.2.3 Other Publications

AUTOSAR Release 4.2.2	www.autosar.org
-----------------------	--

3. DEFINITIONS

The definitions provided in SAE J1213-1 apply to this document. Additional or modified definitions, acronyms, and abbreviations included in this document or relevant to the communication of information in a vehicle are catalogued in this section.

3.1 ARBITRATION BIT TIME

See Nominal Bit Time.

3.2 CAN_H

The CAN_H bus wire is fixed to a mean voltage level during the recessive state and is driven in a positive voltage direction during the dominant bit state.

3.3 CAN_L

The CAN_L bus wire is fixed to a mean voltage level during the recessive state and is driven in a negative voltage direction during the dominant bit state.

3.4 CAN ACTIVITY FILTER TIME

Duration for which the bus needs to be continuously in the same state to enable the signal to pass the bus wake-up filter.

3.5 CAN BUS

Subnet where a number of ECUs communicate via a two-wire link (CAN_H, CAN_L) and where the Controller Area Network protocol is used as data link layer (DLL).

3.6 CAN IDENTIFIER

Bit pattern of 11 bits or 29 bits, located at the beginning of a message that denotes message content and also reflects message priority.

3.7 CLASSICAL CAN MESSAGE

Bus message according to ISO 11898:1993/Amd.1:1995(E). Bus message according to ISO 11898-1:2015(E) where the FDF bit is dominant, also known as CAN 2.0.

3.8 CAN FD MESSAGE

Bus message according to ISO 11898-1:2015(E) where the FDF bit is recessive. A CAN FD message typically employs different bit rates in the data field and in the arbitration field.

3.9 DATA BIT TIME

Length of a single bit in those parts of CAN FD messages where a dedicated separately configurable data bit time is used. The data bit time is not used anywhere in Classical CAN messages and is not used in those CAN FD messages where the BRS bit is dominant.

3.10 DATA LINK LAYER

Provides the reliable transfer of information across the Physical Layer. This includes message qualification and error control.

3.11 DATA SAMPLE POINT (t_{SAMPLE})

The sample point is the time within the bit period at which the single data sample captures the state of the bus. The programmable sample point is located between t_{SEG1} and t_{SEG2} . Equation 1 shows the relationship of t_{SAMPLE} to t_{SEG2} :

$$t_{\text{SAMPLE}} = t_{\text{BIT}} - t_{\text{SEG2}} \quad (\text{Eq. 1})$$

3.12 DIAGNOSTIC CONNECTOR

Provides the electrical connection between Off-Board and On-Board ECUs. For some vehicles, the diagnostic connector is the SAE J1962 connector.

3.13 DISABLING OF DLC MATCHING

When this functionality is supported and active, then the bus transceiver will not compare message data length code (DLC) values as to whether or not they match to configured DLC values when scanning messages for presence of valid wake-up requests.

3.14 DOMINANT STATE

The dominant state is represented by a differential voltage greater than a minimum threshold between the CAN_L and CAN_H bus wires. The dominant state overwrites the recessive state and represents a logic “0” bit value.

3.15 ELECTRONIC CONTROL UNIT (ECU)

A On- or Off-vehicle electronic assembly from which CAN SAE J2284-1 messages may be sent and/or received.

3.16 ECU DELAY (t_{ECU})

An ECU's loop delay includes the following four delays:

- Transmitter Propagation Delay (t_{TX} , this includes device delay and slew)
- Receiver Propagation Delay (t_{RX})
- Receiver Logic Delay (t_{LOGIC})
- Common Mode Choke (t_{CHK} , optional, Includes both Tx and Rx choke delays)

$$t_{\text{ECU}} = (t_{\text{TX}} + t_{\text{RX}} + t_{\text{LOGIC}} + t_{\text{CHK}}) \quad (\text{Eq. 2})$$

3.17 FD_Receive / FD_Transmit

Status flags indicating whether the bus controller employs CAN FD data bit timing presently.

3.18 HANDLE

Hardware object label of one or multiple LLC frames (LPDU). Identifies hardware element used for transaction. Used to facilitate cancellation of pending message transmission requests.

3.19 MEDIA

The physical entity which conveys the electrical (or equivalent means of communication) transmission between ECUs on the network. (e.g., unshielded twisted pair wires). Media is defined as all elements between the connector pins of the communicating ECUs through which the signals pass.

3.20 MEDIA DELAY (t_{BUS})

Media is defined as all elements between the connector pins of the communicating ECUs through which the signals pass.

Media delay is defined as the time required for a signal to pass through the media at the longest specified distance (see Table 1, Table 2, and Table 7).

3.21 MUST

The word “**Must**” is used to indicate that a binding requirement exists on components or devices which are outside the scope of this specification.

3.22 NOMINAL BIT TIME

Length of a single bit in Classical CAN messages. Length of a single bit in CAN FD messages except where data bit timing applies. Also known as arbitration bit time.

3.23 PCS STATUS

Indicates what logical level is presently being received or transmitted and whether or not CAN FD data bit timing applies presently. For details see ISO 11898-1 :2015(E).

3.24 PHYSICAL LAYER

Concerns the transmission of an unstructured bit stream over physical media: deals with the mechanical, electrical, functional and procedural characteristics to access the physical media.

3.25 PROPAGATION DELAY (t_{PROP})

Part of bit cell that serves compensation of data signal delay times in a network. Because CAN is an arbitrating protocol, the propagation delay must take into account the time required for a signal to make a complete round trip from one CAN controller to another and back. This translates to Equation 3 or 4.

$$t_{\text{PROP}} = 2(t_{\text{TX}} + t_{\text{RX}} + t_{\text{LOGIC}} + t_{\text{CHK}} + t_{\text{BUS}}) \quad (\text{Eq. 3})$$

or

$$t_{\text{PROP}} = 2(t_{\text{ECU}} + t_{\text{BUS}}) \quad (\text{Eq. 4})$$

3.26 PROTOCOL

Formal set of conventions or rules for the exchange of information between ECUs. This includes the specification of frame administration, frame transfer and physical layer.

3.27 RADIATED EMISSIONS

Radiated Emissions consists of energy that emanate from the CAN bus wires. Electric field strength in dbmV/m is the typical measure of radiated emissions.

3.28 RADIATED IMMUNITY

A property that ensures that the CAN bus wires will not suffer degraded functional operation within its intended electromagnetic environment .

3.29 RECESSIVE STATE

The recessive state is represented by an inactive state differential voltage that is approximately 0. The recessive state represents a logic "1" bit value.

3.30 SECONDARY SAMPLE POINT (SSP)

Sample point that applies to data bit timing in CAN FD (BRS = recessive) messages when the transmitter delay compensation functionality is configured to be enabled/active. The transmitting bus controller automatically determines/adapts/delays the location of the sample point based on observed data signal delay of the particular transmitter implementation, unless transmitter delay compensation disabled.

3.31 SELECTIVE WAKE-UP BUS TRANSCEIVER

Bus transceiver capable to monitor bus messages while in low power mode and capable to generate a wake-up interrupt when valid messages present on the bus match configured message content (identifier, data field).

3.32 SHALL

The word "**Shall**" is to be used in the following ways:

- a. To state a binding requirement on the CAN interfaces which comprise the ECU, which is verifiable by external manipulation and/or observation of an input or output.
- b. To state a binding requirement upon an ECU that is verifiable through a review of the document.

3.33 SHOULD

The word "**Should**" is used to denote a preference or desired conformance.

3.34 SPLIT BUS TERMINATION

Bus termination where the resistance between CAN_H and CAN_L is split into two parts of equal value. Resistance center tap connected to ground via a capacitor unless otherwise specified. Figure 1 is for informative reference only. See section 6.4 for passive component values.




Figure 1 – Split bus termination

3.35 SYNCHRONIZATION JUMP WIDTH (t_{SJW})

This time interval is the maximum amount of time by which t_{SEG1} may be lengthened or t_{SEG2} shortened to compensate for synchronization differences between ECUs on the CAN network. This is accomplished automatically in the CAN controller as a basic part of the protocol. However, the amount of skew tolerated is adjustable by software programming.

3.36 SYNCHRONIZATION SEGMENT (t_{SYNC_SEG})

This time interval is used to synchronize all ECUs on the bus. If all ECUs are fully synchronized, then all bit edges occur in this interval, which has a fixed period of one Time Quantum.

3.37 TIME QUANTUM (t_Q)

This is the basic unit of time for bit timing. This time is derived from the microcontroller's oscillator clock and is programmable based on the CAN controller's divide register values.

3.38 TRANSMITTER DELAY COMPENSATION (TDC)

For data bit timing in CAN FD messages the transmitting CAN controller automatically will compensate the signal delay caused by the ECU-internal transmitter implementation, unless TDC functionality disabled. Functionality inactive for arbitration bit timing in CAN FD messages and generally inactive in Classical CAN messages. For details see ISO 11898-1 :2015(E).

3.39 TSEG1 (t_{SEG1})

This time interval is used to compensate for positive phase errors in synchronization between ECUs on the network. If an edge occurs during this interval, t_{SEG1} is lengthened to compensate for synchronization differences with other ECUs on the CAN network. t_{SEG1} is equivalent to the combination of the Prop_Seg and Phase_Seg1 parts of the bit period defined in ISO 11898 :2015(E).

$$t_{SEG1} = t_{BIT} - 1 (t_Q) - t_{SEG2} \quad (\text{Eq. 5})$$

3.40 TSEG2 (t_{SEG2})

This time interval is used to compensate for negative phase errors in synchronization between ECUs on the network. If an edge occurs during this interval, t_{SEG2} is shortened to compensate for synchronization differences with other ECUs on the CAN network. t_{SEG2} is equivalent to the Phase_Seg2 part of the bit period defined in ISO 11898-1 :2015(E).