

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

MA2081

RATIONALE

MA2081 HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.

FEDERAL SUPPLY CLASS
4720





TABLE 1

HOSE ASSEMBLY NO. AND SIZE CODE	SIZE REF	THREAD T PER AS1370 (ISO 5855) 4H-5H REF	I.D. MIN	A1 MAX	A2 MAX	C (2) (2) DRILL DIA MIN	E (3) (3) DIA MAX WITHOUT SLEEVING	F HEX REF	G		BALL SIZE MIN THRU DIA (2) (2)	
									MIN	MAX	MS 19059 DASH NO.	DIA MM
MA 2081-06 MA 2081-10	6.0 9.5	MJ 12x1.25 MJ 16x1.5	5.38 7.57	33.02 37.59	52.83 58.17	3.43 6.10	17.53 20.32	14.22 17.53	7.112 9.398	11.430 14.351	4807 4812	2.768 4.775
MA 2081-12 MA 2081-16	12.5 15.5	MJ 18x1.5 MJ 22x1.5	9.93 12.32	42.93 44.96	66.29 78.49	8.64 10.42	24.64 28.20	22.35 25.40	10.922 12.954	16.383 17.145	4816 4818	7.950 9.525
MA 2081-20 MA 2081-25	19.0 25.0	MJ 27x1.5 MJ 33x1.5	15.29 21.64	49.53 59.69	87.38 95.25	12.95 19.30	35.06 42.17	31.75 38.10	14.986 19.304	18.288 20.828	4821 4829	11.912 18.262

SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/MA2081>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3D

PROCUREMENT SPECIFICATION: MA2007



AEROSPACE STANDARD

HOSE ASSEMBLY, POLYTETRAFLUOROETHYLENE,
CRES REINFORCED, 204 °C, 21,000 KPA, 60-DEG CONE,
STRAIGHT TO 45-DEG, LIGHTWEIGHT, METRIC

MA2081
SHEET 1 OF 6

Documents

Copyright 2015 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

TABLE II

SLEEVE CODE	SLEEVE MATERIAL	TEMP LIMIT °C	TOLERANCE	HOSE OR SLEEVE OUTSIDE DIAMETER 5					
				HOSE SIZE					
				06	10	12	16	20	25
-	(--) INDICATES HOSE ONLY NO SLEEVE (AS 1624)	204	MAX MIN	9.91 9.14	12.45 11.56	15.62 14.86	18.54 17.53	25.15 24.13	32.26 31.24
A	ABRASION SLEEVE TUBULAR (TFE-AS1291 - CODE B) 6	204	MAX MIN	12.70 11.18	15.24 13.72	18.54 17.02	21.34 19.81	28.19 26.67	35.56 34.04
B	ABRASION SLEEVE COIL NYLON (AS1294) 7	135	MAX MIN	11.43 9.91	13.97 12.45	17.65 16.13	20.57 19.05	27.43 25.91	34.54 33.02
C	FIRESLEEVE (AS1072 SIL-FC) (15 MIN) 8 9 13	204	MAX MIN	15.88 12.70	19.05 15.88	22.22 19.05	25.40 22.22	31.75 28.58	38.10 34.92
D	ABRASION SLEEVE SHRINK-ON (FEP) 11	177	MAX MIN	10.77 9.50	13.72 12.19	16.89 15.62	20.07 18.54	27.18 25.65	34. 32.
E	ABRASION SLEEVE SHRINK-ON (POLYOLEFIN AS1073 - CODE B) 11	135	MAX MIN	11.43 10.16	14.22 12.83	17.65 16.38	20.57 19.05	27.43 25.91	34.54 33.02
F	FIRESLEEVE (AS1072 SIL-FC) (5 MIN) 8 9 12	204	MAX MIN	15.88 12.70	19.05 15.88	22.22 19.05	25.40 22.22	31.75 28.58	38.10 34.92
G	FIRESLEEVE INTEGRAL SILICONE (15 MIN) (AS1722) 13	204	MAX MIN	16.76 15.24	18.92 17.40	22.73 21.21	25.53 24.00	30.99 29.46	38.48 36.96
H	FIRESLEEVE INTEGRAL SILICONE (5 MIN) 12	204	MAX MIN	16.76 15.24	18.92 17.40	22.73 21.21	25.53 24.00	30.99 29.46	38.48 36.96
J	INTEGRAL ABRASION SLEEVE (BRAIDED) POLYESTER 10	177	MAX MIN	12.45 11.28	14.48 13.59	17.65 16.51	20.32 19.30	27.18 26.16	34.29 33.27
K	ABRASION SLEEVE COIL (PTFE-AS1293) 7	204	MAX MIN	12.70 11.18	15.24 13.72	18.54 17.02	21.90 20.37	28.19 26.67	35.56 34.04



AEROSPACE STANDARD

HOSE ASSEMBLY, POLYTETRAFLUOROETHYLENE,
CRES REINFORCED, 204 °C, 21,000 KPA, 60-DEG CONE,
STRAIGHT TO 45-DEG, LIGHTWEIGHT, METRIC

MA2081
SHEET 2 OF 6



Documents

Document Sharing Hub