

RATIONALE

MA2086 HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.

MA2086

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.




FIGURE 1





FIGURE 2

TABLE 1
DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE SPECIFIED

HOSE ASSEMBLY NO. AND SIZE CODE	SIZE DN	THREAD T PER AS1370	I.D. MIN	A MAX	B SEAL DIA BASIC	C /2/ DRILL DIA MIN	D REF	E /3/ DIA MAX WITHOUT SLEEVING	F HEX REF	BALL SIZE MIN THRU DIA /2/ DIA		
										MS19059 DASH NO.	INCH	MM
MA2086 E	06	MJ12x1.25	5.4	54	7.50	3.4	4.1	18	14	4807	.109	2.8
MA2086 G	10	MJ16x1.5	7.5	62	11.50	6.1	4.1	20	19	4812	.188	4.8
MA2086 H	12	MJ18x1.5	9.9	70	13.50	8.6	4.8	25	22	4816	.313	7.9
MA2086 J	16	MJ22x1.5	12.3	83	17.50	10.4	5.2	28	27	4818	.375	9.5
MA2086 K	20	MJ27x1.5	15.3	95	21.50	12.9	5.8	35	32	4821	.469	10.4
MA2086 M	25	MJ33x1.5	21.6	114	26.60	19.3	7.6	42	41	4829	.719	18.3

SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/MA2086>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3D

PROCUREMENT SPECIFICATION: MA2007



AEROSPACE STANDARD

HOSE ASSEMBLY, TETRAFLUOROETHYLENE,
21000 KPA, FLARELESS, STRAIGHT
TO STRAIGHT, METRIC

MA2086
SHEET 1 OF 4



Documents

Copyright 2015 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

TABLE 2

SLEEVE CODE	SLEEVE MATERIAL	TEMP. LIMIT °C	HOSE OR SLEEVE OUTSIDE DIAMETER /5/ HOSE SIZE						
			TOLE-RANCE	06	10	12	16	20	25
-	(-) INDICATES HOSE ONLY. NO SLEEVE (AS1624)	204	MAX MIN	10.0 9.1	12.4 11.6	15.6 14.9	18.5 17.6	25.1 24.1	32.3 31.2
A	ABRASION SLEEVE TUBULAR (TFE-AS1291-CODE B) /6/	204	MAX MIN	12.7 11.2	15.2 13.7	18.5 17.0	21.3 19.8	28.2 26.7	35.6 34.0
B	ABRASION SLEEVE COIL (NYLON AS1294) /7/	135	MAX MIN	11.4 10.0	14.0 12.4	17.7 16.1	20.6 19.1	27.4 25.9	34.5 33.0
C	FIRESLEEVE (AS1072 SIL-FG) (15 min) /8/ /9/ /13/	204	MAX MIN	15.9 12.7	19.1 15.9	22.2 19.1	25.4 20.6	31.8 28.6	38.1 34.9
E	ABRASION SLEEVE SHRINK-ON (FEP) /11/	177	MAX MIN	10.8 9.5	13.7 12.2	16.9 15.6	20.1 18.5	27.2 25.7	34.3 32.8
F	ABRASION SLEEVE SHRINK-ON (POLYOLEFIN AS1073 - CODE B) /11/	135	MAX MIN	11.4 10.2	14.2 12.8	17.7 16.4	20.6 19.1	27.4 25.9	34.5 33.0
G	FIRESLEEVE (AS1072 SIL-FG) (5 min) /8/ /9/ /12/	204	MAX MIN	15.9 12.7	19.1 15.9	22.2 19.1	25.4 22.2	31.8 28.6	38.1 34.9
H	FIRESLEEVE INTEGRAL SILICONE (15 min) (AS1722) /13/	204	MAX MIN	16.8 15.2	18.9 17.4	22.7 21.2	25.5 24.0	31.0 29.5	38.9 37.0
J	FIRESLEEVE INTEGRAL SILICONE (5 min) /12/	204	MAX MIN	16.8 15.2	18.9 17.4	22.7 21.2	25.5 24.0	31.0 29.5	38.5 37.0
K	INTEGRAL ABRASION SLEEVE (BRAIDED) POLYESTER /10/	149	MAX MIN	12.4 11.2	14.5 13.6	17.7 16.5	20.3 19.3	27.2 26.2	34.3 33.3
L	ABRASION SLEEVE COIL (PTFE-AS1293) /7/	204	MAX MIN	12.7 11.2	15.2 13.7	18.5 17.0	21.9 20.4	28.2 26.7	35.6 34.0

TABLE 3

HOSE ASSEMBLY LENGTH	AVAILABLE INCREMENTS	TOLERANCE
UNDER 500 mm	5 mm	± 3 mm
500 - 1000 mm	10 mm	± 7 mm
1001 - 1500 mm	20 mm	±13 mm
OVER 1500 mm	30 mm	±1% OF LENGTH

TABLE 4

HOSE OR SLEEVE CODE	HOSE OR TYPE SLEEVE	MAXIMUM WEIGHT HOSE SIZE						
		UNITS	06	10	12	16	20	25
-	HOSE ONLY	G/CM	1.607	2.679	3.572	4.822	9.823	15.181
A	ABRASION SLEEVE (TFE-AS1291-B)	G/CM	0.536	0.714	0.714	0.893	1.250	1.607
B	ABRASION SLEEVE (NYLON AS1294)	G/CM	0.178	0.357	0.536	0.536	0.714	0.893
C	FIRESLEEVE (15 min) AS1072	G/CM	1.250	1.607	1.964	2.143	3.036	3.750
E	ABRASION SLEEVE (FEP)	G/CM	0.357	0.536	0.536	0.893	1.072	1.250
F	ABRASION SLEEVE (AS1073B)	G/CM	0.357	0.536	0.536	0.714	0.893	1.072
G	FIRESLEEVE (5 min) AS1072	G/CM	1.250	1.607	1.964	2.143	3.036	3.751
H	FIRESLEEVE INTEGRAL (15 min) WITH HOSE	G/CM	3.393	4.822	6.251	8.394	17.681	20.896
J	FIRESLEEVE INTEGRAL (5 min) WITH HOSE	G/CM	3.393	4.822	6.251	8.349	17.681	20.896
K	ABRASION SLEEVE POLYESTER WITH HOSE	G/CM	2.143	2.858	3.929	5.358	10.716	16.074
L	ABRASION SLEEVE (PTFE-AS1293)	G/CM	0.536	0.714	0.893	0.893	1.072	1.250
NONE	FIRESLEEVE CLAMP	G	9.1	9.1	11.3	11.8	11.8	15.0
NONE	FITTING END (HOSE SIZE - STRAIGHT)	G	27	41	68	109	236	323



AEROSPACE STANDARD

HOSE ASSEMBLY, TETRAFLUOROETHYLENE,
21000 KPA, FLARELESS, STRAIGHT
TO STRAIGHT, METRIC

MA2086

SHEET 2 OF 4



Documents

Document Sharing Hub