

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

MA5075

FEDERAL SUPPLY CLASS
4720

RATIONALE

MA5075 HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.




FIGURE 1 - HOSE ASSEMBLY





FIGURE 2 - HEAT SHRINKABLE SLEEVES REQUIRED FOR COIL AND TUBULAR ABRASION SLEEVES /6/ AND /7/

SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/MA5075>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3D

PROCUREMENT SPECIFICATION: /2/ MA4095



AEROSPACE STANDARD

HOSE ASSEMBLY, POLYTETRAFLUOROETHYLENE, PARA ARAMID REINFORCED, 34,500 KPA, 135 °C, BEAM SEAL, STRAIGHT TO 90°, METRIC

MA5075
SHEET 1 OF 5

Documents

Copyright 2015 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

TABLE 1 - BASIC HOSE DIMENSIONS

HOSE ASSEMBLY SIZE CODE	HOSE SIZE (REF)	THREAD T PER AS1370 (REF)	ID MIN	A MAX	B MIN /12/	C HEX (REF)	D MAX W/O SLEEVING /13/	G	H MIN	H MAX	BALL SIZE MIN THRU DIA /12/
MA5075-08	DN08	MJ12X1.25	4.33	27.75	3.40	14.00	13.75	40.25	20.50	24.50	2.98
MA5075-10	DN10	MJ16X1.50	7.45	33.00	6.10	17.25	17.25	47.00	23.63	34.25	5.75
MA5075-12	DN12	MJ18X1.50	9.78	36.25	8.60	22.00	20.75	49.75	23.50	34.25	7.83
MA5075-16	DN16	MJ22X1.50	12.13	40.00	10.40	25.00	24.25	59.25	29.00	39.75	9.78
MA5075-20	DN20	MJ27X1.50	15.38	45.00	13.00	28.00	29.25	74.50	34.50	48.75	12.88
MA5075-25	DN25	MJ33X1.50	21.28	53.00	19.30	34.50	34.50	80.75	37.68	67.00	18.75

TABLE 2 - LENGTH TOLERANCE

HOSE ASSEMBLY LENGTH	TOLERANCE
UNDER 457 mm	±3 mm
457 TO 914 mm EXCLUSIVE	±7 mm
915 TO 1270 mm EXCLUSIVE	±13 mm
OVER 1270 mm	±1%

TABLE 3 - HOSE AND SLEEVE OD

HOSE OR SLEEVE CODE	HOSE OR TYPE SLEEVE	TEMP LIMIT (°C)	HOSE OR SLEEVE ASSEMBLED OUTSIDE DIAMETER HOSE SIZE DN08	HOSE OR SLEEVE ASSEMBLED OUTSIDE DIAMETER HOSE SIZE DN10	HOSE OR SLEEVE ASSEMBLED OUTSIDE DIAMETER HOSE SIZE DN12	HOSE OR SLEEVE ASSEMBLED OUTSIDE DIAMETER HOSE SIZE DN16	HOSE OR SLEEVE ASSEMBLED OUTSIDE DIAMETER HOSE SIZE DN20	HOSE OR SLEEVE ASSEMBLED OUTSIDE DIAMETER HOSE SIZE DN25
-	HOSE ONLY, NO SLEEVE	204	8.58 7.60	11.73 10.75	14.65 13.65	17.18 16.03	20.30 19.15	28.50 26.95
A	ABRASION SLEEVE TUBULAR (TFE AS1291) /7/	204	11.83 8.58	14.63 11.75	17.85 16.13	20.45 17.03	23.50 20.40	32.00 28.45
B	ABRASION SLEEVE COIL (NYLON AS1294) /6/	135	10.23 8.25	13.38 11.40	17.73 14.75	19.28 17.03	22.40 20.25	30.60 28.05
C	TUBULAR FIRESLEEVE SIL/FG (15 min) /5/ /9/ /14/ (AS1072)	204	15.63 13.10	18.75 16.20	21.88 19.10	25.00 21.48	28.13 24.60	34.38 32.20
E	SHRINK ABRASION SLEEVE (FEP) /8/	177	9.38 8.00	12.68 11.30	15.88 14.45	18.73 16.98	22.18 20.28	30.70 28.65
F	SHRINK ABRASION SLEEVE (POLYOLEFIN AS1073-CODE B) /11/	135	10.28 8.70	13.68 12.10	15.58 15.00	19.23 17.48	22.35 20.60	30.80 28.65
H	INTEGRAL FIRESLEEVE (15 min) /9/	204	16.03 14.85	19.15 17.98	22.28 21.10	25.40 24.23	28.53 26.85	36.35 34.85
K	INTEGRAL ABRASION SLEEVE (BRAIDED POLYESTER) /11/	149	10.75 9.75	13.98 12.75	16.63 15.63	19.30 18.15	22.18 21.03	30.25 28.70
L	ABRASION SLEEVE COIL (PTFE AS1293) /8/	204	11.13 8.33	14.28 11.50	17.18 14.40	19.73 17.03	22.85 20.15	31.05 27.95



AEROSPACE STANDARD

HOSE ASSEMBLY, POLYTETRAFLUOROETHYLENE,
PARA ARAMID REINFORCED, 34,500 KPA, 135 °C,
BEAM SEAL, STRAIGHT TO 90°, METRIC

MA5075

SHEET 2 OF 5



Documents

Document Sharing Hub