

TECHNICAL SPECIFICATION	TS221™	ISSUE 2
	Issued Revised	UNKNOWN 2005-06
Specification for Manufacture and Performance Testing of Quick Release Pins (Ball Type) Imperial (Inch Units)		

NOTE: The issue status of this document remains unchanged as there have been no changes to the technical content.

SAE INDUSTRY TECHNOLOGIES CONSORTIA AEROSPACE STANDARDS AND PART QUALIFICATION PROGRAM

FOREWORD

On the 1st January 2015 the SAE Industry Technologies Consortia (SAE ITC) acquired the ADS Aerospace Standards, previously known as the Society of British Aerospace Companies (SBAC) Aerospace Standards. The SAE ITC established in 2003 operates as a trade association as part of the SAE International Enterprise providing a unique framework serving the automotive, aerospace, and commercial vehicle sectors. Clients include private companies, government agencies, individuals, and trade associations. Building consensus and breakthrough barriers to achieve solutions, and the ways by which those solutions take shape, are tailored to each client's individual needs.

The legal obligations and copyright authority of all Aerospace Standards that were issued by the ADS Group Limited are therefore assigned / transferred to the SAE ITC.

These Standards are produced by the SAE ITC with the assistance of, and for the benefit of the Aerospace Industry, as part of a continuous programme of Standardisation for Aerospace application under the control of the Technical Standards Committee (TSC) of the SAE ITC.

SAE ITC Standards are published as part of the series of SAE ITC Aerospace Industry Standards, and where appropriate, additional manufacturing and inspection requirements are issued as Reference Sheets (RS) or Technical Specifications (TS). It is the responsibility of those using or specifying a Standard to ensure the product, process, or manufacturer so used or specified, is appropriate for the task or role in question. The SAE ITC wishes to draw special attention to the fact Technical Specifications (TS) include testing and procedures by which a user or Design Authority can establish whether a particular manufacturer, prima facie, has the capability to produce hardware in accordance with the appropriate standards and related specifications.

The SAE ITC, its servants, or representatives accept no responsibility for the continued quality of hardware items produced against the relevant drawings and specifications; this responsibility remains with the user.

Whilst the SAE ITC takes all reasonable care in the preparation of its Standards, neither the SAE ITC, its officers, employees, servants, agents, or representatives, shall have any responsibility or liability whatsoever with respect to any act or omission (whether negligent or not) of whatsoever nature, or in connection with the preparation of the Standards or any part thereof. These responsibilities are those of the user or Design Authority. Users of SAE ITC Standards agree that any such liability on the part of the SAE ITC is excluded to the maximum extent permitted by law. SAE ITC Standards may be changed from time to time, and both users and manufacturers of these parts should ensure they are in possession of the latest issue of the Standards and supporting documentation before adoption or the commencement of production.

It is recommended that Technical Specification TS260, Metallic Materials List of Alternative Material Standards, be consulted prior to manufacture of SAE ITC products.

Each Standard is a facsimile or electronic reproduction of a master drawing and, therefore, any outline view scales stated are not necessarily reproduced accurately. A Master Index of all SAE ITC Aerospace Standards is published separately on the SAE ITC website.

All references to Standards include reference to RS and TS publications.

Details of this and any further information can be obtained from the SAE ITC.

SAE Industry Technologies Consortia provides that "This standard is published by SAE ITC to advance the state of technical and engineering sciences. The use of this standard is entirely voluntary and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."
Copyright © 2015 SAE ITC.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, without prior written permission of SAE ITC.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-772-7545 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
<http://itc.sae.org/>

TECHNICAL SPECIFICATION

No. 221

SBAC SPECIFICATION FOR MANUFACTURE AND PERFORMANCE TESTING OF QUICK RELEASE PINS (BALL TYPE) IMPERIAL (INCH UNITS)

*Issued by: Technical Standards Group
The Society of British Aerospace Companies Ltd
Registered in England and Wales no. 143447*

© 2005

Issue 2 - June 2005

 **Documents**
Document Sharing Hub

**SBAC Technical Specification TS 221
for Manufacture, Performance and Testing
of Quick Release Pins (Ball Type) IMPERIAL (Inch Units)**

CONTENTS

1. SCOPE
2. ASSOCIATED SPECIFICATION
3. DEFINITIONS
4. QUALITY ASSURANCE
5. MANUFACTURING AND TEST REQUIREMENT
6. TEST FIXTURES

(Prepared by the Technical Standards Committee)
The Society of British Aerospace Companies Limited
Registered in England and Wales No. 143447

1. SCOPE

This specification covers the requirements for manufacture, testing and procurement of quick release pins (ball type) in Imperial-inch units required for use in aerospace applications.

2. ASSOCIATED DOCUMENTS

ISO2859-1 (BS6001)	-	Sampling procedure for inspection by attributes.
BS EN 10109	-	Method of Rockwell Hardness Test.
BE EN ISO 6507	-	Method for Vickers Hardness Test
BS M39	-	Penetrant inspection of aerospace materials and components.
BS 1134	-	Surface texture.
DEF STAN 07-55	-	Environmental testing.
MIL-STD-810	-	Environmental test methods and engineering guideline.
AS 64363 to AS 64365	-	Pins, quick release (ball type) single / double acting.
TS200	-	Qualified manufacturers for SBAC aerospace industry standards.
TS201	-	Method change approval for qualified parts.
TS202	-	Qualification test requirements and procedures for aerospace industry standard parts.

3. DEFINITIONS

3.1 Authorities

3.1.1 Design Authority

The design authority is the SBAC Technical Standards Committee (TSC).

3.1.2 Qualification Testing Authority

The qualification testing authority shall be the SBAC Technical Standards Committee or other nominated body approved by the TSC to carry out the testing.

3.1.3 Quality Assurance Authority

The quality assurance authority will be as agreed by the TSC. Generally this is the authority involved in the design activity requesting the use of parts approved to this specification.

3.2 Production Batch

A batch shall consist of quick release pins which are of the same type and diameter, fabricated by the same process from material of the same cast, heat-treated as one lot, and assembled as one continuous run free from any interruptions or changes such as might be expected to result in a significant variation in the quality of the finished product.

3.3 Inspection Lot

An inspection lot consists of quick release pins from a single production batch of the same part number which completely defines the lot.

3.4 Discontinuities

3.4.1 Crack

Rupture in the material which may extend in any direction and which may be intercrystalline or transcrystalline in character.

3.4.2 Seam

Open surface defect.

3.4.3 Lap

Surface defect caused by folding over metal fins or sharp corners and then rolling or forging them into the surface.

3.4.4 Inclusion

Non-metallic particles originating from the material making process. They may exist as discrete particles or strings of particles extending longitudinally.

3.5 Test Temperature

Ambient temperature, unless otherwise specified.

3.6 Simple Random Sampling

The taking of n items from a population of N items in such a way that all possible combinations of n items have the same probability of being chosen.

3.7 Critical Defect

A defect that is likely to result in hazardous or unsafe conditions for individuals using, maintaining, or depending upon the considered product, or that is likely to prevent performance of the function of a major end item.

3.8 Major Defect

A defect other than critical, that is likely to result in a failure or to reduce materially the useability of the considered product for its intended purpose.

3.9 Minor Defect

A defect that is not likely to reduce materially the useability of the considered product for its intended purpose, or that is a departure from established specification having little bearing on the effective use or operation of this product.

3.10 Sampling Plan

A plan according to which one or more samples are taken in order to obtain information and possibility to reach a decision.

3.11 Limiting Quality LQ₁₀

In a sampling plan, a quality level which corresponds to a specified and relatively low probability of acceptance - in this case 10% probability of acceptance. It is the limiting lot quality characteristic that a lot of this quality would occur.

When expressed as a percent defective, it may be referred to as a lot tolerance percent defective.

3.12 Acceptable Quality Level

A quality level which in a sampling plan corresponds to a specified but relatively high probability of acceptance.

It is the maximum percent defective (or the maximum number of defects per hundred units) that, for purposes of sampling inspection, can be considered satisfactory as a process average.

3.13 Finished Item

A fully manufactured product ready for use, inclusive of any possible treatments and/or surface coatings, as specified on the relevant definition drawing.

4. QUALITY ASSURANCE

4.1 General

4.1.1 Material and Surface Treatment

- 4.1.1.1 The quick release pin manufacturer shall provide evidence to the quality assurance authority that the controls for the component material and surface treatment process complies with the relevant specifications, and shall also show that the identity of the product material has been maintained throughout all stages of manufacture.

4.1.2 Records

- 4.1.2.1 The manufacturer shall establish a batch record chart (or card) to the satisfaction of the quality assurance authority. The record shall show the batch quantity and the serial numbers of certificates covering approval of the material. The results of the inspections and tests made to the requirements of this specification shall be recorded and correlated with the batch numbers, and the batch chart (or card) shall show the serial numbers of those records to the satisfaction of the quality assurance authority.

4.1.3 Dimensional Control during Manufacture

- 4.1.3.1 The manufacturer shall satisfy the quality assurance authority that the frequency and results of inspections made at each operation during manufacture of each part are adequate.