

SEMI E181.1-0321

SPECIFICATION FOR PANEL FOUP FOR 510 TO 515 mm PANEL SIZE AND 12 SLOTS

This Standard was technically approved by the Physical Interfaces & Carriers Global Technical Committee.
This edition was approved for publication by the global Audits and Reviews Subcommittee on December 10, 2020. Available at www.semiviews.org and www.semi.org in March 2021.

1 Purpose

1.1 This Specification is part of a suite of Standards to establish basic physical dimensions for the Panel FOUP intended to be used to transport and store panels.

2 Scope

2.1 This Document specifies the dimensions that are specific to the combination of 12-slots Panel FOUP for 510 mm × 515 mm panel. Common dimensions are defined in the Primary Standard.

NOTICE: SEMI Standards and Safety Guidelines do not purport to address all safety issues associated with their use. It is the responsibility of the users of the Documents to establish appropriate safety and health practices, and determine the applicability of regulatory or other limitations prior to use.

3 Terminology

3.1 Abbreviations and Acronyms

- 3.1.1 *BP* — bilateral plane
- 3.1.2 *CL* — centerline
- 3.1.3 *EE* — end effector
- 3.1.4 *FOUP* — front-opening unified pod
- 3.1.5 *FP* — facial plane
- 3.1.6 *HP* — horizontal plane
- 3.1.7 *KC* — kinematic coupling
- 3.1.8 *KCP* — kinematic coupling pin
- 3.1.9 *OHT* — overhead hoist transport
- 3.1.10 *RFID* — radio frequency identification
- 3.1.11 *TIR* — total indicator runout
- 3.1.12 *PLP* — panel level packaging

3.2 Definitions

3.2.1 *Panel FOUP* — used generally as a ‘term’ only within this Document to identify the front-opening carrier used in fabs for Panels.

NOTE 1: Unless otherwise specified, the word ‘carrier’ used herein shall mean Panel FOUP.

3.2.2 *bilateral plane (BP)* — a vertical plane, defining $x=0$ of a system with three orthogonal planes (HP, BP, FP), coincident with the nominal location of the rear primary KCP, and midway between the nominal locations of the front primary KCPs.

3.2.3 *centerline (CL)* — a horizontal line centered vertically on the Panel FOUP door used as the reference for z dimensions of door features.

3.2.4 *facial plane (FP)* — a vertical plane, defining $y=0$ of a system with three orthogonal planes (HP, BP, FP), $y_{33}=194 \pm 0$ mm in front of the nominal location of the rear primary KCP.

3.2.5 *front (of Panel FOUP)* — the part of the Panel FOUP closest to the door.

3.2.6 *horizontal plane (HP)* — a horizontal plane, defining $z=0$ of a system with three orthogonal planes (HP, BP, FP), coincident with the nominal location of the uppermost points (tips) of the three KCPs.

3.2.7 *nominal location* — the value a dimension would have if its tolerance were reduced to zero.

3.2.8 *nominal panel seating plane* — a horizontal plane that bisects the panel pickup volume.

3.2.9 *origin* — the intersection of the BP and FP.

3.2.10 *plane* — a theoretical surface which has infinite width and length, zero thickness and zero curvature.

3.2.11 *rear (of Panel FOUP)* — the part of the Panel FOUP farthest from its door.

3.2.12 *panel deflection* — change in panel shape (TIR) due to gravity while the panel is resting on the Panel FOUP Panel supports with the Panel FOUP door open.

3.2.13 *panel seating plane* — the bottom surface of an ideally rigid flat disk that meets the diameter specification for 515 mm × 510 mm and 600 mm × 600 mm panels, with negligible droop due to gravity, as it rests on the panel supports.

3.2.14 *process carrier* — a device or material, usually Si, ceramic, glass, or metal, that provides temporary mechanical support to hold one or more panels during processing.

3.2.15 *panel* — the rectangular base material to implement panel level packaging processes.

3.2.16 *panel substrate* — the rectangular starting material (often epoxy or glass) that can be used to implement panel level packaging processes.

4 Requirements for Panel FOUP

4.1 Individual specifications for the 510 mm × 515 mm panel and 12 slots are listed in Figures 1 and 2, and Tables 1 and 2.




Figure 1
Overall Views of Panel FOUP