

SEMI E19.1-0309

STANDARD MECHANICAL INTERFACE (SMIF), SPECIFICATION FOR 100 mm (4 in.) PORT

This Standard was technically approved by the Physical Interfaces & Carriers Global Technical Committee. This edition was approved for publication by the global Audits and Reviews Subcommittee on January 2, 2009. Available at www.semiviews.org and www.semi.org in March 2009; originally published in 1991; previously published July 2002.

The complete specification for this interface includes all general requirements of SEMI E19.

1 Purpose

1.1 The purpose of this Document is to quantify the requirements for a 100 mm (4 in.) cassette SMIF interface.

2 Scope

2.1 This Specification provides the 100 mm (4 in.) specific values of all alpha-numeric variables (e.g., A1) defined in SEMI E19.

NOTICE: SEMI Standards and Safety Guidelines do not purport to address all safety issues associated with their use. It is the responsibility of the users of the Documents to establish appropriate safety and health practices, and determine the applicability of regulatory or other limitations prior to use.

3 Requirements

3.1 The complete specification of this interface includes all the general requirements of SEMI E19. Table 1 provides the specific values for 100 mm (4 in.) cassette SMIF ports.

4 Referenced Standards and Documents

4.1 *SEMI Standards and Safety Guidelines*

SEMI E19 — Standard Mechanical Interface (SMIF)

NOTICE: Unless otherwise indicated, all documents cited shall be the latest published versions.

Table 1 Port Dimensions for 100 mm (4 in.) Wafer Cassette

Port Door	A1	73.02 mm $\pm$ 0.13 mm	(2.875 in. $\pm$ 0.005 in.)
	A2	73.02 mm $\pm$ 0.13 mm	(2.875 in. $\pm$ 0.005 in.)
	A3	9.53 mm $\pm$ 0.25 mm	(0.375 in. $\pm$ 0.010 in.)
Guide Rails	B1	90.17 mm $\pm$ 0.13 mm	(3.550 in. $\pm$ 0.005 in.)
	B2	82.55 mm $\pm$ 0.13 mm	(3.250 in. $\pm$ 0.005 in.)
	B3	6.35 mm $\pm$ 0.25 mm	(0.250 in. $\pm$ 0.010 in.)
	B4	6.35 mm $\pm$ 0.25 mm	(0.250 in. $\pm$ 0.010 in.)
	B5	17.78 mm (0.700 in.)	maximum
	B6	12.70 mm (0.500 in.)	minimum
	B7		
	B8	3.18 mm $\pm$ 0.25 mm	minimum
	B9	6.35 mm (0.250 in.)	maximum radius
Latch Pins	C1	81.25 mm $\pm$ 0.13 mm	(3.200 in. $\pm$ 0.005 in.)
	C2	6.35 mm $\pm$ 0.13 mm	(0.250 in. $\pm$ 0.005 in.)
	C3		
	C4		
	C5	3.18 mm $\pm$ 0.05 mm	(0.125 in. $\pm$ 0.002 in.)

	C6	6.35 mm $\pm$ 0.25 mm	(0.250 in. $\pm$ 0.010 in.)
	C7	Full spherical radius	
	C8	4.44 mm (0.175 in.)	minimum
Registration Pins	D1	101.60 mm $\pm$ 0.13 mm	(4.000 in. $\pm$ 0.005 in.)
	D2	50.80 mm $\pm$ 0.13 mm	(2.000 in. $\pm$ 0.005 in.)
	D3	114.30 mm $\pm$ 0.13 mm	(4.500 in. $\pm$ 0.005 in.)
	D4	57.15 mm $\pm$ 0.13 mm	(2.250 in. $\pm$ 0.005 in.)
	D5	6.35 mm $\pm$ 0.08 mm	(0.250 in. $\pm$ 0.003 in.)
	D6	10.16 mm $\pm$ 0.25 mm	(0.400 in. $\pm$ 0.010 in.)
	D7	Full spherical radius	
Latch Pin Force each	F1	1.36 kg (3 lb.)	minimum
	F2	1.36 kg (3 lb.)	minimum
Position of Cassette	G1	12.70 mm $\pm$ 0.25 mm	(0.500 in. $\pm$ 0.010 in.)
	G2	0.50 mm (0.020 in.)	maximum

NOTICE: SEMI makes no warranties or representations as to the suitability of the Standards and Safety Guidelines set forth herein for any particular application. The determination of the suitability of the Standard or Safety Guideline is solely the responsibility of the user. Users are cautioned to refer to manufacturer's instructions, product labels, product data sheets, and other relevant literature, respecting any materials or equipment mentioned herein. Standards and Safety Guidelines are subject to change without notice.

By publication of this Standard or Safety Guideline, SEMI takes no position respecting the validity of any patent rights or copyrights asserted in connection with any items mentioned in this Standard or Safety Guideline. Users of this Standard or Safety Guideline are expressly advised that determination of any such patent rights or copyrights and the risk of infringement of such rights are entirely their own responsibility.