

SEMI E19.3-0309

STANDARD MECHANICAL INTERFACE (SMIF), SPECIFICATION FOR 150 mm (6 inch) PORT

This standard was technically approved by the global Physical Interfaces & Carriers Committee. This edition was approved for publication by the global Audits and Reviews Subcommittee on January 2, 2009. It was available at www.semi.org in February 2009 and on CD-ROM in March 2009. Originally published in 1991; previously published June 1997.

The complete specification for this interface includes all general requirements of SEMI E19.

1 Purpose

1.1 The purpose of this document is to quantify the requirements for a 150 mm (6 inch) cassette SMIF interface.

2 Scope

2.1 This specification provides the 150 mm (6 inch) specific values of all alpha-numeric variables (e.g., A1) defined in SEMI E19.

NOTICE: This standard does not purport to address safety issues, if any, associated with its use. It is the responsibility of the users of this standard to establish appropriate safety and health practices and determine the applicability of regulatory or other limitations prior to use.

3 Requirements

3.1 The complete specification of this interface includes all the general requirements of SEMI E19. Table 1 provides the specific values for 150 mm (6 inch) cassette SMIF ports.

4 Referenced Standards and Documents

SEMI E19 — Standard Mechanical Interface (SMIF)

NOTICE: Unless otherwise indicated, all documents cited shall be the latest published versions.

Table 1 Port Dimensions for 150 mm (6 inch) Wafer Cassette

Port Door	A1	98.48 mm $\pm$ 0.13 mm	(3.875 in. $\pm$ 0.005 in.)
	A2	98.48 mm $\pm$ 0.13 mm	(3.875 in. $\pm$ 0.005 in.)
	A3	9.53 mm $\pm$ 0.25 mm	(0.375 in. $\pm$ 0.010 in.)
Guide Rails	B1	115.57 mm $\pm$ 0.13 mm	(4.550 in. $\pm$ 0.005 in.)
	B2	107.95 mm $\pm$ 0.13 mm	(4.250 in. $\pm$ 0.005 in.)
	B3	6.35 mm $\pm$ 0.25 mm	(0.250 in. $\pm$ 0.010 in.)
	B4	6.35 mm $\pm$ 0.25 mm	(0.250 in. $\pm$ 0.010 in.)
	B5	17.78 mm (0.700 in.)	maximum
	B6		
	B7	12.70 mm (0.500 in.)	minimum
	B8	3.18 mm $\pm$ 0.25 mm	(0.125 in. $\pm$ 0.010 in.)
	B9	6.35 mm (0.250 in.)	maximum radius

Latch Pins	C1	106.68 mm $\pm$ 0.13 mm	(4.200 in. $\pm$ 0.005 in.)
	C2	6.35 mm $\pm$ 0.13 mm	(0.250 in. $\pm$ 0.005 in.)
	C3	63.50 mm $\pm$ 0.13 mm	(2.500 in. $\pm$ 0.005 in.)
	C4	3.18 mm $\pm$ 0.05 mm	(0.125 in. $\pm$ 0.002 in.) diameter
	C5		
	C6	6.35 mm $\pm$ 0.25 mm	(0.250 in. $\pm$ 0.010 in.)
	C7	Full spherical radius	
	C8	4.44 mm (0.175 in.)	minimum
Registration	D1	152.40 mm $\pm$ 0.13 mm	(6.000 in. $\pm$ 0.005 in.)
	D2	76.20 mm $\pm$ 0.13 mm	(3.000 in. $\pm$ 0.005 in.)
	D3	165.10 mm $\pm$ 0.13 mm	(6.500 in. $\pm$ 0.005 in.)
	D4	82.55 mm $\pm$ 0.13 mm	(3.250 in. $\pm$ 0.005 in.)
	D5	6.35 mm $\pm$ 0.08 mm	(0.250 in. $\pm$ 0.003 in.)
	D6	10.16 mm $\pm$ 0.25 mm	(0.400 in. $\pm$ 0.010 in.)
	D7	Full spherical radius	
Latch Pin Force each	F1	1.36 kg (3 lb)	minimum
	F2	1.36 kg (3 lb)	minimum
Position of Cassette	G1	12.70 mm $\pm$ 0.25 mm	(0.500 in. $\pm$ 0.010 in.)
	G2	0.50 mm (0.020 in.)	maximum

NOTICE: SEMI makes no warranties or representations as to the suitability of the standard(s) set forth herein for any particular application. The determination of the suitability of the standard(s) is solely the responsibility of the user. Users are cautioned to refer to manufacturer's instructions, product labels, product data sheets, and other relevant literature respecting any materials or equipment mentioned herein. These standards are subject to change without notice.

By publication of this standard, Semiconductor Equipment and Materials International (SEMI) takes no position respecting the validity of any patent rights or copyrights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of any such patent rights or copyrights, and the risk of infringement of such rights are entirely their own responsibility.