

SEMI E90.1-0706

PROVISIONAL SPECIFICATION FOR SECS-II PROTOCOL

SUBSTRATE TRACKING

This standard was technically approved by the global Information & Control Committee. This edition was approved for publication by the global Audits and Reviews Subcommittee on May 16, 2006. It was available at www.semi.org in June 2006 and on CD-ROM in July 2006. Originally published March 2001; previously published July 2005.

1 Purpose

1.1 This document maps the services and data of SEMI E90 to SECS-II streams and functions, and data definitions.

2 Scope

2.1 This is a specification covering equipment supporting automated substrate tracking.

2.2 This document applies to all implementations of SEMI E90 that use the SECS-II message protocol (SEMI E5). Compliance to this standard requires compliance to both SEMI E90 and SEMI E5.

2.3 This standard is provisional. To have the provisional status removed, the following must be completed:

- Table 1 — Services Message Mapping Table
- Table 3 — Services Parameters to SECS-II Data Items Mapping

NOTICE: This standard does not purport to address safety issues, if any, associated with its use. It is the responsibility of the users of this standard to establish appropriate safety and health practices and determine the applicability of regulatory or other limitations prior to use.

3 Referenced Standards and Documents

3.1 SEMI Standards

SEMI E5 — SEMI Equipment Communications Standard 2 Message Content (SECS-II)

SEMI E30 — Generic Model for Communications and Control of Manufacturing Equipment (GEM)

SEMI E39.1 — SECS-II Protocol for Object Services Standard (OSS)

SEMI E53 — Event Reporting

NOTICE: Unless otherwise indicated, all documents cited shall be the latest published versions.

4 Mapping

4.1 This section shows the specific SECS-II streams and functions that shall be used for SECS-II implementation of the services defined in SEMI E90, as well as the parameter mapping for data attached to services.

4.2 Message Mapping

4.2.1 *Services Message Mapping* — Table 1 defines the relationships between SEMI E90 services and SECS-II messages.

4.2.2 *Event Message Mapping* — Table 2 defines the relationships between SEMI E90 collection events and SECS-II messages.

Table 1 Services Message Mapping Table

Service Name	Stream, Function	SECS-II Message Name
change substrate state	(not yet defined)	(not yet defined)
register substrate	S14,F9/10	Create Object Request/Acknowledge [SEMI E39.1]

Service Name	Stream, Function	SECS-II Message Name
remove substrate	S14,F11/12	Delete Object Request/Acknowledge [SEMI E39.1]
UpdateSubstrateObject	S14F19/F20	Generic Service Request/Acknowledge
ProceedWithSubstrate	S14F19/F20	Generic Service Request/Acknowledge
CancelSubstrate	S14F19/F20	Generic Service Request/Acknowledge

Table 2 Event Message Mapping Table

Event Name	Stream, Function	SECS-II Message Name
All state model transitions	If SEMI E30 style events: S6F11/12 If SEMI E53 style events: S6F11/12 S6F13/14	If SEMI E30 style events: Event Report Send/Acknowledge If SEMI E53 style events: Event Report Send/Acknowledge Annotated Event Report Send/Ack

4.3 *Parameter Mapping* — Table 3 defines the relationships between SEMI E90 service parameters and SECS-II data definitions.

Table 3 Service Parameters to SECS-II Data Items Mapping

Parameter Name	Range	SECS-II Data Item
ErrorCode	Enumerated.	ERRCODE
ErrorText	1 to 80 characters.	ERRTEXT
ObjectAction	“UpdateSubstrateObject”.	SVCNAME
ObjectActionStatus	List of service acknowledge and status.	L,2 1. SVCACK 2. Status
ObjectAction-ParameterResult	(List of) name value pairs providing information about the attributes successfully set.	L,n 1. L,2 1. SPNAME ₁ 2. SPVAL ₁ : n. L,2 1. SPNAME _n 2. SPVAL _n
ObjectLinkID	51.	LINKID
OperationID	51.	OPID
STAcknowledge	0 if success; 1 if error (Conforms to ObjAck in SEMI E39.1).	OBJACK
Status	List of error information.	L,n n = number of errors 1. L,2 1. <ErrorCode ₁ > 2. <ErrorText ₁ > . . n. L,2 1. <ErrorCode _n > 2. <ErrorText _n >
STStatus	STAcknowledge and Status.	L,2 1. <STAcknowledge> 2. <Status>

<i>Parameter Name</i>	<i>Range</i>	<i>SECS-II Data Item</i>
SubstID	1–80 characters (Conforms to ObjID in SEMI E39.1).	OBJID
SubstIDList (ordered list of)	List of Substrate IDs.	L,n n = number of substrate identifiers 1. <SubstID ₁ > . . n. <SubstID _n >
SubstLocID	1–80 characters (Conforms to ObjID in SEMI E39.1).	OBJID
SubstLocIDList (ordered list of)	List of Substrate Location ID's corresponding to the SubstIDList (ordered list of).	L,n n = number of substrate identifiers in SubstIDList (ordered list of) 1. <SubstLocID ₁ > . . n. <SubstLocID _n >
SubstProcState	Enumerated per Variable SubstProcState.	U1
SubstProcStateList (ordered list of)	List of Substrate Processing States corresponding to the SubstIDList (ordered list of).	L,n n = number of substrate identifiers in SubstIDList (ordered list of) 1. <SubstProcState ₁ > . . n. <SubstProcState _n >
SubstrateObject-Attributes	(List of) substrate object attribute names and values.	L,n 1. L,2 1. SPNAME ₁ 2. SPVAL ₁ : n. L,2 1. SPNAME _n 2. SPVAL _n
SubstState	Enumerated per Variable SubstState.	U1
SubstStateList (ordered list of)	List of Substrate Transport States corresponding to the SubstIDList (ordered list of).	L,n n = number of substrate identifiers in SubstIDList (ordered list of) 1. <SubstState ₁ > . . n. <SubstState _n >

4.4 *SECS-II Data Items without Corresponding SEMI E90 Parameters* — Table 4 contains the SECS-II data items that do not correspond to SEMI E90's service parameter.

Table 4 Additional Data Item Requirements Table

<i>Function</i>	<i>SECS-II Data Item</i>
"TimeIn" from SubstHistory variable data definition	TIMESTAMP.
"TimeOut" from SubstHistory variable data definition	A[0] if the substrate(s) remain in the location. TIMESTAMP if the substrate(s) have departed the location.

5 Variable Data Item Mapping

5.1 Table 5 shows the specific SECS-II data classes, and formats needed for SECS-II implementations of SEMI E90 variable data items.