

SEMI M31-0718

SPECIFICATION FOR MECHANICAL FEATURES OF FRONT-OPENING SHIPPING BOX USED TO TRANSPORT AND SHIP 300 mm WAFERS

This Standard was technically approved by the Silicon Wafer Global Technical Committee. This edition was approved for publication by the global Audits and Reviews Subcommittee on February 1, 2018. Available at www.semiviews.org and www.semi.org in July 2018; originally published June 1998; previously published July 2008.

NOTICE: This Standard or Safety Guideline has an Inactive Status because the conditions to maintain Current Status have not been met. Inactive Standards or Safety Guidelines are available from SEMI and continue to be valid for use.

NOTICE: The section symbol (§) is used to reference a numbered section, paragraph, or header and all subordinate paragraphs, headers, and embedded material (i.e., EXCEPTIONs, lists) therein. The paragraph symbol (¶) is used to reference a particular numbered paragraph and embedded material therein. When duplicated (i.e., §§ and ¶¶) the symbols are used to reference more than one section or paragraph, respectively.

NOTICE: Paragraphs entitled ‘NOTE:’ are not an official part of this Standard or Safety Guideline and are not intended to modify or supersede the official Standard or Safety Guideline. These have been supplied by the global technical committee to enhance the usage of the Standard or Safety Guideline.

1 Purpose

1.1 This Standard specifies the front-opening shipping box (FOSB) used to ship 300 mm wafers from wafer suppliers to their customers (typically IC manufacturers), while maintaining wafer quality.

NOTE 1: Refer to SEMI silicon wafer related specifications M-series such as SEMI M1 as for a wafer quality.

2 Scope

2.1 This Standard is intended to set an appropriate level of specification that places minimal limits on innovation while ensuring modularity and interchangeability at all mechanical interfaces. However, this Standard has been written so that injection-molded plastic FOSBs can be manufactured in conformance with it, and those can be utilized for maintaining wafers quality during transportation, opening and closing the door.

2.2 This Standard assumes that the FOSB is used in the last process in wafer manufacturing, in acceptance and inspection, and in transferring the wafers from the FOSB to a front-opening unified pod (FOUP), front-opening box for interfactory transport (FOBIT) or open cassette inside an IC manufacturing facility. The FOSB is not intended to be used in IC manufacturing processes. It is recommended that wafers be transferred from the FOSB to a FOUP, FOBIT or open cassette using automated methods. As described in ¶ 5.4, the purchaser needs to specify which type of FOSB door is required:

1. Manual door as described in ¶ 5.4.1; or
2. Automated-shippable door as described in ¶ 5.4.2.

NOTICE: SEMI Standards and Safety Guidelines do not purport to address all safety issues associated with their use. It is the responsibility of the users of the Documents to establish appropriate safety and health practices, and determine the applicability of regulatory or other limitations prior to use.

3 Referenced Standards and Documents

3.1 SEMI Standards and Safety Guidelines

SEMI E1.9 — Mechanical Specification for Cassettes Used to Transport and Store 300 mm Wafers

SEMI E15 — Specification for Tool Load Port

SEMI E15.1 — Specification for 300 mm Tool Load Port

SEMI E47.1 — Mechanical Specification for FOUPS Used to Transport and Store 300 mm Wafers

SEMI E57 — Specification for Kinematic Couplings Used to Align and Support 300 mm Wafer Carriers

SEMI E62 — Specification for 300 mm Front-Opening Interface Mechanical Standard (FIMS)

SEMI M45 — Specification for 300 mm Wafer Shipping System

SEMI S8 — Safety Guideline for Ergonomics Engineering of Semiconductor Manufacturing Equipment

3.2 ISO® Standards¹

ISO/IEC 16022 — International Technology – Automatic Identification and Data Capture Techniques – Data Matrix Bar Code Symbology Specification

NOTICE: Unless otherwise indicated, all documents cited shall be the latest published versions.

4 Terminology

4.1 Definitions

4.1.1 *bilateral datum plane* — a vertical plane that bisects the wafers and that is perpendicular to both the horizontal and facial datum planes. [SEMI E57]

4.1.2 *box* — a protective portable container for a carrier and/or substrate(s).

4.1.3 *carrier* — an open structure that holds one or more substrates.

4.1.4 *carrier bottom domain* — volume (below z6 above the horizontal datum plane) that contains the bottom of the carrier. [SEMI E1.9]

4.1.5 *carrier capacity* — the number of substrates that a carrier holds. [SEMI E1.9]

4.1.6 *carrier sensing pads* — surfaces on the bottom of the carrier for triggering optical or mechanical sensors.

4.1.7 *carrier side domains* — volumes (from z6 above the horizontal datum plane to z15 above the top nominal wafer seating plane) that contain the mizo teeth or slots that support the wafer and the supporting columns on the sides and rear of the carrier.

4.1.8 *carrier top domain* — volume (higher than z15 above the top wafer) that contains the top of the carrier.

4.1.9 *facial datum plane* — a vertical plane that bisects the wafers and that is parallel to the front side of the carrier (where wafers are removed or inserted). On tool load ports, it is also parallel to the load face plane specified in SEMI E15 on the side of the tool where the carrier is loaded and unloaded. [SEMI E57]

4.1.10 *front-opening shipping box (FOSB)* — a shipping box with a front-opening interface.

4.1.11 *front-opening unified pod (FOUP)* — a box (that complies with SEMI E47.1) with a nonremovable cassette (so that its interior complies with SEMI E1.9) and with a front-opening interface (that mates with a FIMS port that complies with SEMI E62). [SEMI E47.1]

4.1.12 *front-opening box for interfactory transport (FOBIT)* — box for interfactory transport between IC manufacturing sites.

4.1.13 *horizontal datum plane* — a horizontal plane from which projects the kinematic-coupling pins on which the carrier sits. On tool load ports, it is at the load height specified in SEMI E15 and might not be physically realized as a surface. [SEMI E57]

4.1.14 *minienvironment* — a localized environment created by an enclosure to isolate the product from contamination and people.

4.1.15 *nominal wafer centerline* — the line that is defined by the intersection of the two vertical datum planes (facial and bilateral) and that passes through the nominal centers of the seated wafers (which must be horizontal when the carrier is placed on the coupling). [SEMI E57]

¹ International Organization for Standardization, ISO Central Secretariat, Chemin de Blandonnet 8, CP 401-1214 Vernier, Geneva, Switzerland; Telephone: +41.22.749.01.11, Fax: +41.22.733.34.30, <http://www.iso.org>. ISO trademark is owned by International Organization for Standardization.

4.1.16 *optical wafer sensing paths* — lines of sight for optically sensing the positions of the wafers. Several horizontal optical wafer sensing paths are present in between the carrier side domains. In addition, two vertical optical wafer sensing paths are created by rectangular exclusion zones in the front of the carrier top and bottom. [SEMI E1.9]

4.1.17 *shipping box* — a protective portable container for a carrier and/or wafer(s) that is used to ship wafers from the wafer suppliers to their customers.

4.1.18 *shipping-box front-opening mechanical interface (SFMI)* — optional automated-shippable door style for a FOSB that is compatible with SEMI E62, and must be considered characteristics with exceptions as noted in ¶ 5.4.2.

4.1.19 *virtual tracking unit* — an entity (which could be a number of substrates or an individual die or mask group) that the factory floor control system treats as a single unit for tracking purposes. [SEMI E1.9]

4.1.20 *wafer carrier* — any cassette, box, pod, or boat that contains wafers. [SEMI E15]

4.1.21 *wafer extraction volume* — the open space for extracting a wafer from the carrier.

4.1.22 *wafer pick-up volume* — the space that contains entire bottom of a wafer if the wafer has been pushed to the rear of the carrier.

4.1.23 *wafer set-down volume* — the open space for inserting and setting down a wafer in the carrier.

4.1.24 *2D code placement area* — an area on the door and another area on top of the shell, where a 2D code can be placed.

4.1.25 *2D code* — a code identifying elements such as maker, model, version and serial number of a FOSB, by using a data matrix ECC200 symbol according to ISO/IEC 16022.

5 Requirements

5.1 The FOSB has the following components and subcomponents:

Key:

- Required feature
- ◊ Optional feature
- Rear
 - ◊ RFID Tag Placement Volume
- Door on front
 - ◊ Manual door (optional)
 - ◊ Automated door (optional)
 - ◊ 2D code placement area (optional)
 - Holes for latch keys that lock the door to the SFMI interface when the door is unlatched from the box
 - Holes for registration pins
 - Door presence sensing areas
- Top
 - ◊ Top robotic handling flange (optional)
 - ◊ 2D code placement area (optional)
- Interior
 - Cassette with supports for 13 or 25 wafers
 - Wafer retainer
 - End effector exclusion zone

- Sides
- ◊ Ergonomic manual handles (optional)
- Bottom
 - 5 carrier sensing pads
 - 4 Info pads
 - 3 features that mate with kinematic coupling pins and provide a 10 mm lead-in
 - ◊ 3 features that mate with kinematic coupling pins and provide a 15 mm lead-in (optional)
 - ◊ Retaining features for manual door (optional)
 - Retaining features for automated-shippable door

5.2 Kinematic Couplings — The physical alignment mechanism from the FOSB to the tool load-port (or a nest on a vehicle or in a stocker) consists of features (not specified in this Standard) on the top entity that mate with three or six pins underneath as defined in SEMI E57. The three features that mate with the kinematic coupling pins must provide a lead-in capability that corrects a FOSB misalignment of up to $r69$ in any horizontal direction.

5.3 Inner and Outer Radii — All required concave features may have a radius of up to $r65$ to allow cleaning and to prevent contaminant build-up. All required convex features may also have a radius of up to $r66$ to prevent small contact patches with large stresses that might cause wear and particles. Note that these limits on the radius of all required features are specified as a maximum (not a minimum) to ensure that the required features are not rounded off too much. The lower bound on the radius is up to the FOSB supplier. Note also that this radius applies to every required feature unless another radius is called out specifically. Here a required feature is an area on the surface of the FOSB supplier. Note also that this radius applies to every required feature unless another radius is called out specifically. Here a required feature is an area on the surface of the FOSB specified by a dimension (or intersections of dimensions) that has a tolerance and not just a maximum or minimum (such as the edges of the robotic handling flange).

5.4 Door — It is recommended that the FOSB not be vertical when it is opened or closed. When the FOSB is in a vertical orientation with the door removed, the wafers must be restrained from touching each other by appropriate wafer support design or other retaining techniques.

5.4.1 Manual Door — If chosen, the manual door option requires no automation to open the door. An exclusion zone surrounding the manual door area is specified in the Standard. There are several possible techniques for sealing and clamping the manual door that meet user requirements. Therefore, only an exclusion zone surrounding the manual door area is specified in this Standard. All features of the door and door retaining mechanism must lie within the exclusion zone illustrated in Figure 1 and must not interfere with other specified features (including the kinematic couplings). Figure 1 and dimensions $x81$, $y50$, $y81$, $y82$, $z47$, $z48$ and $z49$ define the manual door area and therefore apply only to the manual door option as described in this section. The $y81$ dimension applies from the horizontal datum plane to the top surfaces of the FOSB ($z47 - z48$ or $z47 + z49$ at the upper door frame volume specified by $y50$).

5.4.2 Automated-Shippable Door — If chosen, the automated-shippable door must be designed to mate with a port that conforms to SEMI E62. However, following characteristics of automate-shippable door must be considered.

5.4.2.1 Wafer Retaining Structure — The slot is usually designed that wafers are suspended in the slot without contacting the surface of the slot for preventing the damage during transportation when FOSB door is closed. It should be noted that wafer position of FOSB is different from that of FOUP when the door is closed due to the wafer retaining structure.

5.4.2.2 Rear of Door ($y51$) — For manual door, FOSB has a $y51 \geq 50$ mm to hold wafers in large area at front wafer retainer for keeping wafer quality during transportation. For automated-shippable door, FOSB has a $y51 \geq 140$ mm to comply with SEMI E47.1.

5.4.2.3 Force with Which the Load Port Presses the Box Door into the Box ($f34$: defined by SEMI E62) — $f34$ is related to wafer retaining force though, need to consider door is pulled by latching too. The gap $y88$ shall be zero (or even can have a slightly negative value compared to the 'datum measured from' in Table 3), when the load port applies a force $f34$ of 110 N or more. Even though, $f34$ is increased, minimum force applied to wafer would be recommended for eliminating damage to the wafers in dynamic motion for opening and closing the door.

5.4.2.4 *Latch Key Torque (f30: defined by SEMI E62)* — The required latch key torque depends on the closing force.

5.4.2.5 A FOSB with an automated-shippable door should be able to withstand a force when applied to one of the retaining features of up to 40 N (f61) in any direction without negative impact to the intended function of the FOSB (e.g., shell deformation, wafer positions, door closing capabilities).

5.4.2.6 *Gap (y88)* — The distance between 1) the FOSB Door Front in the fully seated position when the door is closed on a FOSB containing up to 25 wafers, and 2) the FOSB Door Front at the stage when the latch keys are allowed to be turned. The Gap value is specified by y88 where y88 is added to the measured y52 dimension of the FOSB. This would result in the dimension of the front of the automated-shippable door from the facial datum plane being equal to the measured y52 value plus y88 (refer to Figure 15). Note:

- a) The FOSB door may not be pushed to the fully seated position by f34. There might be a gap left of up to y88, especially when a force close to the lower limit of f34 will be applied. Fully seated within this context should be understood as the static position of the FOSB door within the box shell, when the box is completely closed and the box front features are within the limits as defined by y52 of SEMI M31.
- b) Final closing, which includes a movement of the FOSB door to its fully seated position, is accomplished by turning latch keys as described in ¶ 5.4 of SEMI E62.
- c) Measured y52 is the physical measurement of the y52 dimension of the FOSB, within the tolerance as specified for y52 in SEMI M31.
- d) The gap y88 may have a size of up to the maximum value defined in Table 3, when a load port applies the minimum force f34 as defined in SEMI E62 for a FOSB.
- e) The current size of the gap y88, within the given limits, may depend both from the actual amount of force f34 applied by a load port as well as from the specific design of the FOSB.

5.5 *Seal Zones for Door* — In the Front Opening Shipping Box Automated Door Option the automated box door is on the front side of the box (corresponding to the front side of the carrier where wafers are accessed so the door is perpendicular to the wafers and parallel to the facial datum plane). The automated door and the carrier frame must have surfaces that mate with the seal zones defined in SEMI E62. Specifically, the FOSB automated box door option and the carrier frame must have surfaces that made with the seal zones and the reserved spaces for vacuum application (which includes all of the circles bounded by r38 except for the holes for the registrations at the center of each circle) defined in § 5 of SEMI E62 (which specifies r38 as well as the seal zone dimensions). These automated door and frame surfaces must be a distance of y52 from the facial datum plane and must have a flatness of y42. No surface on the automated door may project further from the facial datum plane than the door seal zone and the reserved spaces for vacuum application. The automated door must also be designed so that when the box is pressed against the FIMS port, both latch keys on the port are inserted to their full length. Furthermore, when the latch keys are turned more than 45° toward the position that unlocks the automated door from the box, the latch key holes on the door must be such that the door is not removable from the latch keys. There are no door seal zone requirements for the manual door option, but a FOSB with the manual door must contain a frame seal zone that meets the frame seal zone requirements specified in this section.

5.6 *Wafer Retaining* — When the FOSB is closed, the wafers must be retained in the FOSB to prevent movement during subsequent handling, including shipping. It should be noted that wafers are typically shipped in a vertical orientation and generally require support from a secondary package. It is recommended that this secondary package be designed to allow for easy removal of the FOSB from the secondary package.




Figure 1
Manual Door Area

5.7 Wafer Orientation and Numbering — The wafers must be horizontal when the FOSB is placed on the coupling, and the wafers slots are numbered in increasing order from bottom to top (so the bottom wafer is wafer number 1, the next wafer up is wafer number 2, etc.).

5.8 Internal Horizontal Dimensions — Figure 2 shows a cross-section of the horizontal boundaries of the FOSB side domains (which contain the parts of the FOSB higher than z_6 above the horizontal datum plane and lower than z_{15} above the top wafer). In this and following figures, the most heavy lines are used for surfaces that have tolerances (not surfaces that have only maximum or minimum dimensions).




Figure 2
Top View of FOSB Internal Dimensions

5.9 Internal Vertical Dimensions — Figures 3 through 7 show the vertical dimensions of the internal FOSB. Note that z_8 (the height of the bottom nominal wafer seating plane above the horizontal datum plane) and z_{12} (the distance between adjacent nominal wafer seating planes) are given as absolute distances with no tolerance. This means that the sum of actual height variations in the FOSB from the kinematic coupling to the supporting features holding each wafer

must be contained within the tolerance of z_{10} with no further stack-up at each higher wafer. The method for meeting this requirement is left up to the FOSB supplier. Table 2 defines all dimensions for Figures 3 through 7.




Figure 3
Side View of FOSB Internal Dimensions




Figure 4
Front View of FOSB Internal Dimensions




Figure 5
Upper Cross-Section at Facial Datum Plane

5.9.1 Wafer Set-Down Volume — The open space for the wafer set-down volume consists of a cylindrical section with radius $r2$ and a main axis parallel to and $y1$ in front of the nominal wafer centerline. The top of this cylindrical section is $z11$ above the nominal wafer seating plane and its bottom is $z10$ above the nominal wafer seating plane. The implications for wafer positioning of the tolerance on $r2$ are as follows. The wafers should be placed in the FOSB within a circle of radius corresponding to the smaller bound on $r2$ to avoid touching the edge of the wafer to the side of the FOSB. Once the wafer has been placed, the FOSB must not allow a wafer to move outside of a circle of radius corresponding to the larger bound on $r2$. There are two exceptions to this limit on wafer movement. When the wafer is pushed toward the rear of the FOSB, the location of the wafer is defined by the wafer pick-up volume (refer to ¶ 5.9.3). When the FOSB is gently tilted forward up to 45° , the wafers may slide forward, but it is recommended that they not extend further than $y20$ from the facial datum plane. This may be accomplished by designing the teeth supporting the wafers to include a ‘wafer stopper’ at the front that is outside of $r2$ and under $z29$ as illustrated in Figure 6.

5.9.2 Wafer Extraction Volume — The open space for the wafer extraction volume includes a cylindrical section with radius $r3$ and a main axis parallel to and $y1$ in front of the nominal wafer center line. The top of this cylindrical section is $z11$ above the nominal wafer seating plane and its bottom is $z23$ above the nominal wafer seating plane. The wafer extraction volume also includes the extrusion out the front of the FOSB of this cylindrical section and the portion of the wafer set-down volume above $z29$. The implications for wafer extraction of the definition of dimension $r3$ ($r3 \geq r2 + 1$) are as follows. The FOSB must give an extra 1 mm (0.04 in.) of horizontal clearance once the wafer is picked up from wherever it ends up (within the bounds of $r2$) after transport in the FOSB.