



The attached SMPTE Engineering Document has been declared “Stable” by the controlling Technology Committee.

The SMPTE Operations Manual for Standards states:

A document should be stabilized if it is believed to be substantially correct, does not contain harmful or misleading recommendations, may still be relevant to equipment or practices in use, is stable, but does not represent current technology, and need not be subject to future reviews.

A Stable document shall still be made available and offered for sale by the Society, but it shall be prefaced by a cover page explaining its current status.

At any time, a Technology Committee may revise, amend, or otherwise initiate a new Project on a Stable document.

A Stable document is “In Force”, and not deprecated or withdrawn.

*** * * * ***

Note:

SMPTE “Stable” documents were previously described as “Archived” and the attached document may be marked as “Archived”. The status of a SMPTE document described as “Archived” is exactly as described above for a “Stable” document.

Stable documents may not adhere to the latest style and format of SMPTE documents, or to current usage of normative language. Suitable care should be taken in interpretation.

SMPTE RECOMMENDED PRACTICE

RP 176-1997

Revision of RP 176-1993

Derivation of Reference Signals for Television Camera Color Evaluation



Page 1 of 2 pages

1 Scope

This practice is intended to define the numerical procedure for deriving reference video signals for television camera evaluation. A standard reflection test pattern is assumed and the signal levels computed by this procedure are the signals to be expected from an ideal camera as defined by the television system color specifications.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this practice. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this practice are encouraged to investigate the possibility of applying the most recent edition of the standards indicated below.

ASTM E308-96, Practice for Computing the Colors of Objects by Using the CIE System

CIE Publication 15.2 (1986), Colorimetry

SMPTE RP 177-1993 (R1997), Derivation of Basic Television Color Equations

3 Definitions

The color reproduction objective of television systems is to reproduce all colors as though they were illuminated by CIE illuminant D_{65} . Thus, the ideal or reference camera used in this practice always uses a D_{65} illuminant. This practice utilizes CIE tristimulus values (XYZ) as given in CIE 15.2 to specify color samples, and the normalized primary matrix (NPM) as given in SMPTE RP 177 to derive the ideal camera linear video signal levels (RGB).

4 Input data

4.1 The required data are first the CIE tristimulus values XYZ, computed using CIE illuminant D_{65} , for each of the color patches on the test pattern to be used. One of the patches should be a reference white that will be used for the white balance of the reference camera. If the tristimulus values for the test pattern are not available, they should be computed from the spectral reflectances of the patches using the weighting tables and procedures from CIE 15.2 or ASTM E308. The reflectance data should ideally be measured using 45/0 measuring geometry as specified in CIE 15.2 and be made against an absolute white reflectance reference.

4.2 The second input data required is the normalized primary matrix, NPM, of the television standard for which the camera is being evaluated. This NPM matrix should be derived from the system reference primary chromaticities using the procedure given in SMPTE RP 177. The NPM should be accurate to at least four significant digits and ideally all 10 digits carried in its derivation should be used. The reference system NPM uses a D_{65} white reference by definition.

4.3 The final input data are the equations for the opto-electronic transfer function (gamma correction) for the television standard.

5 General procedure

5.1 The NPM defines the relationship between the normalized linear RGB video levels and CIE tristimulus values XYZ: