



The attached SMPTE Engineering Document has been declared “Stable” by the controlling Technology Committee.

The SMPTE Operations Manual for Standards states:

A document should be stabilized if it is believed to be substantially correct, does not contain harmful or misleading recommendations, may still be relevant to equipment or practices in use, is stable, but does not represent current technology, and need not be subject to future reviews.

A Stable document shall still be made available and offered for sale by the Society, but it shall be prefaced by a cover page explaining its current status.

At any time, a Technology Committee may revise, amend, or otherwise initiate a new Project on a Stable document.

A Stable document is “In Force”, and not deprecated or withdrawn.

*** * * * ***

Note:


SMPTE “Stable” documents were previously described as “Archived” and the attached document may be marked as “Archived”. The status of a SMPTE document described as “Archived” is exactly as described above for a “Stable” document.

Stable documents may not adhere to the latest style and format of SMPTE documents, or to current usage of normative language. Suitable care should be taken in interpretation.

SMPTE RECOMMENDED PRACTICE**RP 84-1996**

Revision of RP 84-1992

Reference Carrier Frequencies and Preemphasis Characteristics for 1-in Type B Helical-Scan Television Analog Recording



Page 1 of 2 pages

1 Scope

This practice specifies the video reference frequencies to which the carrier is deviated and the associated video preemphasis for 1-in type B helical-scan television tape recording. (The video deemphasis to be used in reproduction is specified indirectly by requiring a flat input-to-output video response along with a specified preemphasis in recording.)

2 Electrical parameters**2.1 Modulation system**

The video information shall be recorded in the form of an rf signal frequency modulated by the video signal. The instantaneous frequencies of the rf signal shall vary linearly with respect to the amplitude of the modulating signal.

2.2 Characteristic frequencies

The instantaneous frequencies of the rf signal corresponding to characteristic levels of the video signal shall be as specified in table 1.

2.3 Preemphasis and deemphasis

The time constants of the video emphasis networks shall be as defined in table 2.

Table 1 – Video levels

Video levels	MHz
Synchronization tip	7.06 nom
Blanking	7.90 ± 0.05
Peak white	10.00 ± 0.05

Table 2 – Time constants

Time constants	ns
t_1	240
t_2	600

Annex A (informative)**Transmission characteristics of the signal chain**

The transmission characteristics of the signal chain of a television tape recorder may be defined by one of two methods which are in agreement:

A.1 Definition of the recording chain

For reference purposes, an ideal recording chain is defined as consisting of (a) a modulator having a flat frequency response with respect to the modulating video frequencies, (b) an rf section having a transfer characteristic that produces constant amplitude alternating magnetic flux in the video head pole tips when driven by an alternating signal from the modulator having constant amplitude, and (c) a

video preemphasis network inserted before the modulation stage.

The preemphasis is then defined by the frequency and phase characteristic of a network, such as that shown in figure 1, fed from a low-impedance source and feeding a high-impedance load.

The ideal recording chain described above is intended to be taken as a basis for producing reference tapes to be used for the alignment of television tape recorders.

When using present-day recording chains, the following points should be considered: