



The attached SMPTE Engineering Document has been declared “Stable” by the controlling Technology Committee.

The SMPTE Operations Manual for Standards states:

A document should be stabilized if it is believed to be substantially correct, does not contain harmful or misleading recommendations, may still be relevant to equipment or practices in use, is stable, but does not represent current technology, and need not be subject to future reviews.

A Stable document shall still be made available and offered for sale by the Society, but it shall be prefaced by a cover page explaining its current status.

At any time, a Technology Committee may revise, amend, or otherwise initiate a new Project on a Stable document.

A Stable document is “In Force”, and not deprecated or withdrawn.

*** * * * ***

Note:

SMPTE “Stable” documents were previously described as “Archived” and the attached document may be marked as “Archived”. The status of a SMPTE document described as “Archived” is exactly as described above for a “Stable” document.

Stable documents may not adhere to the latest style and format of SMPTE documents, or to current usage of normative language. Suitable care should be taken in interpretation.

SMPTE STANDARD**SMPTE 216-1998**Revision of
ANSI/SMPTE 216-1985

for Motion-Picture Film (35-mm) — Four-Track Striped Release Prints — Recorded Characteristic of Magnetic Audio Records



Page 1 of 2 pages

1 Scope

This standard specifies the recorded characteristic of magnetic audio records on 35-mm four-track striped motion-picture release prints, when reproduced at 24 frames per second or approximately 90 ft (27 m) per minute.

2 Recorder characteristic

With a constant-amplitude sine-wave signal applied to the input of the recording system, the relative characteristic in effective values of the short circuit magnetic flux versus frequency shall decrease with increasing frequency proportionately to the impedance of a parallel combination of a capacitance and a resistance having time constants of 35 and 3180 μ s (see note 1). The characteristic defined above is obtained by the following equation:

$$L_{\phi} = C_0 - 10 \log_{10} \left(\frac{1 + (2\pi\tau_h)^2 f^2}{1 + 1/[(2\pi\tau_l)^2 f^2]} \right)$$

where L_{ϕ} is the recorded relative short circuit magnetic flux level in decibels, f is the frequency in hertz for which L_{ϕ} is computed, τ_l is the low-frequency time constant of 3180 μ s, τ_h is the high-frequency time constant of 35 μ s, and C_0 is a constant with a value of 0.19424 calculated to make $L_{\phi} = 0$ at the reference frequency of 1000 Hz. The approximate numerical values are given in the table (see note 2).

Frequency, Hz f	Relative level L_{ϕ}
31.5	+ 5.66
40	+ 4.29
50	+ 3.21
80	+ 1.63
100	+ 1.16
160	+ 0.59
400	+ 0.23
1000	0.00
2500	– 0.95
4000	– 2.29
6300	– 4.46
8000	– 5.93
10 000	– 7.47
12 500	– 9.13
16 000	–11.07

3 Tolerances

Magnetic audio records on the film shall be recorded to the characteristic specified in clause 2 within the tolerances given in figure 1.

NOTES

1 A time constant is a shorthand notation, such as illustrated by a frequency response curve, having a shape which results from a time constant of one or more microseconds. This is a convenient way of defining a response curve and is not intended as a recommended electrical circuit.

2 The corresponding reproducing characteristic is that which gives a flat response.

3 It has been shown that a straight 35- μ s curve should be used for optimal use of the magnetic medium. It is recognized, however, that it is necessary for the immediate future to continue to add 3180 μ s because some theater equipment is unable to compensate for the low end.