
SMPTE STABLE DOCUMENT



The attached SMPTE Engineering Document has been declared “Stable” by the controlling Technology Committee.

The SMPTE Operations Manual for Standards states:

A document should be stabilized if it is believed to be substantially correct, does not contain harmful or misleading recommendations, may still be relevant to equipment or practices in use, is stable, but does not represent current technology, and need not be subject to future reviews.

A Stable document shall still be made available and offered for sale by the Society, but it shall be prefaced by a cover page explaining its current status.

At any time, a Technology Committee may revise, amend, or otherwise initiate a new Project on a Stable document.

A Stable document is “In Force”, and not deprecated or withdrawn.

*** * * * ***

Note:

SMPTE “Stable” documents were previously described as “Archived” and the attached document may be marked as “Archived”. The status of a SMPTE document described as “Archived” is exactly as described above for a “Stable” document.

Stable documents may not adhere to the latest style and format of SMPTE documents, or to current usage of normative language. Suitable care should be taken in interpretation.

SMPTE STANDARD

for Motion-Picture Film (35-mm) — Perforated DH-1870



Page 1 of 3 pages

1 Scope

This standard specifies the cutting and perforating dimensions for 35-mm motion-picture film with a DH-type perforation and a perforation pitch of 0.1870 in (4.750 mm).

2 Dimensions

2.1 The dimensions shall be as given in figure 1 and table 1.

2.2 The dimensions pertain to a safety film as defined in SMPTE 223M.

2.3 The dimensions apply at the time of cutting and perforating for film adjusted to a temperature of $23^{\circ}\text{C} \pm 1^{\circ}\text{C}$ (nominally converted to $73^{\circ}\text{F} \pm 2^{\circ}\text{F}$) and a relative humidity of $(50 \pm 2)\%$. The manufacturer may indicate other nominal temperature and humidity conditions under which the dimensions apply.

NOTES

1 The title of this standard was established by the application of a nomenclature system developed for all film dimension standards: Each title provides an indication of the film width, a code designation for the perforation shape (BH, KS, DH, or CS), or the number of rows of perforations (1R, 2R, etc.), depending upon which is the significant factor, or the perforation pitch without the decimal point.

2 The metric conversion of dimension A is purposely chosen and shown to three decimal places to prevent the maximum width dimension from exceeding 35 mm.