


INTERNATIONAL



UNION OF RAILWAYS

U I C CODE	
Leaflet to be classified in Volumes :	
VI	- TRACTION
VII	- WAY AND WORKS

606-2
OR

4th edition, 1-1-86

INSTALLATION OF 25 KILOVOLTS AND 50 OR 60 HERTZ OVERHEAD CONTACT LINES (1)

(1) Obligatory regulations are preceded by an asterisk : ★

OR

REVISIONS

Leaflet 606-2 - 4th edition dated 1-1-86			
Amendment		Amendment	
No.	Date	No.	Date

NOTES

This leaflet forms part of a series which also includes:

- Leaflet 505-1 0I: Kinematic gauge for powered units used on international services.
- Leaflet 505-2 0I: Kinematic gauge for coaches and vans used on international services.
- Leaflet 505-3 0RI: Kinematic gauge for wagons used on international services.
- Leaflet 505-4 0RI: Effects of the application of the kinematic gauges defined in the 505 series of leaflets on the positioning of structures in relation to the tracks and of the tracks in relation to each other.
- Leaflet 505-5 0I: Basic conditions common to Leaflets 505-1 to 505-4 - Notes on the preparation and provisions of these leaflets.
- Leaflet 505-6 1): Effects of the application of the kinematic gauges defined in the 505 series of leaflets on overhead line system design.
- Leaflet 505-7 1): Rules for the application of the expanded A, B and C gauges.
- Leaflet 600 0R: Electric traction with aerial contact lines.
- Leaflet 608 R: Conditions to be complied with for the pantographs of tractive units used on international services.

CONTENTS

0 - GENERAL

0.1 - Purpose of the leaflet

0.2 - Scope

0.3 - Voltage and frequency

0.4 - Definition of the gauge

1 - CONTACT LINE

1.1 - Height of the contact wire

1.2 - Stagger of the contact wire

1.3 - Neutral section

1.4 - Air-gap overlap span

1.5 - Running speed

2 - CLEARANCE DISTANCES

2.1 - Clearance distances for 25 kV

2.2 - Clearance distances between wire parts of the contact line or the pantograph and mass of the structures or rolling stock

3 - REQUIREMENTS CONCERNING PANTOGRAPHS