

1st edition, May 2005

Original

R

Track equipment for 25 tons (250 kN) axle loads on ballasted track

*Armement pour voie ballastée chargée à 25 tonnes (250 kN) par essieu
Gleisbewehrung für 25 Tonnen (250 kN) auf Schotteroberbau*



UNION INTERNATIONALE DES CHEMINS DE FER
INTERNATIONALER EISENBAHNVERBAND
INTERNATIONAL UNION OF RAILWAYS

Leaflet to be classified in Volume:

VII - Way and Works

Application:

With effect from 1 May 2005

All members of the International Union of Railways

Record of updates

1st edition, May 2005

First issue

The person responsible for this leaflet is named in the UIC Code

Contents

Summary	1
1 - Introduction	2
2 - Maximum permissible forces	4
2.1 - Maximum vertical forces	4
2.2 - Force levels and running conditions acceptable on a given line.....	4
3 - Track equipment for new tracks or renewed tracks dedicated for 25 t axle loads	5
3.1 - Sub-grade	5
3.2 - Ballast	5
3.3 - Sleepers and sleeper spacing	6
3.3.1 - Sleeper types	6
3.3.2 - Sleeper spacing	6
3.4 - Rail-fastening systems.....	6
3.5 - Rails.....	6
3.6 - Switches and crossings	7
3.6.1 - Turnout type 60 E1	7
3.6.2 - Bearers	7
Bibliography	8

Summary

This leaflet sets out recommendations for track equipment to be used on the main lines of rail networks operating freight wagons loaded at 250 kN/axle for line categories E4 and E5, as understood by *UIC Leaflet 700* and running at maximum speeds of 100 km/h.

These recommendations are based on the results of previous work carried out in ORE (ERRI) and UIC Committees in connection with the increase in axle loads from 200 kN to 225 kN. They are only valid for ballasted tracks.