



ULC Standards
Normes ULC



ANSI/CAN/UL/ULC 1316:2018

JOINT CANADA-UNITED STATES
NATIONAL STANDARD

Standard for Fibre Reinforced
Underground Tanks for Flammable and
Combustible Liquids



Standards Council of Canada
Conseil canadien des normes



Documents

Document Sharing Hub

SCC FOREWORD

National Standard of Canada

A National Standard of Canada is a standard developed by a Standards Council of Canada (SCC) accredited Standards Development Organization, in compliance with requirements and guidance set out by SCC. More information on National Standards of Canada can be found at www.scc.ca.

SCC is a Crown corporation within the portfolio of Innovation, Science and Economic Development (ISED) Canada. With the goal of enhancing Canada's economic competitiveness and social well-being, SCC leads and facilitates the development and use of national and international standards. SCC also coordinates Canadian participation in standards development, and identifies strategies to advance Canadian standardization efforts.

Accreditation services are provided by SCC to various customers, including product certifiers, testing laboratories, and standards development organizations. A list of SCC programs and accredited bodies is publicly available at www.scc.ca.

UL Standard for Safety for Fibre Reinforced Underground Tanks for Flammable and Combustible Liquids, ANSI/CAN/UL/ULC 1316:2018

Third Edition, Dated November 21, 2018

Summary of Topics

This March 2019 revision of UL/ULC 1316 has been issued as part of the project to support the National Research Council of Canada program to address Climate Change Adaptation in Canadian Codes and Standards.

The new and revised requirements are substantially in accordance with Proposal on this subject dated August 24, 2018.

Text that has been changed in any manner or impacted by UL's electronic publishing system is marked with a vertical line in the margin.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of UL.

UL provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will UL be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if UL or an authorized UL representative has been advised of the possibility of such damage. In no event shall UL's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold UL harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

No Text on This Page



ANSI/UL 1316-2019



NOVEMBER 21, 2018
(Title Page Reprinted: March 12, 2019)

1

ANSI/CAN/UL/ULC 1316:2018

**Standard for Fibre Reinforced Underground Tanks for Flammable and
Combustible Liquids**

First Edition – July, 1983
Second Edition – January, 1994

Third Edition

November 21, 2018

This ANSI/CAN/UL/ULC Safety Standard consists of the Third Edition including revisions through March 12, 2019.

The most recent designation of ANSI/UL 1316 as an American National Standard (ANSI) occurred on March 12, 2019. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, Title Page, Preface or SCC Foreword.

This standard has been designated as a National Standard of Canada (NSC) on March 12, 2019.

COPYRIGHT © 2019 UNDERWRITERS LABORATORIES INC.

No Text on This Page

CONTENTS

Preface	5
---------------	---

INTRODUCTION

1 Scope	7
2 Units of Measurement and References	8
3 Glossary.....	8

CONSTRUCTION

4 General	9
5 Interstitial Spaces and Leak Monitoring.....	10
6 Vent Openings	10
7 Tank Lifting	10
8 Manways.....	10
9 Striker Plates	11
10 Tank Connections	11
10.1 General	11
10.2 Hardware installed for shipping only	12
11 Corrosion Protection.....	12

PERFORMANCE

12 General Performance	12
13 Leakage Test	13
14 Water Load and Hydrostatic Pressure Test.....	13
15 Tank Lifting Test	14
16 Tank Connection Torque and Bending Test.....	14
17 Interstitial Integrity and Communication Test.....	15
18 Buried Tank Load Tests	16
19 Immersion	17
20 Impact and Cold Exposure	18
21 Light and Water Exposure.....	18

PRODUCTION TESTS

22 Leakage Test	19
23 Documentation	19

MARKING

24 General	19
------------------	----

INSTALLATION INSTRUCTIONS AND SUPPLEMENTARY MANUALS

25 General	21
------------------	----

APPENDIX A – (NORMATIVE) – LIST OF STANDARDS ON FUELS AND OTHER FLAMMABLE AND COMBUSTIBLE LIQUIDS

APPENDIX B – (NORMATIVE) – REFERENCE STANDARDS**APPENDIX C – (NORMATIVE) – FLEXURAL STRENGTH TESTING MODIFICATIONS TO ASTM
D790****APPENDIX D – (NORMATIVE) – ALTERNATE GLASS QUALIFICATION****APPENDIX E – (NORMATIVE) – TEST FUEL FORMULATIONS**

E.1	Representative Test Mixtures for Aggressive Combustible Fuels and UL-B100	29
E.2	Representative Test Mixtures for Aggressive Flammable Fuels and Blends	29

APPENDIX F – (INFORMATIVE) – OPTIONAL CLIMATE CHANGE ADAPTATION REQUIREMENTS

F.1	General	31
F.2	Temperatures	31
F.3	Flooding	31
F.4	Climate Change Factors Not Applicable to this Standard	31

Preface

This is the Third Edition of the ANSI/CAN/UL/ULC 1316, Standard for Fibre Reinforced Underground Tanks for Flammable and Combustible Liquids, including revisions through March 12, 2019.

UL is accredited by the American National Standards Institute (ANSI) and the Standards Council of Canada (SCC) as a Standards Development Organization (SDO).

This Standard has been developed in compliance with the requirements of ANSI and SCC for accreditation of a Standards Development Organization. ULC Standards is accredited by the Standards Council of Canada (SCC) as a Standards Development Organization (SDO).

Only metric SI units of measurement are used in this Standard. If a value for measurement is followed by a value in other units in parentheses, the second value may be approximate. The first stated value is the requirement.

Appendices A through E, are identified as Normative, forms a mandatory part of this Standard.

Appendix F, identified as Informative, is for information purposes only.

This ANSI/CAN/UL/ULC 1316 Standard is under continuous maintenance, whereby each revision is approved in compliance with the requirements of ANSI and SCC for accreditation of a Standards Development Organization. In the event that no revisions are issued for a period of four years from the date of publication, action to revise, reaffirm, or withdraw the standard shall be initiated.

In Canada, there are two official languages, English and French. All safety warnings must be in French and English. Attention is drawn to the possibility that some Canadian authorities may require additional markings and/or installation instructions to be in both official languages.

This Third Edition Joint American National Standard and National Standard of Canada is based on, and now supersedes, the Second Edition of UL 1316 and the Third Edition of CAN/ULC-S615-14.

Comments or proposals for revisions on any part of the Standard may be submitted to UL at any time. Proposals should be submitted via a Proposal Request in UL's On-Line Collaborative Standards Development System (CSDS) at <http://csds.ul.com>.

Requests for interpretation of this Standard should be sent to ULC Standards. The requests should be worded in such a manner as to permit a "yes" or "no" answer based on the literal text of the requirement concerned.

UL's Standards for Safety are copyrighted by UL. Neither a printed nor electronic copy of a Standard should be altered in any way. All of UL's Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of UL.

To purchase UL Standards, visit the UL Standards Sales Site at <http://www.shopulstandards.com/HowToOrder.aspx> or call tollfree 1-888-853-3503.

This Edition of the Standard has been formally approved by the Joint UL/ULC Technical Committee (TC) on Flammable and Combustible Liquid Underground Tanks, TC 1316.

This list represents the TC 1316 membership when the final text in this standard was balloted. Since that time, changes in the membership may have occurred.

TC 1316 Membership

Name	Representing	Interest Category	Region
Boyd, D.	BP America	Commercial/Industrial User	USA
Deschamps, C.	Régie du bâtiment du Québec (RBQ)	AHJ	Quebec
D'Onofrio, C. (Project Manager)	ULC Standards	Non-voting	Canada
Grainawi, L.	Steel Tank Institute	General Interest	USA
Legault, P.	Integrated Review Services – Consulting	General Interest	Canada
Lexvold, J.	Xerxes Corp.	Producer	USA
Loucks, J.	Modern Welding Company, Inc.	Producer	USA
Mailvaganam, M.	Consultant	General Interest	Canada
Morgan, J.	SC DHEC	Government	USA
Pomes, M.	U.S. Environmental Protection Agency	Government	USA
Renkes, R.	Fiberglass Tank & Pipe Institute	General Interest	USA
Riegel, R.	UL LLC	Testing & Standards Organization	USA
Schneider, W.	Containment Solutions, Inc.	Producer	USA
Schruben, T.	Consultant	General Interest	USA
Scragg, R.	ZCL Composites Inc.	Producer	Canada
Siegel, M.	AOC LLC	Producer	USA
Sowers, J.	Florida Department of Health – Pinellas	AHJ	USA
Stevens, M.	Ashland Inc.	Supply Chain	USA
Thompson, J.	Association for Petroleum & Explosives Administration	AHJ	UK
Wade, J. (Chair)	ULC Standards	Non-voting	Canada

International Classification for Standards (ICS): 23.020.10

For further information on UL standards, please contact:

Underwriters Laboratories Inc.
171 Nepean Street, Suite 400
Ottawa, Ontario K2P 0B4
Phone: 1-613.755.2729
E-mail: cec@ul.com
Web site: ul.com

This Standard is intended to be used for conformity assessment.

The intended primary application of this standard is stated in its scope. It is important to note that it remains the responsibility of the user of the standard to judge its suitability for this particular application.

CETTE NORME NATIONALE DU CANADA EST DISPONIBLE EN VERSIONS FRANÇAISE ET ANGLAISE.

INTRODUCTION

1 Scope

1.1 This Standard sets forth minimum design and construction requirements for fibre reinforced plastic, non-pressure tanks that are used for the underground storage of flammable and combustible liquids, such as:

- a) Petroleum products, including petroleum hydrocarbon fuels with low-biofuels blends, per specifications, and similar flammable or combustible liquid petroleum derivatives, such as fuel components (cetane, hexane, heptane), and oils (lubricating, hydraulic, machine);
- b) Oxygenated fuel blends, including all "petroleum product" liquids plus petroleum hydrocarbon fuels with low-biofuels blends;
- c) Oxygenates, including all "petroleum product" and "oxygenated fuel blends" liquids plus pure/denatured or highest oxygenated blend stocks for use in mixing of dispensed lower fuel-blends and components, such as biodiesel and ethanol; and
- d) Other flammable and combustible liquids (for which the test fuels in Appendix [A](#) are not considered to be sufficient or applicable) that can be demonstrated or determined to be compatible with the reinforced plastic underground tank materials as determined by the certifier.

In addition to this Standard's traditional safety requirements for underground fiber reinforced plastic tanks that primarily evaluate structural integrity, material compatibility and mitigate environmental hazards from loss of liquid containment under expected normal conditions; optional construction and/or performance requirements, and associated ratings, intended to address more severe conditions associated with the effects of Climate Change are included in Appendix [E](#).

NOTE: The test fuels in Appendix [A](#) are considered to be sufficient and representative for US or Canadian approved motor fuels, off-road fuels, gasoline from renewable and petroleum feedstocks, diesel, renewable diesel, synthetic diesel, biodiesel, kerosene, aviation fuels, jet fuels, fuel oil and heating oil as referenced in (a), (b), and (c).

1.2 This Standard covers tanks of either single, double or multiple wall construction.

1.3 Tanks covered by this Standard are fabricated, inspected, and tested for leakage prior to shipment from the factory as completely assembled vessels.

1.4 This Standard covers tanks where the primary tank may have a single compartment or have multiple compartments.

1.5 These tanks are intended for installation and use in accordance with applicable documents in the following list:

a) In Canada:

- 1) National Fire Code of Canada;
- 2) CAN/CSA-B139, Installation code for oil-burning equipment;
- 3) CCME PN1326, Environmental Code of Practice for Aboveground and Underground Storage Tank Systems Containing Petroleum and Allied Petroleum Products;
- 4) Regulations of the authority having jurisdiction; and

b) In the United States:

- 1) Standard for the Installation of Oil-Burning Equipment, NFPA 31;
- 2) Flammable and Combustible Liquids Code, NFPA 30; and
- 3) Code for Motor Fuel Dispensing Facilities and Repair Garages, NFPA 30A, as applicable.

1.6 Accessories, such as, ladders, tank sumps, risers, and guide lugs, that do not affect tank performance and are attached to the tank internally or externally during manufacture are permitted but not covered by this standard.

1.7 Except for optional Climate Change Adaptation requirements in Appendix [E](#), these requirements do not cover special evaluations for resistance to, or use after earthquakes, floods, high wind events, or other natural disasters.

NOTE: See the Note at the beginning of Appendix [E](#) for further information on the terms "Adaptation" and "Mitigation", as they pertain to Climate Change.

2 Units of Measurement and References

2.1 When a value for measurement is followed by a value in other units in parentheses, the second unit is only approximate. The first stated value is the requirement.

2.2 Any undated references to a code or standard appearing in the requirements of this standard shall be interpreted as referring to the latest edition of that code or standard, refer to Appendix [B](#).

3 Glossary

3.1 **AUTHORITY HAVING JURISDICTION (AHJ)** – The governmental body responsible for the enforcement of any part of this Standard or the official or agency designated by that body to exercise such a function.

3.2 **COMBUSTIBLE LIQUID** – Any liquid having a flash point at or above 37.8 °C (100 °F) and below 93.3 °C (200 °F) and as defined in the National Fire Code of Canada and NFPA 30, Flammable and Combustible Liquids Code.

3.3 **CRUSHED STONE** – Washed, crushed aggregate or crushed gravel with an angular particle size of not more than 13 mm (0.5 in) diameter that is clean and free flowing and with no more than 5 % passing a No. 8 sieve (2.38 mm screen size opening). The material has a minimum dry gravel density of 1520 kg/m³ (95 lb/ft³) and meets the Fine Aggregate requirements for deleterious substances and soundness of ASTM C33/C33M, Standard Specification for Concrete Aggregates.

3.4 **DESIGN SERIES** – A tank design series is a set of tanks of the same diameter, number of walls, and head shape that vary in length.

3.5 **DOUBLE WALL TANK** – A primary tank with an integral secondary containment where the space between the walls is capable of being monitored.

3.6 **FIBRE REINFORCED PLASTIC (FRP)** – A composite material consisting of a combination of rigid thermoset resin and glass fibre reinforcements. The glass fibre reinforcements may take the form of short randomly oriented fibre and/or woven or nonwoven fabrics and/or glass fibre rovings.

3.7 **FLAMMABLE LIQUID** – Any liquid having a flash point below 37.8 °C (100 °F) and a vapour pressure not exceeding 275 kPa (absolute) (40 psig) at 37.8 °C (100 °F) and as defined in the National Fire Code of Canada, and NFPA 30.