

 **Documents**
Document Sharing Hub



Underwriters Laboratories Inc.®

A not-for-profit organization dedicated to public safety
and committed to quality service

February 23, 1996

Revision pages for

Standard for

Installation and Classification of Residential Burglar Alarm Systems

UL 1641, Third Edition

Attached to this transmittal notice is a revision of the third edition of UL 1641.

A CHANGE ON A PAGE DATED FEBRUARY 23, 1996 IS INDICATED BY A SMALL PRINT NOTE FOLLOWING THE AFFECTED ITEM, PRECEDED AND FOLLOWED BY AN ASTERISK.

THESE NEW AND REVISED REQUIREMENTS ARE NOW IN EFFECT EXCEPT FOR PARAGRAPHS 16.2.1, 16.3, 16.4 AND 16.4.1, AND SECTION A10 OF APPENDIX A, WHICH BECOME EFFECTIVE AUGUST 22, 1997 AS INDICATED IN THE SMALL PRINT NOTE FOLLOWING THE AFFECTED ITEM. TO RETAIN THE REQUIREMENTS IN EFFECT UNTIL AUGUST 22, 1997, DO NOT DISCARD THE PREVIOUS PAGES CONTAINING THE REQUIREMENTS SPECIFIED ABOVE UNTIL THIS FUTURE EFFECTIVE DATE.

Alarm installations made prior to a specified future effective date will be judged under all of the requirements in this standard unless the applicant specifically requests that the installation be judged under the current requirements. However, should the applicant elect this option, it should be noted that compliance with all the requirements in this standard will be required as a condition of continued Listing and Follow-Up Services after the effective date and understanding of this should be signified in writing.

The new and revised requirements are substantially in accordance with UL's bulletin on this subject dated July 6, 1995. The bulletin is now obsolete and may be discarded.

Attention is directed to the note on the title page of this standard outlining the procedure to be followed to retain the approved text of ANSI/UL 1641-1994.

Revised and/or additional pages may be issued from time to time.

With the inclusion of the accompanying material, the standard consists of pages dated as shown in the following checklist:

Page	Date
1	September 28, 1994 (Reprinted February 23, 1996)
2	—
3	February 23, 1996
4	September 28, 1994
5, 6	February 23, 1996
6A	September 29, 1994
7, 8, 8A	February 23, 1996

(Continued)

February 23, 1996 – UL 1641

Page	Date
9 – 18	September 28, 1994
19, 20, A1 – A17	February 23, 1996

SEPTEMBER 28, 1994
(Title Page Reprinted: February 23, 1996)



1

UL 1641

Standard for

Installation and Classification of Residential Burglar Alarm Systems

First Edition – April, 1983
Second Edition – April, 1989

Third Edition

September 28, 1994

Approval as an American National Standard (ANSI) covers the numbered paragraphs on pages dated September 28, 1994. These pages should not be discarded when revised or additional pages are issued if it is desired to retain the ANSI approved text.

An effective date included as a note immediately following certain requirements is one established by Underwriters Laboratories Inc.

Approved as ANSI/UL 1641-1984, March 2, 1984
Approved as ANSI/UL 1641-1988, December 14, 1988
Approved as ANSI/UL 1641-1994, January 31, 1994

Revisions of this standard will be made by issuing revised or additional pages bearing their date of issue. A UL Standard is current only if it incorporates the most recently adopted revisions, all of which are itemized on the transmittal notice that accompanies the latest published set of revision pages.

ISBN 1-55989-653-1

COPYRIGHT © 1983, 1996 UNDERWRITERS LABORATORIES INC.

CONTENTS**FOREWORD****INTRODUCTION**

1 Scope	5
2 General	5
3 Glossary	6
4 Control Units	8

EXTENT OF PROTECTION FOR RESIDENTIAL ALARMS

5 General	8
6 Wiring	9
7 Windows	10
8 Doors and Other Openings	11
9 Air Conditioners, Exhaust Fans, and Similar Units	12
10 Screens	12
11 Floor Mats	12
12 Intrusion Detection Devices	12
13 Shunts	13
14 Control Unit	13

INTERPRETATIONS

15 General	13
------------------	----

MAINTENANCE AND SERVICE

16 General	19
------------------	----

APPENDIX A — PROCEDURES FOR ISSUING AND CANCELING RESIDENTIAL BURGLAR ALARM CERTIFICATES

A1 Certificates	A1
A2 Procedure For Issuing A Residential Burglar Alarm Certificate	A2
A3 Faster Service By Fax	A13
A4 How To Fill-In A "Request For Certificate" Form	A13
A5 How To Fill-In The "Alarm System Description" Form	A14
A6 Procedure For Canceling A Residential Burglar Alarm Certificate	A16
A7 Correction Of Defects	A16
A8 Master Certificate File	A17
A9 Maintenance and Service	A17
A10 Service Area	A17

FOREWORD

A. This Standard contains the basic requirements of Underwriters Laboratories Inc. (UL) for the installation of Burglar-Alarm systems covered by UL under its Follow-Up Service, and the rules for classifying the extent of protective wiring at a specified location as indicated by a certificate issued thereon. These requirements are based upon sound engineering principles, research, records of tests and field experience, and an appreciation of the problems of manufacture, installation, and use derived from consultation with and information obtained from manufacturers, users, and others having specialized experience. They are subject to revision as further experience and investigation may show is necessary or desirable.

B. The observance of the requirements of this Standard by an installing company is one of the conditions of the continued coverage of the installing company under this classification.

C. A system or a component of a system which complies with the text of this Standard will not necessarily be judged to comply with the Standard if, when examined and tested, it is found to have other features which impair the level of safety contemplated by these requirements.

D. A system or a component of a system employing materials or having forms of construction differing from those detailed in the requirements of this Standard may be examined and tested according to the intent of the requirements and, if found to be substantially equivalent, may be judged to comply with the Standard.

E. UL, in performing its functions in accordance with its objectives, does not assume or undertake to discharge any responsibility of the installer or any other party. The opinions and findings of UL represent its professional judgment given with due consideration to the necessary limitations of practical operation and state of the art at the time the Standard is processed. UL shall not be responsible to anyone for the use of or reliance upon this Standard by anyone. UL shall not incur any obligation or liability for damages, including consequential damages, arising out of or in connection with the use, interpretation of, or reliance upon this Standard.

F. Many tests required by the Standards of UL are inherently hazardous and adequate safeguards for personnel and property shall be used in conducting such tests.

INTRODUCTION

1 Scope

1.1 These requirements apply to the installation of alarm protection products and devices connected to form a residential burglar alarm system.

1.2 These requirements include the criteria for classifying the extent of alarm protection at an individual residence as either basic protection or expanded protection.

1.3 A residential burglar alarm system may or may not have a remote connection to a central station, proprietary station, residential monitoring station, or police station. If there is a remote connection, the signal receiving location shall comply with the requirements in the following standards, as applicable:

- a) The Standard for Central-Station Burglar-Alarm Systems, UL 611,
- b) The Standard for Central-Stations for Watchman, Fire-Alarm, and Supervisory Services, UL 827,
- c) The Standard for Proprietary Burglar Alarm Units and Systems, UL 1076.
- d) The Standard for Police Station Connected Burglar Alarm Units and Systems, UL 365.

1.3 revised February 23, 1996

1.4 Alarm systems covered by these requirements have a sounding device that may be mounted indoors or outdoors.

1.5 These systems comply with the requirements for Class 2 remote-control and signal circuits as defined by Article 725 of the National Electrical Code, NFPA 70. Systems using both fire and burglary protection operate as defined by Article 760 of the National Electrical Code, NFPA 70.

1.6 The requirements assume that standard telephone operating practices may be used for leased or other lines connecting to a police or central station as defined by Article 800 of the National Electrical Code, NFPA 70.

1.7 An alarm service that is new or different from that covered in this standard shall be evaluated using the appropriate additional service requirements as determined necessary to maintain the acceptable level of security as originally anticipated by the intent of this standard. A service that conflicts with specific service provisions in this standard cannot be judged to comply with this standard. Where considered appropriate, revised service requirements will be proposed and adopted in conformance with the methods employed for development, revision, and implementation of this standard.

1.7 revised February 23, 1996

2 General

2.1 Components

2.1.1 Except as indicated in 2.1.2, a component of a product covered by this standard shall comply with the requirements for that component.

2.1.2 A component need not comply with a specific requirement that:

- a) Involves a feature or characteristic not needed in the application of the component in the product covered by this standard or
- b) Is superseded by a requirement in this standard.

2.1.3 A component shall be used in accordance with its recognized rating established for the intended conditions of use.

2.1.4 Specific components are recognized as being incomplete in construction features or restricted in performance capabilities. Such components are intended for use only under limited conditions, such as certain temperatures not exceeding specified limits, and shall be used only under those specific conditions for which they have been recognized.

2.1.5 Components of a residential alarm system shall comply with the requirements for those components, and shall not be modified before, during, or after installation into the system.

2.2 Units of measurement

2.2.1 If a value for measurement is followed by a value in other units in parentheses, the second value may be only appropriate. The first stated value is the requirement.

2.3 Undated references

2.3.1 Any undated reference to a code or standard appearing in the requirements in this standard shall be interpreted as referring to the latest edition of that code or standard.

2.4 Overall requirements

2.4.1 The area protected by a residential alarm shall be provided with a complete physical boundary.

2.4.1 revised February 23, 1996

2.4.2 A sounding device is required, and if mounted outdoors shall be investigated to determine if the device is acceptable for outdoor use.

3 Glossary

3.1 For the purpose of this standard, the following definitions apply.

3.2 ALARM PROTECTION – Equipment and wiring that is installed to provide protection within an alarm system.

3.3 AREA, INACCESSIBLE – An area in which people can not freely move about, such as crawl spaces and the like.

3.4 BOUNDARY, PHYSICAL – A barrier, such as a wall, ceiling, floor, partition, window, or door, that encloses the protected area.

3.5 COMBINATION SYSTEM – An alarm system that provides both burglary and fire protection. The alarm system may also provide additional supervisory circuits, such as medical alert, police call, basement flooding and the like.

3.9 MAINTENANCE – Repair service and inspections at prescribed intervals that are intended to keep the burglar alarm system and all installed equipment in a fully operative condition.

3.10 OPENING – A point at which entry can be gained through an aperture of manhole size without cutting or tearing down any part of the building structure. An opening can be fixed or movable.

3.11 OPENING, ACCESSIBLE – An opening that does not comply with the requirements for an inaccessible opening.

3.12 OPENING, INACCESSIBLE – An opening:

- a) More than 12 feet (3.7 m) above either the ground or any projection from the same building, adjoining building or both;
- b) More than 12 feet away from a directly or diagonally opposite window, fire escape, or roof; or
- c) More than 3 feet (0.9 m) away from an opening, fire escape, fixed object, and the like, that is in or projecting from the same or adjacent wall and that leads to other premises. See Interpretations, General, Section 15.

3.13 OPENING, MANHOLE SIZE – An opening with a clear cross-section area of 96 square inches (619 cm²) or more, and with the smallest dimension exceeding 6 inches (152 mm).

3.14 PROTECTION OF AN OPENING, COMPLETE – Alarm protection applied to a fixed or movable opening, plus contacts installed on a movable opening. A screen over an opening is considered complete protection of an opening. See also 12.4.1.

3.15 PROTECTION OF AN OPENING, PARTIAL – Contacts installed on a movable opening; or an intrusion detection device installed so as to detect entry through the opening. See also 12.4.1.

3.16 RESIDENCE – Any dwelling in which people reside.

3.17 RESIDENTIAL ALARM – A burglar alarm system used in a residence with or without a fire or supervisory alarm.

3.18 SCREEN – A fully framed assembly of grooved-wood dowels having fine wire secured in the grooves, or window screen with the circuit wire secured to the mesh and frame, and complying with the Standard for Linings and Screens for Use With Burglar-Alarm Systems, UL 606.

3.18.1 SERVICE CENTER – A location that may be separate from the alarm service company's main business location providing installation, maintenance, and repair service to systems served by the company. The service center is to keep maintenance records for the systems that it serves unless the records can be accessed from another location.

3.18.1 added February 23, 1996

3.18.2 SERVICE VEHICLE – A vehicle that is used to provide installation, maintenance, and repair service to systems served by the company.

3.18.2 added February 23, 1996

3.19 SOUNDING DEVICE – An audible signal appliance used to signal unauthorized entry into a protected area.

3.20 TRAP – A conductor or device fastened between a building structure and a screen, stripping, foiled or wired panel, fan, air conditioner, or similar device so that the two cannot be separated without initiating an alarm.

3.21 WIRE, FINE – Bare, hard-drawn, solid copper wire not larger than No. 24 AWG (0.21 mm²) or insulated solid copper wire not larger than No. 26 AWG (0.13 mm²) or the equivalent, used for alarm protection.

3.22 WIRING, INTERCONNECTING – Those conductors used to interconnect protective devices in a burglar alarm system.

4 Control Units

4.1 A control unit used in a residential burglar alarm system shall comply with the control unit requirements in one of the following:

- a) The Standard for Police Station Connected Burglar Alarm Units and Systems, UL 365;
- b) The Standard for Local Burglar Alarm Units and Systems, UL 609;
- c) The Standard for Household Burglar-Alarm System Units, UL 1023, (for grade A units only);
- d) The Standard for Proprietary Burglar Alarm Units and Systems, UL 1076;
- e) The Standard for Central-Station Burglar-Alarm Units, UL 1610; or
- f) The Standard for Digital Alarm Communicator System Units, UL 1635.

4.1 revised February 23, 1996

EXTENT OF PROTECTION FOR RESIDENTIAL ALARMS

5 General

5.1 Details

5.1.1 An individual alarm system protecting an entire residence or a portion thereof shall be identified as expanded or basic (see 5.2.1 and 5.3.1). The alarm system may or may not include fire or supervisory alarm protection.

5.1.2 The fire protection portion of a combination system shall comply with the requirements of the Standard for Household Fire Warning Equipment, NFPA 74, or Chapter 2 of the National Fire Alarm Code, NFPA 72.

5.1.2 revised February 23, 1996

5.2 Basic protection

5.2.1 Basic protection shall consist of:

- a) Contacts on all movable accessible openings or

b) Contacts on all accessible exterior doors and:

- 1) A motion detection device in one or more selected areas;
- 2) A photoelectric beam or motion detector across one or more hallways, stairways, rooms, or the like;
- 3) A floor mat in one or more selected areas, such as a hallway, stairway, room entrance, and the like; or
- 4) A contact on one or more interior doors leading from one area of the residence to another.

MAINTENANCE AND SERVICE

16 General

16.1 Installations shall be maintained by the alarm service company under provisions of a service contract or agreement.

16.1 revised February 23, 1996

16.2 Each installation shall have a maintenance inspection at least once a year by a representative of the alarm service company. A record of the inspection shall be kept in the alarm service company's file. The regular maintenance inspection may be done in parts throughout the year.

16.2 revised February 23, 1996

16.2.1 Terms of the contract or agreement referenced in 16.1 shall be such that the alarm service company, not the user of the alarm system, is responsible for determining if service is needed. The user of the alarm system may request service. However, the contract or agreement shall not allow the user to decline service or regularly scheduled system inspection and maintenance.

Added 16.2.1 effective August 22, 1997

16.3 The alarm company shall provide the subscriber to the alarm service with written instructions on how to contact the company for service. The method of communication shall allow the subscriber to promptly report trouble conditions.

Revised 16.3 effective August 22, 1997

16.4 Repairs to a residential burglar alarm system shall begin within 24 hours after the receipt of the request for service. The maximum range of travel (driving time) from the alarm service company's main business location or service center to an alarm system installation shall not exceed 6 hours in a land-based vehicle.

Exception: The beginning of repair service may be extended to a time specified by the subscriber if the subscriber to the alarm service provides written or oral authorization. Authorization shall be given to alarm service company personnel when the subscriber makes the decision to delay service. If authorization is given, the alarm service company shall make a record of the:

- a) *Time and date of the authorization,*
- b) *Name of the person giving the authorization,*
- c) *Identification code of the person, and*
- d) *The name and address of the residence receiving alarm service.*

Revised 16.4 effective August 22, 1997

16.4.1 The alarm service company shall maintain a means of receiving requests for service at all times, and keep a record of the time and date that:

- a) A request for service is received,
- b) Service begins, and
- c) The repairs are completed.

A request for service shall be received directly by alarm service company personnel, or shall be received by a method that will result in responsible alarm service company personnel receiving the request for service, and service shall begin within the time interval indicated in 16.4.

Added 16.4.1 effective August 22, 1997

16.5 If the installation and maintenance of remote alarm receiving equipment is the responsibility of another company, this company shall be a qualified alarm company. See 1.3. There shall be an agreement between the two companies that provides for the same maintenance and service as would be provided if one company were responsible for the entire system.

16.6 Service centers maintained by the alarm company shall provide the same maintenance service as that available from the alarm company's main center. A complete stock of equipment replacement parts and repair service shall be available.

APPENDIX A – PROCEDURES FOR ISSUING AND CANCELING RESIDENTIAL BURGLAR ALARM CERTIFICATES**A1 Certificates**

A1.1 Underwriters Laboratories Inc. (UL) under its Certificate Service program authorizes the issuance of Certificates for residential burglar alarm system installations which a Listed Alarm Service Company (ASC) represents to be in compliance with requirements established for residential burglar alarm service. An issued Residential Burglar Alarm Certificate indicates the extent of protection, name and location of protected property, period of issuance, and name and address of the ASC Service Center.

A1.1 added February 23, 1996

A1.2 An alarm system is considered to be Listed only if it is covered by a current Certificate. Only those alarm system installations for which a Certificate has been properly issued are covered under UL's Certificate Service. The verification of a Certificate on "Underwriters Laboratories Certificate Verification Service" (ULCVS) is a method UL provides to identify Certificated alarm systems actively covered under its Listing and Follow-Up Service.

A1.2 added February 23, 1996

A1.3 A Certificate may also be verified by telephone if its serial number is known or if the correct name, address, and zip code are known. Verification may be obtained by contacting the burglar alarm certificate service at UL's Northbrook, Illinois office.

A1.3 added February 23, 1996

A1.4 UL regularly counterchecks representative Certificated alarm system installations of each ASC. Under the Follow-Up Service program UL Field Representatives conduct regular inspections and tests of representative alarm system installations to verify proper installation of protective devices and wiring, quality of workmanship, operability of circuits, maintenance procedures, and levels of protection. If an alarm system does not comply with UL's requirements it is subject to correction by the ASC or cancellation of the Certificate.

A1.4 added February 23, 1996

A1.5 UL makes no representations or warranties, expressed or implied, that the Residential Burglar Alarm Certificated alarm system will prevent any loss, or that the system will in all cases provide the protection for which it is installed or intended. UL conducts countercheck field inspections of representative installed alarm systems of the ASC. UL does not assume or undertake to discharge any liability of the ASC or any other party. UL is not an insurer and assumes no liability for any loss which may result from failure of the equipment, incorrect Certification, nonconformity with requirements, cancellation of the Residential Burglar Alarm Certificate or withdrawal of the ASC from inclusion in UL's Directory prior to the expiration date appearing on the Residential Burglar Alarm Certificate.

A1.5 added February 23, 1996

A2 Procedure For Issuing A Residential Burglar Alarm Certificate

A2.1 There are four steps to issuing a Residential Burglar Alarm Certificate as follows (Figures A2.1 through A2.5 illustrate the different types of documents used.):

- a) The ASC initiates the Residential Burglar Alarm Certificate issuing process by executing the "Request for Certificate" form, Figure A2.1, and an "Alarm System Description" form, Figure A2.2. The original of the "Request for Certificate" shall be attached to the "Alarm System Description" and sent to the UL Northbrook Office for processing. For faster service, the ASC may "FAX" a copy of the "Request for Certificate" and "Alarm System Description" forms. UL will then communicate a serial number to them. See Faster Service by FAX, Section A3.
- b) When UL receives the original of both forms ("Request for Certificate" and "Alarm System Description"), a Certificate will be printed after verifying that the information on the "Request for Certificate" form and "Alarm System Description" form, is correct. Thirty days before the issue date, UL sends the "Residential Burglar Alarm System Certificate," Figure A2.3, to the ASC. The Certificate is then added to the "Master Certificate File" in a "pending" status.
- c) The ASC signs the Certificate and distributes it to the representative of the protected property.
- d) On the issue date indicated on the request, UL will activate the Certificate and the installation becomes eligible for periodic review.

A2.1 added February 23, 1996

Figure A2.1
Request for certificate form

 Underwriters Laboratories Inc. • 333 PFINGSTEN ROAD • NORTHBROOK, ILLINOIS 60062-2096 AN INDEPENDENT, NOT-FOR-PROFIT ORGANIZATION TESTING FOR PUBLIC SAFETY	SN: _____
REQUEST FOR CERTIFICATE	
Upon receipt of the executed Request for Certificate, Underwriters Laboratories Inc. (UL) will provide a Certificate for use by the <i>Alarm Service Company</i> in connection with the <i>Alarm System</i> installed for the <i>Protected Property</i>. The <i>Alarm System</i> will be installed and maintained in accordance with the UL requirements for the Burglar, Holdup or Fire Alarm Certificate marked below:	
BURGLAR ALARM SYSTEMS ☐ CENTRAL STATION ☐ POLICE STATION CONNECTED MERCANTILE ☐ LOCAL MERCANTILE ☐ PROPRIETARY ☐ LIMITED MERCANTILE ☐ POLICE STATION CONNECTED BANK ☐ LOCAL BANK ☐ DEFENSE INDUSTRIAL SECURITY (DIS) ☒ RESIDENTIAL	FIRE ALARM SYSTEMS ☐ CENTRAL STATION (NFPA 71 or 72) ☐ LOCAL (NFPA 72) ☐ AUXILIARY (NFPA 72) ☐ REMOTE STATION (NFPA 72) ☐ PROPRIETARY (NFPA 72) HOLDUP ALARM SYSTEMS ☐ HOLDUP
File Number: <u>BP99990</u> Service Center Number: <u>2</u> Issue Date: <u>8/4/92</u> Expiration Date: <u>8/4/93</u>	
☒ New Certificate ☐ Renewed or Replacement Certificate (Prior Certificate Serial No. _____)	
LIMITATION OF LIABILITY: Underwriters Laboratories Inc. makes no representations or warranties, express or implied, that the Alarm System will prevent any loss by fire, smoke, water damage, burglary, hold-up or otherwise, or that the Alarm System will in all cases provide the protection for which it is installed or intended. UL may at times conduct inspections of the Alarm Service Company including inspections of representative installations made by it. UL does not assume or undertake to discharge any liability of the Alarm Service Company or any other party. UL is not an insurer and assumes no liability which may result directly or indirectly from inspection of the equipment, failure of the equipment, failure to conduct inspections, incorrect certification, nonconformity with requirements, failure to discover nonconformity with requirements, cancellation of the Certificate or withdrawal of the Alarm Service Company from inclusion in UL's Directory prior to the expiration date appearing on this Certificate.	
Protected Property: His House 22 Nice St. Palatine, IL 60074	Alarm Service Company An Alarm Co. 333 Pfingsten Rd. Northbrook, IL 60062-2096
The undersigned, as an authorized representative of the <i>Protected Property</i> named herein, acknowledges he has read and agrees on behalf of the above named <i>Protected Property</i> to the terms and conditions of this Request for Certificate.	
Authorized Representative of Protected Property <u>John Smith</u> Typed Name of Representative Signature of Representative Date <u>July 12</u>, 19 <u>92</u>	Authorized Representative of Alarm Service Company <u>John Doe</u> Typed Name of Representative Signature of Representative Date <u>July 12</u>, 19 <u>92</u>
UNDERWRITERS LABORATORIES COPY © 1994 CS-R1 REV	

SM1123B

(Continued)

Figure A2.1 (Cont'd) Request for certificate form

DEFINITIONS

Alarm Service Company — The Listed company assuming responsibility for the installation and maintenance of the alarm system under UL's Certificate Service programs.

Alarm System — A protective signaling system which is considered to be a combination of interrelated signal initiating devices, signal transmitting devices, signal notification devices and control equipment and interconnecting wiring installed for a particular application.

Directory — A publication issued annually by UL that contains the name of companies having products that comply with UL's requirements.

File Number — Alarm Service Company's file number. A number assigned by UL to identify a file for a Listee within a specific Product Category.

Protected Property — The alarm user, business, residence, location, and/or area protected by the alarm system.

Service Center Number — A number, code or distinctive identification, assigned either by UL or the Listee, which when used in association with a client's file number uniquely defines a central station, service center, satellite station, monitoring station, or other service location of the Listee.

CERTIFICATE TYPES

The Fire Alarm System Certificate types are:

CENTRAL STATION (NFPA 71 OR 72) — CENTRAL STATION FIRE ALARM SYSTEM CERTIFICATE

LOCAL (NFPA 72) — LOCAL FIRE ALARM SYSTEM CERTIFICATE

AUXILIARY (NFPA 72) — AUXILIARY FIRE ALARM SYSTEM CERTIFICATE

REMOTE STATION (NFPA 72) — REMOTE STATION FIRE ALARM SYSTEM CERTIFICATE

PROPRIETARY (NFPA 72) — PROPRIETARY FIRE ALARM SYSTEM CERTIFICATE

The Burglar Alarm System Certificate types are:

CENTRAL STATION — CENTRAL STATION BURGLAR ALARM SYSTEM CERTIFICATE

LIMITED MERCANTILE(1) — LIMITED MERCANTILE BURGLAR ALARM SYSTEM CERTIFICATE

POLICE STATION CONNECTED MERCANTILE — POLICE STATION CONNECTED MERCANTILE BURGLAR ALARM SYSTEM CERTIFICATE

POLICE STATION CONNECTED BANK — POLICE STATION CONNECTED BANK BURGLAR ALARM SYSTEM CERTIFICATE

LOCAL MERCANTILE — LOCAL MERCANTILE BURGLAR ALARM SYSTEM CERTIFICATE

LOCAL BANK — LOCAL BANK BURGLAR ALARM SYSTEM CERTIFICATE

PROPRIETARY — PROPRIETARY BURGLAR ALARM SYSTEM CERTIFICATE

RESIDENTIAL — RESIDENTIAL BURGLAR ALARM SYSTEM CERTIFICATE

DEFENSE INDUSTRY SECURITY — DEFENSE INDUSTRIAL SECURITY SYSTEM CERTIFICATE

The Holdup Alarm System Certificate types are:

HOLDUP — HOLDUP ALARM SYSTEM CERTIFICATE

(1) The Limited Mercantile Certificate provides for a basic system which can be enhanced as required by the Authority Having Jurisdiction or the Alarm System user. Other types of Certificated systems are available which the alarm user may wish to consider.

S36508

Figure A2.1 added February 23, 1996

Figure A2.2
Alarm system description form



Underwriters Laboratories Inc.



Alarm System Description
For Residential
Burglar Alarm System Certificate

PROTECTED PROPERTY			
Name: His House			
Address: 22 Nice St.			
City: Palatine	State: IL	Zip Code: 60074	
ALARM SERVICE COMPANY			
File No. BP99990	Service Center No. 2		
Name: An Alarm Service Co.			
Address: 333 Pfingsten Rd.			
City: Northbrook	State: IL	Zip Code: 60062-2096	
Representative (Name & Title): John Doe, Alarm Manager		Phone Number: (708) 555-6776	
PERIOD OF ISSUANCE			
Issue Date: 8-4-92	Expiration Date: 8-4-93	☒ New ☐ Renewal	Prior Certificate Serial No.
COMMENTS AND CLARIFICATIONS			
None			

Copyright © 1993 UL

Form No. CS-ASD-BRD

SM1122B

(Continued)