



UL 1786

STANDARD FOR SAFETY

Direct Plug-In Nightlights

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000



Documents

Document Sharing Hub

*UL COPYRIGHTED MATERIAL –
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR
DISTRIBUTION WITHOUT PERMISSION FROM UL*



Documents
Document Sharing Hub

UL Standard for Safety for Direct Plug-In Nightlights, UL 1786

Fourth Edition, Dated December 17, 2014

Summary of Topics

This new edition of ANSI/UL 1786 includes the following changes in requirements:

- 1. Revise polarization requirements for nightlights provided with switches***
- 2. Add reference to UL 8750 requirements for isolated output LED drivers***
- 3. Revise paragraph 11.5.1 to include cadmium sulfide photocells***
- 4. Add ballast construction requirements to correlate with UL 935***
- 5. Add requirements for nightlights with vessels containing liquid***
- 6. Revise paragraph 1.3 to exclude direct plug in devices such as plasma light***
- 7. Propose additional testing to determine suitability of mechanism and contacts of devices that rotate to accommodate receptacle orientation (add 7.7.4, 11.11, and 11.12)***

The new and revised requirements are substantially in accordance with Proposal(s) on this subject dated August 22, 2014.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of UL.

UL provides this Standard “as is” without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will UL be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if UL or an authorized UL representative has been advised of the possibility of such damage. In no event shall UL’s liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL’s Standards for Safety agree to defend, indemnify, and hold UL harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney’s fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser’s computer system.

The requirements in this Standard are now in effect, except for those paragraphs, sections, tables, figures, and/or other elements of the Standard having future effective dates as indicated in the preface. The prior text for requirements that have been revised and that have a future effective date are located after the Standard, and are preceded by a “SUPERSEDED REQUIREMENTS” notice.

The following table lists the future effective dates with the corresponding reference.

**UL COPYRIGHTED MATERIAL –
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR
DISTRIBUTION WITHOUT PERMISSION FROM**

Documents
Document Sharing Hub

Future Effective Date	Reference
August 21, 2017	Clauses 6.3, 7.1.12, and 10.7.4





CSA Group
CSA C22.2 No. 256-14
Second Edition



Underwriters Laboratories Inc.
UL 1786
Fourth Edition

Direct Plug-In Nightlights

December 17, 2014



ANSI/UL 1786-2014

UL COPYRIGHTED MATERIAL –
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR
DISTRIBUTION WITHOUT PERMISSION FROM UL



Documents
Document Sharing Hub

Commitment for Amendments

This standard is issued jointly by the Canadian Standards Association (operating as “CSA Group”) and Underwriters Laboratories Inc. (UL). Comments or proposals for revisions on any part of the standard may be submitted to CSA Group or UL at any time. Revisions to this standard will be made only after processing according to the standards development procedures of CSA Group and UL. CSA Group and UL will issue revisions to this standard by means of a new edition or revised or additional pages bearing their date of issue.

ISBN 978-177139-710-0 © 2014 CSA Group

All rights reserved. No part of this publication may be reproduced in any form whatsoever without the prior permission of the publisher.

This Standard is subject to periodic review, and suggestions for its improvement will be referred to the appropriate committee. To submit a proposal for change, please send the following information to inquires@csagroup.org and include “Proposal for change” in the subject line: Standard designation (number); relevant clause, table, and/or figure number; wording of the proposed change; and rationale for the change.

To purchase CSA Group Standards and related publications, visit CSA Group’s Online Store at shop.csa.ca or call toll-free 1-800-463-6727 or 416-747-4004.

Copyright © 2014 Underwriters Laboratories Inc.

UL’s Standards for Safety are copyrighted by UL. Neither a printed nor electronic copy of a Standard should be altered in any way. All of UL’s Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of UL.

This ANSI/UL Standard for Safety consists of the Fourth edition. The most recent designation of ANSI/UL 1786 as an American National Standard (ANSI) occurred on December 17, 2014. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, Title Page (front and back), or the Preface.

Comments or proposals for revisions on any part of the Standard may be submitted to UL at any time. Proposals should be submitted via a Proposal Request in UL’s On-Line Collaborative Standards Development System (CSDS) at <http://csds.ul.com>.

To purchase UL Standards, visit Comm 2000 at http://www.comm-2000.com/help/how_to_order.aspx or call toll-free 1-888-853-3503.

CONTENTS

Preface	5
1 Scope	7
2 Reference Publications	7
3 Components	9
4 Units of Measurement	9
5 Application of Requirements	9
6 Definitions	10
7 Construction	11
7.1 Enclosures – General	11
7.2 Polymeric materials for enclosure and electrical insulation	12
7.3 Enclosure assembly methods	13
7.4 Corrosion protection	13
7.5 Current-carrying parts	13
7.6 Plug blades	14
7.7 Plug face dimensions	14
7.8 Polarization and identification	14
7.9 Switching mechanisms	15
7.10 Lampholder	15
7.11 Wiring and terminal connections	15
7.12 Internal wiring	16
7.13 Spacing of conductive parts	17
7.14 Grounding and bonding	18
7.15 Maximum tipping moment	18
7.16 Electroluminescent panels	18
7.17 Incandescent lamps	19
7.18 LED light sources	19
7.19 Receptacle	19
7.20 Ballasts	20
7.21 Vessels containing a liquid	20
8 General Tests	20
8.1 General	20
8.2 Accessibility of live parts	21
8.3 Dielectric voltage-withstand	21
8.4 Plug blades accessibility	22
9 Normal Operation Tests	22
9.1 Temperature	22
9.2 Lampholder and lamp base accessibility	23
10 Component Tests	23
10.1 Switch mechanism	23
10.2 Plug blade secureness test	25
10.3 Folded blade compression test	26
10.4 Mold stress-relief distortion test	26
10.5 Lamp cavity separation test	26
10.6 Pull test	27
10.7 Enclosure impact test	27
11 Abnormal Tests	27
11.1 Blanketing test	27
11.2 Overlamping test	28
11.3 Limited short-circuit test	29

UL COPYRIGHTED MATERIAL –
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR
DISTRIBUTION WITHOUT PERMISSION FROM UL



Documents
Document Sharing Hub

11.4	Overvoltage test	29
11.5	Component breakdown test	29
11.6	Voltage surge test	30
11.7	Humidity conditioning test	31
11.8	Leakage-current test	31
11.9	Grounding continuity test	33
11.10	Crush test	34
11.11	Torque test	34
11.12	Rotational endurance test	34
12	Factory Production Tests	34
12.1	Dielectric voltage-withstand test	34
12.2	Additional factory production tests in Canada	36
13	Marking	36

Annex A (Normative) Standards for components

Annex B (CAN) (Normative) Grounding and bonding of electrical equipment

B.1	General	56
B.2	Impedance	56
B.3	Impedance Test	56

ANNEX C (CAN) (Normative) Printed circuit-board requirements

C.1	Application	57
C.2	Special Terminology	57
C.3	General	57
C.4	Printed Circuit-Board Coatings Tests	58
C.4.1	Dielectric strength	58
C.4.2	Adhesion	59
C.4.3	Abrasion resistance test apparatus	59
C.4.4	Insulation Resistance Test Voltage	60
C.4.5	Fault conditions test	61
C.5	Bond Strength of Printed-Wiring Boards	61
C.5.1	General	61
C.5.2	Test procedure	62

Annex D (CAN) (Normative) Factory Tests for Canada

D.1	Grounding continuity	63
D.2	Separation	63
D.3	Candelabra lamp devices	63
D.4	Test records	64

Annex E (CAN) (Informative) French translations and markings

Preface

This is the common CSA Group and UL Standard for *Direct Plug-In Nightlights*. It is the second edition of CSA C22.2 No. 256 and the fourth edition of UL 1786. This edition of CSA C22.2 No. 256 supersedes the previous edition published in 2005. This edition of UL 1786 supersedes the previous editions published in 1995, 1988, and 2005.

This common Standard was prepared by the CSA Group and Underwriters Laboratories Inc. (UL). The efforts and support of the CANENA Technical Harmonization Committee are gratefully acknowledged.

This Standard was reviewed by the CSA Subcommittee on Lighting Products, under the jurisdiction of the CSA Technical Committee on Consumer and Commercial Products and the CSA Steering Committee on Requirements for Electrical Safety, and has been formally approved by the CSA Technical Committee.

This Standard has been approved by the American National Standards Institute (ANSI) for publication as an American National Standard.

A UL Standard is current only if it incorporates the most recently adopted revisions, all of which are itemized on the transmittal notice that accompanies the latest set of revised requirements.

Where reference is made to a specific number of samples to be tested, the specified number is considered to be a minimum quantity.

Note: Although the intended primary application of this Standard is stated in its scope, it is important to note that it remains the responsibility of the users of the Standard to judge its suitability for their particular purpose.

Level of harmonization

This Standard uses the IEC format but is not based on, nor is it to be considered equivalent to, an IEC Standard. This Standard is published as an equivalent Standard for CSA Group and UL. An equivalent Standard is a Standard that is substantially the same in technical content, except as follows: Technical national differences are allowed for codes and governmental regulations as well as those recognized as being in accordance with NAFTA Article 905, for example, because of fundamental climatic, geographical, technological, or infrastructural factors, scientific justification, or the level of protection that the country considers appropriate. Presentation is word for word except for editorial changes.

Reasons for differences from IEC

There is not an IEC Standard that is equivalent to the requirements contained in this Standard.

Interpretations

The interpretation by the standards development organization of an identical or equivalent Standard is based on the literal text to determine compliance with the Standard in accordance with the procedural rules of the standards development organization. If more than one interpretation of the literal text has been identified, a revision is to be proposed as soon as possible to each of the standards development organizations to more accurately reflect the intent.

CSA Group Effective Date

The effective date for CSA Group will be announced through *CSA Informs* or a CSA Group Certification Notice.

UL COPYRIGHTED MATERIAL –
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR
DISTRIBUTION WITHOUT PERMISSION FROM  **Documents**
Document Sharing Hub

UL Effective Date

As of December 17, 2014, all products Listed or Recognized by UL must comply with the requirements in this standard except for the following:

Clauses 6.3, 7.1.12, and 10.7.4 are effective August 21, 2017.

A UL effective date is one established by Underwriters Laboratories Inc. and is not part of the ANSI approved Standard.

1 Scope

1.1 This Standard applies to direct plug-in nightlights not exceeding 10 W input, for indoor use only, in non-hazardous locations and intended to be used in accordance with the *Canadian Electrical Code, Part I*, CSA C22.1, and the *National Electrical Code*, ANSI/NFPA 70. Light source types include incandescent candelabra base lamps, non-replaceable lamps, [fluorescent, neon, or light-emitting diode (LED) type] or electroluminescent panels.

1.2 These requirements cover direct plug in nightlights for insertion into a parallel slot receptacle rated 125 volts maximum.

1.3 These requirements do not cover:

- (a) cord-connected luminaires;
- (b) nightlights with more than one receptacle;
- (c) direct plug-in devices with other primary functions, such as room deodorizers, insect repellents, or rechargeable flashlights; or
- (d) direct plug-in devices utilizing plasma light.

2 Reference Publications

2.1 For undated references to Standards, such reference shall be considered to refer to the latest edition and all revisions to that edition up to the time when this Standard was approved. For dated references to Standards, such reference shall be considered to refer to the dated edition and all revisions published to that edition up to the time the Standard was approved.

2.2 Products covered by this Standard shall comply with the reference installation codes and Standards as appropriate for the country where the product is to be used. When the product is intended for use in more than one country, the product shall comply with the installation codes and Standards for all countries where it is intended to be used. A list of reference publications is provided below.

CSA Group

C22.1-12

Canadian Electrical Code, Part I

C22.2 No. 0.4-04 (R2013)

Bonding of Electrical Equipment

CAN/CSA-C22.2 No. 0.17-00 (R2013)

Evaluation of Properties of Polymeric Materials

C22.2 No. 42-10

General Use Receptacles, Attachment Plugs, and Similar Wiring Devices

CAN/CSA C22.2 No. 60065-03 (R2012)

Audio, Video, and Similar Electronic Apparatus – Safety Requirements

UL (Underwriters Laboratories Inc)

UL 498

Attachment Plugs and Receptacles

UL 498A

Current Taps and Adapters

UL 746C

Polymeric Materials – Use in Electrical Equipment Evaluations

UL 796

Printed-Wiring Boards

UL 840

Insulation Coordination Including Clearances and Creepage Distances for Electrical Equipment

UL 1449

*Surge Protective Devices***ASTM (American Society for Testing and Materials)**

ASTM D 1000

Standard Test Methods for Pressure-Sensitive Adhesive-Coated Tapes Used for Electrical and Electronic Applications

ANSI/ASTM E230/E230M

*Standard Specification and Temperature-Electromotive Force (emf) Tables for Standardized Thermocouples***IEC (International Electrotechnical Commission)**

IEC 60061-1

Lamp caps and holders together with gauges for the control of interchangeability and safety Part 1: Lamp caps

IEC 60664-1

*Insulation coordination for equipment within low-voltage systems – Part 1: Principles, requirements and tests***NEMA (National Electrical Manufacturers Association)**

NEMA ANSLG C81.61

Electrical Lamp Bases – Specifications for Bases (Caps) for Electric Lamps

NEMA ANSLG C81.63a

*Gauges for Electric Lamp Bases and Lampholders***NFPA (National Fire Protection Association)**

ANSI/NFPA 70

National Electrical Code (NEC)

UL COPYRIGHTED MATERIAL –
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR
DISTRIBUTION WITHOUT PERMISSION FROM  **Documents**
Document Sharing Hub

3 Components

3.1 Except as indicated in Clause 3.2, a component of a product covered by this Standard shall comply with the requirements for that component. See Annex A for a list of Standards covering components generally used in the products covered by this Standard. A component shall comply with the CSA or UL Standards as appropriate for the country where the product is to be used.

3.2 A component is not required to comply with a specific requirement that:

(a) involves a feature or characteristic not required in the application of the component in the product covered by this Standard; or

(b) is superseded by a requirement in this Standard. Electrical circuit components of an LED light source, including the LED itself, that are directly connected to line voltage are considered covered by the requirements of this Standard.

3.3 A component shall be used in accordance with its rating established for the intended conditions of use.

3.4 Specific components are accepted as being incomplete in construction features or restricted in performance capabilities. Such components are intended for use only under limited conditions, such as certain temperatures not exceeding specified limits, and shall be used only under those specific conditions.

3.5 In Canada, a driver or part thereof providing an isolated output to an LED light source shall comply with applicable requirements of the Standard for Light Emitting Diode (LED) Equipment for Lighting Applications, CAN/CSA-C22.2 No. 250.13.

In the United States, a driver or part thereof providing an isolated output to an LED light source shall comply with applicable requirements of the Standard for Light Emitting Diode (LED) Equipment for Use in Lighting Products, UL 8750.

4 Units of Measurement

4.1 The values given in SI (metric) units shall be normative. Any other values given are for information only.

Note: Wire gauge sizes are expressed in American Wire Gauge sizes because of its widespread usage.

4.2 Temperatures are given in degrees Celsius only.

4.3 Unless indicated otherwise, all voltage and current values mentioned in this Standard are root-mean-square (rms).

5 Application of Requirements

5.1 The requirements of the national installation code and other practices of Canada and the United States have been addressed in the requirements of this Standard.

5.2 Products intended to be used in both Canada and the United States shall comply with the requirements of this Standard.

5.3 Products to be used only in Canada or only in the United States shall comply with the requirements of this Standard, but need only comply with the applicable country-specific requirement, if provided.

6 Definitions

6.1 For the purpose of these requirements, the following definitions apply:

6.2 **Accessible** – able to be contacted by the articulate probe described in Clause 8.2.2.

6.3 **Child-appealing feature** – A feature that provides visual appeal and attraction to children in the form of shape, decoration, bright colors, or unusual illuminations.

6.4 **Device** – the general term used to denote all direct plug-in nightlights covered by this Standard. A more specific term is used if a requirement applies only to a certain type of device.

6.5 **Direct Plug-In Nightlight** – a nightlight with an integral parallel blade plug and a 10 W maximum light source, and which may incorporate a shade. It is used not for general illumination but for illuminating obstacles. For the purpose of this Standard, a nightlight may be referred to as “a device.”

6.6 **Electroluminescent Panel** – a solid phosphor layer, contained between two electrodes, that will emit light when subjected to alternating current.

6.7 **Enclosure, Electrical** – a part of the device intended to reduce the risk of contact with parts at hazardous voltage or hazardous energy levels.

6.8 **Enclosure, Mechanical** – a part of the device intended to reduce the risk of injury due to mechanical or other physical hazards.

6.9 **Light Emitting Diode (LED)** – a solid state component embodying a p-n junction, emitting optical radiation when excited by an electric current.

6.10 **LED Light Source** – a system comprising one or more LEDs along with the necessary circuitry that supplies the proper voltage and current or that is used to switch, dim or otherwise control the electrical energy to operate the LEDs.

6.11 **Live Part** – a metal or other conductive part that, during intended use, has an electrical potential difference with respect to earth ground or any other conductive part.

6.12 **Measurement Indication Unit (MIU)** – the output voltage across the meter, in millivolts RMS, in the measurement instrument in Figure 1, divided by 500 Ω . (The instrument indication is equal to the RMS value in milliamperes when the frequency is 60 Hz (sinusoidal current). The reading may not be a direct indication of the RMS or other common amplitude quantifier of leakage-current when the leakage-current is of complex waveform or frequency other than 50 or 60 Hz.)

6.13 Neon Lamp – a discharge light source, also known as a “glow lamp,” that has a current limiting resistor in series with the lamp and is filled with a neon gas.

6.14 Non-Relampable Direct Plug-In Nightlight – a device constructed with permanent non-replaceable lamps.

6.15 Relampable Direct Plug-In Nightlight – a device constructed in such a way as to allow user replacement of the lamp.

6.16 Risk Of Electric Shock – a risk that exists between any two uninsulated conductive parts of a nightlight or between an uninsulated conductive nightlight part and earth ground, if the continuous current flow through a 1500 resistor in parallel with a 0.015 μ F capacitor connected between the two points exceeds 5 mA rms (7 mA peak) and if the open circuit voltage exceeds 30 V rms or 42.4 V peak.

6.17 Shade – a diffuser intended to reduce the glare of the lamp.

6.18 Skeleton-Type Lampholder – a screw lampholder that does not use conductive screwshell threads to make electrical contact with the lamp screw base. Electrical contact with the lamp screw base is made with one or more separate contacts in the side wall of the lamp cavity or a ring contact in the bottom of the lamp cavity.

6.19 User Maintenance – servicing operations, such as relamping and cleaning, expected to be carried out by untrained persons.

7 Construction

7.1 Enclosures – General

7.1.1 Enclosures shall have the strength and rigidity required to resist the abuses to which they are liable to be subjected, without increasing the risk of fire, electric shock, or injury to persons due to a reduction of the required spacing for live parts or the loosening or displacement of live parts.

7.1.2 The enclosure material shall be metal or a polymeric material that complies with Clause 7.2.

7.1.3 A device shall be constructed so that it is not necessary to open or remove the enclosure during normal use or user maintenance. Parts that can be removed during normal use or for user maintenance such as cleaning or relamping shall not be considered to be a part of the enclosure. The incorrect replacement or discarding of such parts shall not affect the intended operation of the device.

7.1.4 A live part shall be contained within an enclosure. A part that is intended to be live at any time during the normal maintenance and use of a device shall be considered to be a live part. An enclosure shall comply with Clause 8.2.

7.1.5 Lampholder contacts need not be enclosed if live parts are not accessible with the lamp in place as determined by the requirements of Clause 9.2 for lampholder and lamp base accessibility.

7.1.6 The blades of a nightlight are not required to be enclosed.

7.1.7 An enclosure shall comply with the enclosure impact test of Clause 10.7.

7.1.8 There shall not be any method of construction, such as sharp edges or burrs, that causes damage to electrical insulation, reduces electrical spacings, or increases the risk of personal injury to the user.

7.1.9 If knobs on switches are removable from outside the enclosure, their removal shall not expose live parts.

7.1.10 A non-relampable device shall comply with the pull test described in Clause 10.6.

7.1.11 Removable parts of direct plug-in nightlights with child-appealing features shall not present a risk of injury to persons from a sharp edge after being subjected to the Enclosure Impact Test, Section 10.7. Removable parts shall be tested both attached to the appliance and separated from the appliance.

7.1.12 In the United States, an accessible liquid coating material (such as paint, enamel, lacquer, ink, and the like) applied to direct plug-in nightlights with child-appealing features shall not contain compounds of lead, antimony, arsenic, barium, cadmium, chromium, mercury, or selenium exceeding amounts specified in ASTM F963. A liquid coating material is considered to be accessible if it can be contacted by persons before or after compliance with the performance requirements described in the Mold Stress-Relief Distortion Test, Clause 10.4, and the Enclosure Impact Test, Clause 10.7.

Note 1: In Canada, various requirements in jurisdictions such as federal, provincial, or municipal may apply.

Note 2: The requirements for a liquid coating material do not apply to ink applied to a packing material.

7.2 Polymeric materials for enclosure and electrical insulation

7.2.1 An enclosure of polymeric material (thermoplastic or thermoset) that encloses a live part shall:

- (a) have a flammability rating of V-0, V-1, or V-2 in accordance with CAN/CSA-C22.2 No. 0.17 or UL 746C;
- (b) comply with the appropriate lamp cavity separation test of Clause 10.5 or the pull test of Clause 10.6;
- (c) comply with the enclosure impact test of Clause 10.7; and
- (d) if thermoplastic, comply with the mold stress-relief distortion test of Clause 10.4.

7.2.2 A polymeric material, thermoplastic or thermoset, used as electrical insulation shall comply with the requirements of Clauses 7.2.3 and 7.2.4 when the polymeric part is:

- (a) in direct contact with a live part;
- (b) used to enclose a live part and is within 0.8 mm (0.032 in) of a live part; or
- (c) used to enclose arcing parts and within 13 mm (0.50 in) of such live parts. The high current arc ignition (HAI) shown in Table 1 only applies in this application.

7.2.3 A polymeric material (thermoplastic or thermoset) used as electrical insulation shall have a flammability rating in accordance with Table 1.

7.2.4 A polymeric material used as electrical insulation or enclosure, as defined in Clause 7.2.2, shall be able to withstand the hot wire ignition (HWI), the comparative tracking index test (CTI), and the high current arc ignition (HAI) to a level not exceeding the values in accordance with Table 1.

7.2.5 A polymeric material used as an enclosure or electrical insulation shall have a relative thermal index (RTI) equal to or exceeding the values as determined by the temperature test of Clause 9.1 and, as a minimum, specified in Table 2.

7.3 Enclosure assembly methods

7.3.1 Mechanical fastenings

7.3.1.1 Construction of mechanical joints or fastening of parts shall prevent turning if turning can result in movement of internal wiring or components. Frictional contact alone between parts shall not be used to prevent turning. Parts in a brush and slip-ring arrangement, such as the front of a device intended to be rotated regardless of the orientation of the supply receptacle, shall not involve the movement of internal wiring or components.

7.3.1.2 Screws used to mount components shall be provided with a means to reduce the likelihood of loosening.

7.3.2 Adhesives

7.3.2.1 An adhesive, glue, or ultrasonic or chemical bonding that is relied upon to hold together parts of an enclosure shall be evaluated by the mechanical tests of this Standard.

7.4 Corrosion protection

7.4.1 Iron or steel, other than stainless steel, shall be protected from corrosion by painting, coating, or plating. Non-plated iron or steel alloys may be used for lead wires that are part of a neon lamp.

7.5 Current-carrying parts

7.5.1 Current-carrying parts shall be copper, copper alloy, or aluminum unless otherwise specified in this Standard.

7.5.2 Stainless steel is acceptable for current-carrying parts not subject to arcing.

7.5.3 Iron or steel, other than stainless steel, may be used for lead wires that are part of a neon lamp.

7.6 Plug blades

7.6.1 Current-carrying parts shall be copper or copper alloy unless otherwise specified in this Standard.

7.6.2 Plug blade shall conform to the dimensional requirements as specified in Figure 2. If the plug blades employ a folded blade construction, the blades shall also conform to Figure 3.

7.6.3 Plug blades shall comply with the plug blade secureness test of Clause 10.2 and, if applicable, with the folded blade compression test of Clause 10.3.

7.7 Plug face dimensions

7.7.1 The minimum plug face dimensions shall be in accordance with Figure 5 or with the plug blade accessibility test of Clause 8.4.

7.7.2 A nightlight shall be of such dimensions that, when plugged into an outlet of a duplex receptacle, it shall either:

- (a) sufficiently cover the remaining outlet of the duplex receptacle to render it unusable, or
- (b) leave the remaining outlet completely open such that an attachment plug can be fully inserted.

Unless otherwise restricted by instructions on the packaging, any orientation of the nightlight that allows for compliance with (a) or (b) shall be considered when determining compliance with this clause. The dimensions for a duplex receptacle are shown in Figure 4 and those for an attachment plug in Figure 5.

7.7.3 A device shall not be provided with a means for being permanently mounted to a duplex receptacle face.

7.7.4 A plug face provided with a rotational mechanism to permit adjustable positioning of the device after insertion into the duplex receptacle shall comply with the torque test of Clause 11.11 and the rotational endurance test of Clause 11.12.

7.8 Polarization and identification

7.8.1 A device provided with a relampable candelabra screwshell lampholder shall be polarized. The plug blades shall comply with the dimensions of either Figure 2 or 3. The lampholder screw-shell shall be connected to the grounded supply conductor (such as the wide blade of the attachment plug).

7.8.2 A device that includes live parts that may become accessible during normal operation or user maintenance and is provided with a switch shall be polarized. The plug blades shall comply with the dimensions of either Figure 2 or 3, and the switch shall interrupt the ungrounded supply conductor (the narrow blade of the attachment plug).

7.9 Switching mechanisms

7.9.1 A switching mechanism shall comply with the switching mechanism tests of Clause 10.1. A component switch with a load rating that is equal to or greater than the load intended in this application is not required to be tested.

7.9.2 When a manual switching mechanism is operated as in actual service, the rate of motion of the contactor shall not be subject to control by the operator at the point of break.

7.9.3 A removable switch knob shall not expose live parts when removed in accordance with Clause 8.2.

7.10 Lampholder

7.10.1 A device intended for use with screw-base lamps shall be the E-12 candelabra size only.

7.10.2 A screwshell shall be tested with GO and NOT GO gauges made in accordance with NEMA ANSLG C81.63a. A skeleton-type lampholder shall provide an equivalent mechanical engagement. A skeleton-type of construction shall make electrical contact with at least two threads of the threaded lamp base. An equivalent mechanical construction generally consists of one or more narrow strips of metal secured to a molded, threaded body of insulating material. The strip generally extends the length, and conforms to the shape, of the molded threads.

7.10.3 A device incorporating a replaceable lamp shall comply with the lampholder and lamp base accessibility tests of Clause 9.2.

7.10.4 A device using a replaceable lamp shall comply with the lamp cavity separation test specified in Clause 10.5.

7.10.5 The minimum thickness of the candelabra base screw shell shall be:

- (a) 0.25 mm (0.010 in) for copper-alloy; or
- (b) 0.33 mm (0.013 in) for aluminum.

7.11 Wiring and terminal connections

7.11.1 A soldered connection shall be made mechanically secure before soldering by one of the following acceptable methods:

- (a) twisting of conductors together;
- (b) insertion of a bare conductor through a hole in a flat terminal;
- (c) insertion of a bare conductor straight into a terminal sleeve; and
- (d) wrapping at least halfway (180 degrees) around a terminal.

7.11.2 A printed-wiring board connection need not be mechanically secure if an automatic soldering operation is employed.

7.11.3 A live part shall be secured by means other than friction alone so that it cannot be turned relative to the surface on which it is mounted in a way that can reduce the spacing of the live part to another part.

7.11.4 Two live parts shall be joined by brazing, soldering, or crimping. Two parts may be held together by a fit where the parts are wedged into a molded slot of the enclosure. The pad contact of an electroluminescent panel may be joined to another live part by a fit where the two parts are held together by the enclosure.

7.12 Internal wiring

7.12.1 Insulated wire shall be suitable for the temperature and voltage encountered.

7.12.2 Conductors shall be not smaller than 18 AWG. However, conductors as small as 24 AWG may be used where the wire is selected in relation to the maximum current during normal operating conditions, and the time and level of the current flowing during fault conditions do not result in a risk of fire, in conjunction with the following conditions:

- (a) The wire is completely enclosed and not used in a swivel joint.
- (b) The length of the wire is not more than 152 mm (6 in).
- (c) Wiring is connected to the supply via an internal current-limiting device (e.g., lamp current control device, circuit cutouts, energy limited or isolated transformers).

7.12.3 In Canada, a printed-wiring board shall be suitable for the application. The criteria shall include and comply with:

- (a) the bonding of the foil to the substrate for the minimum conductor width and maximum unpierced area in accordance with Annex C.
- (b) the temperatures measured during the temperature test of Clause 9.1 shall be less than the relative thermal index (RTI) rating of the substrate in accordance with CAN/CSA-C22.2 No 0.17.
- (c) the printed-wiring board substrate shall:
 - (1) have a flammability rating of no less than V-2; and
 - (2) be suitable for direct support, in accordance with CAN/CSA-C22.2 No. 0.17.

In the United States, a printed-wiring board shall be suitable for the application. The criteria shall include and comply with:

- (a) the bonding of the foil to the substrate for the minimum conductor width and maximum unpierced area in accordance with UL 796;
- (b) the temperatures measured in the temperature test of Clause 9.1 shall be less than the relative thermal index (RTI) rating of the substrate in accordance with UL 746C;
- (c) the printed-wiring board substrate shall:

- (1) have a flammability rating of no less than V-2; and
- (2) be suitable for direct support in accordance with UL 746C.

7.13 Spacing of conductive parts

7.13.1 Spacing of conductive parts through air and over surface of insulating materials shall comply with the minimum spacing requirements in Table 3 for:

- (a) uninsulated live parts of opposite polarity; and
- (b) an uninsulated live part and a non-current-carrying metal part that may be grounded or a metal part exposed to contact by persons.

7.13.2 With reference to Clause 7.13.1, the requirement does not apply when an insulating barrier or liner is used. In lieu of the spacing required, it shall be:

- (a) of electrical grade paper not less than 0.3 mm (0.011 in) thick;
- (b) of polyester film not less than 0.25 mm (0.01 in) thick; or
- (c) capable of withstanding the dielectric voltage-withstand test of Clause 8.3.

7.13.3 A complete device shall comply with the dielectric voltage-withstand test of Clause 8.3.

7.13.4 With reference to Clause 7.13.1, the requirement does not apply at the body of a neon light if, when the lead wires are short-circuited at the base of the light, the series resistor does not operate in excess of its nominal rating.

7.13.5 In Canada, the spacing between uninsulated live parts of opposite polarity on a printed-wiring board may be less than specified in Table 3 when a printed wiring board is conformally coated with material that complies with the conformal-coating requirements specified in Annex C.

In United States, the spacing between uninsulated live parts of opposite polarity on a printed-wiring board may be less than specified in Table 3 when a printed wiring board is conformally coated with material that complies with the conformal-coating requirements specified in UL 746C.

7.13.6 In Canada, the spacing between uninsulated live parts of opposite polarity on a printed-wiring board may be less than as specified in Table 3 when a printed wiring board complies with clearances and creepage specified in IEC 60664-1 for overvoltage category 2 and:

- (a) for pollution degree 1 for conformally coated printed-wiring boards; or
- (b) for pollution degree 2 for uncoated printed-wiring boards.

In the United States, the spacing between uninsulated live parts of opposite polarity on a printed-wiring board may be less than as specified in Table 3 when a printed wiring board complies with clearances and creepage specified in UL 840.