



UL 497

Underwriters Laboratories Inc. Standard for Safety

Protectors for Paired- Conductor Communications Circuits



Documents
Document Sharing Hub

*UL COPYRIGHTED MATERIAL –
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR
DISTRIBUTION WITHOUT PERMISSION FROM UL*



Documents
Document Sharing Hub

Underwriters Laboratories Inc. (UL)
333 Pfingsten Road
Northbrook, IL 60062-2096

UL Standard for Safety for Protectors for Paired-Conductor Communications Circuits, UL 497

Seventh Edition, Dated April 25, 2001

Revisions: This Standard contains revisions through and including April 9, 2009.

Summary of Topics

This revision is being issued to reaffirm approval of UL 497 as an American National Standard. No changes in requirements are involved.

UL Standards for Safety are developed and maintained in the Standard Generalized Markup Language (SGML). SGML -- an international standard (ISO 8879-1986) -- is a descriptive markup language that describes a document's structure and purpose, rather than its physical appearance on a page. Due to formatting differences resulting from the use of UL's new electronic publishing system, please note that additional pages (on which no requirements have been changed) may be included in revision pages due to relocation of existing text and reformatting of the Standard.

The revisions are substantially in accordance with UL's Proposal(s) on this subject dated January 30, 2009.

The revisions dated April 9, 2009 include a reprinted title page (page1) for this Standard.

As indicated on the title page (page 1), this UL Standard for Safety is an American National Standard. Attention is directed to the note on the title page of this Standard outlining the procedures to be followed to retain the approved text of this ANSI/UL Standard.

The UL Foreword is no longer located within the UL Standard. For information concerning the use and application of the requirements contained in this Standard, the current version of the UL Foreword is located on ULStandardsInfoNet at: <http://ulstandardsinfo.net/ulforeword.html>

The master for this Standard at UL's Northbrook Office is the official document insofar as it relates to a UL service and the compliance of a product with respect to the requirements for that product and service, or if there are questions regarding the accuracy of this Standard.

UL's Standards for Safety are copyrighted by UL. Neither a printed copy of a Standard, nor the distribution diskette for a Standard-on-Diskette and the file for the Standard on the distribution diskette should be altered in any way. All of UL's Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of UL.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of UL.

Revisions of UL Standards for Safety are issued from time to time. A UL Standard for Safety is current only if it incorporates the most recently adopted revisions.

UL provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

UL COPYRIGHTED MATERIAL –
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR
DISTRIBUTION WITHOUT PERMISSION FROM  **Documents**
Document Sharing Hub

In no event will UL be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if UL or an authorized UL representative has been advised of the possibility of such damage. In no event shall UL's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

UL will attempt to answer support requests concerning electronic versions of its Standards. However, this support service is offered on a reasonable efforts basis only, and UL may not be able to resolve every support request. UL supports the electronic versions of its Standards only if they are used under the conditions and operating systems for which it is intended. UL's support policies may change from time-to-time without notification.

UL reserves the right to change the format, presentation, file types and formats, delivery methods and formats, and the like of both its printed and electronic Standards without prior notice.

Purchasers of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold UL harmless from and against any loss, expense, liability, damage, claim, or judgement (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

If a single-user version electronic Standard was purchased, one copy of this Standard may be stored on the hard disk of a single personal computer, or on a single LAN file-server or the permanent storage device of a multiple-user computer in such a manner that this Standard may only be accessed by one user at a time and for which there is no possibility of multiple concurrent access.

If a multiple-user version electronic Standard was purchased, one copy of the Standard may be stored on a single LAN file-server, or on the permanent storage device of a multiple-user computer, or on an Intranet server. The number of concurrent users shall not exceed the number of users authorized.

Electronic Standards are intended for on-line use, such as for viewing the requirements of a Standard, conducting a word search, and the like. Only one copy of the Standard may be printed from each single-user version of an electronic Standard. Only one copy of the Standard may be printed for each authorized user of a multiple-user version of an electronic Standard. Because of differences in the computer/software/printer setup used by UL and those of electronic Standards purchasers, the printed copy obtained by a purchaser may not look exactly like the on-line screen view or the printed Standard.

An employee of an organization purchasing a UL Standard can make a copy of the page or pages being viewed for their own fair and/or practical internal use.

The requirements in this Standard are now in effect, except for those paragraphs, sections, tables, figures, and/or other elements of the Standard having future effective dates as indicated in the note following the affected item. The prior text for requirements that have been revised and that have a future effective date are located after the Standard, and are preceded by a "SUPERSEDED REQUIREMENTS" notice.

New product submittals made prior to a specified future effective date will be judged under all of the requirements in this Standard including those requirements with a specified future effective date, unless the applicant specifically requests that the product be judged under the current requirements. However, if the applicant elects this option, it should be noted that compliance with all the requirements in this Standard will be required as a condition of continued Listing, Recognition, and Follow-Up Services after the effective date, and understanding of this should be signified in writing.

Copyright © 2009 Underwriters Laboratories Inc.

UL COPYRIGHTED MATERIAL –
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR
DISTRIBUTION WITHOUT PERMISSION FROM  Documents
Document Sharing Hub

This Standard consists of pages dated as shown in the following checklist:

Page	Date
1	April 9, 2009
2-3	June 14, 2004
4-5	April 25, 2001
6-7	June 14, 2004
8-10	April 25, 2001
11-13	June 14, 2004
14-27	April 25, 2001
28	May 21, 2001
29	April 25, 2001
30	May 21, 2001
31-44	April 25, 2001
45	May 21, 2001
46-48	April 25, 2001

No Text on This Page

**UL COPYRIGHTED MATERIAL –
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR
DISTRIBUTION WITHOUT PERMISSION FROM UL**



Documents

Document Sharing Hub

APRIL 25, 2001
(Title Page Reprinted: April 9, 2009)



ANSI/UL 497-2004 (R2009)

1

UL 497

Standard for Protectors for Paired-Conductor Communications Circuits

The first – fourth editions were titled Protectors for Communication Circuits. The fifth edition was titled Protectors for Paired Conductor Communication Circuits.

First Edition – March, 1953
Second Edition – November, 1965
Third Edition – February, 1971
Fourth Edition – December, 1978
Fifth Edition – February, 1991
Sixth Edition – July, 1995

Seventh Edition

April 25, 2001

This ANSI/UL Standard for Safety consists of the Seventh Edition including revisions through April 9, 2009.

The most recent designation of ANSI/UL 497 as a Reaffirmed American National Standard (ANS) occurred on April 9, 2009. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, Title Page, or effective date information.

Comments or proposals for revisions on any part of the Standard may be submitted to UL at any time. Proposals should be submitted via a Proposal Request in UL's On-Line Collaborative Standards Development System (CSDS) at <http://csds.ul.com>.

UL's Standards for Safety are copyrighted by UL. Neither a printed nor electronic copy of a Standard should be altered in any way. All of UL's Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of UL.

COPYRIGHT © 2009 UNDERWRITERS LABORATORIES INC.

**UL COPYRIGHTED MATERIAL –
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR
DISTRIBUTION WITHOUT PERMISSION FROM UL**



Documents
Document Sharing Hub

No Text on This Page

*UL COPYRIGHTED MATERIAL –
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR
DISTRIBUTION WITHOUT PERMISSION FROM UL*



Documents

Document Sharing Hub

CONTENTS

INTRODUCTION

1 Scope	7
2 General	8
2.1 Components	8
2.2 Units of measurement	8
2.3 Undated references	8
3 Glossary	8

CONSTRUCTION

4 General	10
5 Enclosures	11
5.1 General	11
5.2 Sheet metal	11
5.3 Nonmetallic	13
5.4 Arrester well sizes	13
6 Protection Against Corrosion	14
6.1 General	14
6.2 Outdoor use	15
6.3 Grommets	15
7 Field-Wiring Connections	15
7.1 General	15
7.2 Field-wiring terminals	15
7.3 Field-wiring connections (appliqué units)	16
7.4 Field-wiring leads and cables	17
7.5 Field-wiring terminals accessible to users	17
8 Components	18
8.1 General	18
8.2 Arrester assemblies	18
8.3 Electrical insulation material	18
9 Spacings	19
10 Fuses	19

PERFORMANCE

11 General	20
12 Line Fuse Current-Carrying Capacity Tests	21
13 Line Fuse Overload Test	22
14 Line Fuse Short-Circuit Test	22
15 Instrument Fuse Limited Current Tests	23
16 Breakdown Voltage Measurement Test	23
17 Impulse Sparkover Voltage Measurement Test	24
18 Limited Short-Circuit Current Test	25
19 Abnormal Operation Test	27
20 Endurance Conditioning Test	28
21 Induced Low-Current Test	28
22 Sneak Current Test	29

UL COPYRIGHTED MATERIAL –
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR
DISTRIBUTION WITHOUT PERMISSION FROM



Documents

Document Sharing Hub

23	Gas Tube Arrester Vent Test	30
24	Distortion Test	30
25	Flame Test	30
26	Ultraviolet Light and Water Exposure	31
27	Low Temperature Drop	32
28	Rubber Materials Tensile Strength and Elongation Tests	32
29	Air Oven Aging Test	33
30	Ozone Exposure Test	33
31	Indoor Corrosion Test	34
31.1	General	34
31.2	Hydrogen sulfide exposure	34
31.3	Sulfur dioxide-carbon dioxide	34
32	Outdoor Corrosion Test	34
32.1	General	34
32.2	Hydrogen sulfide exposure	35
32.3	Sulfur dioxide-carbon dioxide exposure	35
32.4	Salt spray exposure	35
33	Jarring Test	35
34	Water Spray Test	36
35	Drop Test	39
36	Impact Test (Polymeric Enclosures)	39
37	Cover Replacement Test	40
38	Strain Relief Test	40
39	Replacement Arresters Installation Test	40
40	Appliqué Assemblies Installation Test	40
41	Dielectric Voltage-Withstand Test	41

MANUFACTURING AND PRODUCTION-LINE TESTS

42	Gas Tube Seal Test Program	42
42.1	General	42
42.2	Breakdown voltage measurements – gas tube seal test program	44
42.3	Mechanical stress test	44
42.4	Thermal aging	44
42.5	Thermal shock	44
42.6	Service life	45
42.7	Over-pressure leak test	45
43	General	46
44	Breakdown Voltage Test	46

MARKING

45	General	46
----	---------------	----

INSTALLATION INSTRUCTIONS

46	General	47
----	---------------	----

No Text on This Page

*UL COPYRIGHTED MATERIAL –
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR
DISTRIBUTION WITHOUT PERMISSION FROM UL*



Documents

Document Sharing Hub

This page intentionally left blank.

*UL COPYRIGHTED MATERIAL –
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR
DISTRIBUTION WITHOUT PERMISSION FROM UL*



Documents

Document Sharing Hub

INTRODUCTION

1 Scope

1.1 These requirements cover protectors for paired-conductor communications circuits to be used in accordance with Article 800 of the National Electrical Code, NFPA 70.

1.2 As covered by these requirements, a communications circuit protector consists of single- and multiple-pair air gap arresters, gas tube arresters, or solid state arresters, with or without fuses or other voltage-limiting devices. A circuit protector is intended to protect equipment, wiring, and personnel against the effects of excessive potentials and currents in telephone lines caused by lightning, contacts with power conductors, power induction, and rises in ground potential.

1.3 This standard does not cover the following:

- a) Lightning protective devices for the protection of secondary distribution wiring systems and equipment.
- b) Antenna discharge units for radio- and television-receiving appliances.
- c) Lightning conductor and air terminals for connection of lightning rods for building protection.
- d) Protectors for fire alarm signaling circuits that are covered by the Standard for Protectors for Data Communications and Fire-Alarm Circuits, UL 497B.
- e) Secondary Protectors for Communications Circuits, UL 497A.
- f) Transient Voltage Surge Suppressors, UL 1449.

1.4 A product that contains features, characteristics, components, materials, or systems new or different from those covered by the requirements in this standard, and that involves a risk of fire or of electric shock or injury to persons shall be evaluated using appropriate additional component and end-product requirements to maintain the level of safety as originally anticipated by the intent of this standard. A product whose features, characteristics, components, materials, or systems conflict with specific requirements or provisions of this standard does not comply with this standard. Revision of requirements shall be proposed and adopted in conformance with the methods employed for development, revision, and implementation of this standard.

2 General

2.1 Components

2.1.1 Except as indicated in 2.1.2, a component of a product covered by this standard shall comply with the requirements for that component.

2.1.2 A component is not required to comply with a specific requirement that:

- a) Involves a feature or characteristic not required in the application of the component in the product covered by this standard, or
- b) Is superseded by a requirement in this standard.

2.1.3 A component shall be used in accordance with its rating established for the intended conditions of use.

2.1.4 Specific components are incomplete in construction features or restricted in performance capabilities. Such components are intended for use only under limited conditions, such as certain temperatures not exceeding specified limits, and shall be used only under those specific conditions.

2.2 Units of measurement

2.2.1 Values stated without parentheses are the requirement. Values in parentheses are explanatory or approximate information.

2.2.2 Unless otherwise indicated, all voltage and current values mentioned in this standard are root-mean-square (rms).

2.3 Undated references

2.3.1 Any undated reference to a code or standard appearing in the requirements of this standard shall be interpreted as referring to the latest edition of that code or standard.

3 Glossary

3.1 For the purpose of this standard the following definitions apply.

3.2 **APPLIQUÉ ARRESTER ASSEMBLY** – An assembly containing two 2-electrode or one 3-electrode gas tube arresters intended for factory or field connection on a protector block across a pair of carbon arresters. It is intended to reduce maintenance of carbon arresters by discharging lightning-induced voltages that can cause deterioration of carbon arresters. An appliqué arrester may be constructed to shunt the telephone circuit to earth ground or remove itself from the telephone circuit by fusing open, thus permitting operation of parallel arresters during sustained abnormal line voltage.

3.3 **ARRESTER** – An overvoltage component or assembly of components which permits current flow through it when a designed voltage limit is reached. The arrester may consist of a spark gap, gas tube, solid-state component, or the like, coupled with other hardware which serves to support, position, and align the current-carrying components that make up the arrester.

3.4 **ARRESTER RATING** – The breakdown voltage rating specified by the manufacturer.

3.5 DIRECT CURRENT (DC) BREAKDOWN VOLTAGE – The voltage at which an arrester changes from non-conduction to conduction when the DC potential is increased at a rate not greater than 2000 volts per second.

3.6 FUSE, INSTRUMENT (FUSE, SNEAK CURRENT) – A fuse connected in series between the equipment side of an arrester and the telephone equipment that is intended to limit "sneak currents."

3.7 FUSE, LINE – A fuse connected in series between a telephone entrance conductor and an arrester and the telephone equipment that is intended to open during a sustained power fault and prevent the protector and ground wire from overheating. The equipment side of the fuse is connected to an arrester.

3.8 FUSE WIRE – A conductor inserted in the telephone outside plant (OSP) if fuseless protectors are installed. The fuse wire is inserted into the connections of the telephone distribution plant between the telephone wire on the pole and the aerial drop wire leading to the building protector.

3.9 FUSIBLE ELEMENT – A portion of an arrester assembly composed of a eutectic alloy that melts on occurrence of a sustained fault, such as a power line contact fault, and permanently shorts the arrester to ground. Other mechanisms that operate and provide a short-circuit mode are also considered fusible elements.

3.10 GAS TUBE SURGE ARRESTER – A gap or series of gaps in an enclosed discharge medium, other than air at atmospheric pressure, designed to protect apparatus or personnel or both from high transient voltages.

3.11 GLOW MODE – The conductive mode of a gas arrester that exists after breakdown when the circuit impedance limits the current to a value less than the glow-to-arc transition current. In the glow mode the gas in the arrester is not completely ionized and the voltage across the arrester is greater than the arc voltage but less than the breakdown voltage.

3.12 HEAT COIL – A protection device that is used to detect low current fault conditions that flow through the protector to the equipment side when the abnormal voltage is insufficient to cause the overvoltage device to shunt the abnormal current to ground. It is comprised of a small gauge wire wound on a metallic bobbin with a shorting pin. When the coil is heated above a predetermined temperature and melts the eutectic alloy holding the pin in position, it grounds or opens the circuit.

3.13 LINE CONDUCTOR – A conductor that terminates on the outside plant or field side of the protector.

3.14 PROTECTOR, FUSED – A protector containing arresters and line fuses.

3.15 PROTECTOR, FUSELESS – A protector containing arresters, but no line fuses.

3.16 PROTECTOR, MULTIPLE PAIR – A protector intended for connection of more than one telephone circuit.

3.17 PROTECTOR, SINGLE PAIR – A protector intended for connection of only one telephone circuit.

3.18 SHORT-CIRCUIT MODE – A resulting mode whereby the voltage across the line contact and ground contact point of a protector assembly will not exceed 50 volts when subjected to the DC breakdown and surge voltage measurement procedure described in this standard.

3.19 SNEAK CURRENT – An abnormal current on a telephone conductor that is not sufficient to open a fuse wire or line fuse and that is not driven by a voltage that is high enough to cause an arrester to operate.

3.20 STATION CONDUCTOR – A conductor that terminates on the inside plant or house side of the protector.

CONSTRUCTION

4 General

4.1 A communications circuit protector shall be constructed to withstand, without damage, its intended installation and use and shall comply with the performance requirements specified in Sections 11 – 44.

4.2 A fuseless protector shall consist of an assembly comprising:

- a) An insulating base containing two or more arresters or the equivalent;
- b) Provision for connecting one or more pairs of telephone line conductors and a corresponding number of station conductors; and
- c) Provision for connecting at least one grounding conductor.

An arrester shall be connected between each line conductor and ground. The connection or connections for the grounding conductor shall be conductively connected to the ground electrodes of the several arresters. A cover may be provided over the assembly.

4.3 A fused protector shall consist of an assembly comprising:

- a) An insulating base containing two or more arresters or the equivalent;
- b) Provision for mounting two or more line fuses;
- c) Provision for connecting one or more pairs of telephone line conductors and a corresponding number of station conductors; and
- d) Provision for connecting at least one grounding conductor.

The fuses shall be mounted so that one fuse is connected in series between each incoming line termination and the corresponding station termination. The connection or connections for the grounding conductor or conductors shall be conductively connected to the ground electrodes of the several arresters. The arresters shall be connected to the station termination ends of the fuses. A cover may be provided over the assembly.

4.4 An arrester shall not have provision for adjustment of the electrode gap.

5 Enclosures

5.1 General

5.1.1 An enclosure for protectors shall have the strength and rigidity to resist total or partial collapse with attendant reduction of spacings, loosening or displacement of parts, or other conditions that could impair the operation of the product and increase the risk of fire, electric shock, or injury to persons.

5.1.2 Enclosures for individual components, outer enclosures, and combinations of the two are considered in determining compliance with 5.1.1.

5.1.3 Protector enclosures shall have provision for mounting.

5.1.4 A protector intended for outdoor use shall be provided with a watertight cover or enclosure.

5.2 Sheet metal

5.2.1 The thickness of sheet metal used for an enclosure of a protector shall not be less than the applicable value specified in Table 5.1 or 5.2.

Exception: Sheet metal of lesser thickness is not prohibited from being used when, considering the shape, size, and function of the enclosure, it is determined to provide equivalent mechanical strength.

Table 5.1
Minimum thickness of sheet metal for electrical enclosures – carbon steel or stainless steel

Table 5.1 revised June 14, 2004

Without supporting frame ^a		With supporting frame or equivalent reinforcing ^a		Minimum thickness	
Maximum width, ^b	Maximum length, ^c	Maximum width, ^b	Maximum length, ^c	Uncoated,	Metal coated,
inches (cm)	inches (cm)	inches (cm)	inches (cm)	inches (mm) [MSG]	inches (mm) [GSG]
4.0 (10.2)	Not limited	6.25 (15.9)	Not limited	0.020 (0.51)	0.023 (0.58)
4.75 (12.1)	5.75 (14.6)	6.75 (17.1)	8.25 (21.0)	[24] [24]	
6.0 (15.2)	Not limited	9.5 (24.1)	Not limited	0.026 (0.66)	0.029 (0.74)
7.0 (17.8)	8.75 (22.2)	10.0 (25.4)	12.5 (31.8)	[22] [22]	
8.0 (20.3)	Not limited	12.0 (30.5)	Not limited	0.032 (0.81)	0.034 (0.86)
9.0 (22.9)	11.5 (29.2)	13.0 (33.0)	16.0 (40.6)	[20] [20]	
12.5 (31.8)	Not limited	19.5 (49.5)	Not limited	0.042 (1.07)	0.045 (1.14)
14.0 (35.6)	18.0 (45.7)	21.0 (53.3)	25.0 (63.5)	[18] [18]	
18.0 (45.7)	Not limited	27.0 (68.6)	Not limited	0.053 (1.35)	0.056 (1.42)
20.0 (50.8)	25.0 (63.5)	29.0 (73.7)	36.0 (91.4)	[16] [16]	
22.0 (55.9)	Not limited	33.0 (83.8)	Not limited	0.060 (1.52)	0.063 (1.60)
25.0 (63.5)	31.0 (78.7)	35.0 (88.9)	43.0 (109.2)	[15] [15]	
25.0 (63.5)	Not limited	39.0 (99.1)	Not limited	0.067 (1.70)	0.070 (1.78)
29.0 (73.7)	36.0 (91.4)	41.0 (104.1)	51.0 (129.5)	[14] [14]	
33.0 (83.8)	Not limited	51.0 (129.5)	Not limited	0.080 (2.03)	0.084 (2.13)
38.0 (96.5)	47.0 (119.4)	54.0 (137.2)	66.0 (167.6)	[13] [13]	
42.0 (106.7)	Not limited	64.0 (162.6)	Not limited	0.093 (2.36)	0.097 (2.46)

UL COPYRIGHTED MATERIAL –
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR
DISTRIBUTION WITHOUT PERMISSION FROM UL

Table 5.1 Continued on Next Page



Documents
Document Sharing Hub